RENOVATION WORK FOR PROPOSED GYM ROOM AT 3RD FLOOR ADMINISTRATIVE OFFICE BUILDING, **GANDHINAGAR BILL OF QUANTITIES (NOT TO BE FILLED BY THE BIDDERS)** SN Description of item Qy. Unit Rate/ Rate/Unit Total Unit in in Words Amount **Figure** Providing and fixing Laminated Wooden flooring with AC4 grade (12|55) sqm mm thk) as directed on existing surface of approved make, quality, shade, having high pressure laminate surface of 0.3 mm thick with surface guard care material of high density fibre board, flooring planks having click joint system (Tongue and groove joint) Joint sealing with wax as per manufactures specifications, properly finishing the exposed edges and T moulding provided at the junction at laminated flooring and vitrified tiles, including skirting, corner profile, door profile complete in all aspects, as directed by the Engineer/Architect. (Basic rate of laminated flooring: Rs. 1800/- per Sq.mt.). The rate should include leveling of existing floor with cement sand mortar and cement slurry. Brands are . Action 'TESA' Armstrong, Kahr, Ego, Vista Providing and Fixing of Amstrong Mineral Fibre Acoustical Suspended 55 ceilling system with FINE FISSURED (MICRO LOCK) EDGE TILES With Armstrong Silhouette Exposed Grid. Using Silhouette Grid with Fine Fissured microlook Edge Tiles. With necessary Angles at junctions as per company specifications as directed complete. Rate includes necessary cut outs for A/C Grills, diffusers light fixtures complete as directed. Cutout for light and Diffusers will be deducted from the payable area. After completion of work, certificate from Company to be obtained and submitted with bill that work is carried out as per their specifications Providing and painting walls, with plastic emulsion paint after preparing 67 sqm the base by removing existing paint/ finish and applying 2-3 coats of putty for leveled plain, smooth surface and applying 2 or more coats of plastic emulsion complete. All work upto G+4 lvl. Providing and applying synthetic enamel paint on steel surface at all 5 sqm heights of required shade and approved make on old work including the scrapping/cleaning and preparation of surfaces for painting, applying primer and putty, with two or more coats of approved first quality enamel. Providing & Fixing of 8 mm thick Mirror polished edge with teak wood 10 sam

TOTAL
RATES ARE INCLUSIVE OF ALL TAXES EXCEPT GST. GST WILL BE PAID EXTRA AS APPLICABLE

beading on 12 mm thick ply.

AS PER ACTUAL