



**SBI- PADAMPUR (NEW PREMISES)  
INTERIOR FURNISHING WORKS  
PRICE BID**

SI No	Item Description	Unit	Qty	Rate in Rs.	Amount in Rs.
1	<b>Single Window Counter (1800x900x750 mm) without Side Credenza</b> Providing and fixing in position 750 mm high single window counter without side credenza. Side Credenza shall be paid in separate item where ever required. SWC shall consist of: a) 19mm thick block board for Top (1800 x 900 mm), Front (1800x750 mm), Two sides and one middle member (each 900x750 mm) b) 400 mm wide Drawer unit having 3 drawers of equal sizes made of 12 mm thick BWP grade ply of approved make with Godrej autolocking push type locks and "C" type SS finish handles. c) Ebco/Godrej make telescopic sliding key board tray. d) All exposed surfaces shall be clad with 1 mm thick high gloss laminate of approved make and shade except edges, which shall be covered with teakwood round and half-round polished beading as directed by the Engineer-in-charge. e) All un-exposed surfaces shall be clad with 0.8 mm thick laminate of approved make and shade. f) Provisions to be made for Corian solid surface work as per the design / direction of Engineer-in-Charge	Each	6		
2	<b>Work-stations:</b>				
a	<b>Work-station for CM (2100x750x750 mm)</b> Work station for BM (2100x750x750) without Side Credenza Providing and fixing work station for Branch Manager with same specification as item no. 1 above (Single Window Counter) but having only one drawer and one cup board in place of three drawers as mentioned in item 1(b). The drawer Should be provided with auto locking Godrej key system.	Each	1		
b	<b>Work-station for Officers (1600x750x750 mm)</b> Work station for BM (2100x750x750) without Side Credenza Providing and fixing work station for Branch Manager with same specification as item no. 1 above (Single Window Counter) but having only one drawer and one cupboard in place of three drawers as mentioned in item 1(b). The drawer should be provided with auto locking Godrej key system.	Each	9		
c	<b>Work station for System room/ Grahak Mitra/ Misc.</b> Providing and fixing continuous work station for system room, with same specification as item no. 1 above (Single Window Counter) but having only one drawer and one cupboard in place of three drawers as mentioned in item 1(b) as directed by Engineer-in-charge. The drawer should be provided with auto locking Godrej key system.	Running Meter	10		
d	<b>Table for Clearing Cell Cum Meeting Room:</b> Providing and fixing conference table as per design and instructions of Engineer-in-charge, the table shall consist of: a) 19mm thick blackboard for Top (900 mm) , stiffened at sides and supports. b) Supported by suitable support every 1.5 meter as per design and instructions of Engineer-in-charge c) All exposed surfaces shall be clad with 4 MM thick polished veneer of approved make and shade except edges, which shall be covered with teakwood round and halfround polished beading as directed by the Engineer-in-charge. d) All un-exposed surfaces shall be clad with 1.0 mm thick s laminate of approved make and shade. e) 8 mm thk. Glass work in the supporting structure as directed.	Running Meter	5		
3	<b>Side Credenza (950X450X750)</b> Providing and fixing in position Side Credenza made of 19mm thick block board (Top: 900 mm x 450 mm) having 1 drawer unit (450 W x 150 H mm) at the top made of 12 mm thick BWP grade ply of approved make complete with Godrej multipurpose drawer locks and "C" type SS finish handles and one cupboard (450 W x 500 H mm) at bottom with telescopic sliding drawers as above with auto closing hinges for the shutters of the cupboards. The unit shall be complete with SS finish "C" type handles with locking arrangement. All exposed surfaces shall be clad with 1 mm thick mirror/matt finished laminates of approved make and shade except edges, which shall be covered with teakwood round and halfround polished beading as directed by the Engineer-in-charge. All un-exposed surfaces shall be clad with 0.8 mm thick laminate of approved make and shade complete in all respect as per the drawing and direction of Engineer-in-charge.	Each	22		

4	<p><b>12 mm thick Glass for Single Window Counter/ Work Station Top and in SWC front</b>  Providing and fixing in position 12 mm thick clear float glass of Modi float / Indo asahi / Saint Gobin over Single Window Counter top up to 1200 / 1350 mm height in arch profile with wooden vertical supports with required etching of SBI emblem &amp; border on the glass as directed and with machine polish finish edges and with teak wood beading and required hard ware fittings / bracket etc to complete the work in all respect. All glasses should be clean, beveled edges and machine cut and machine moulded with provision of half round opening in bottom middle portion of glass. No extra payment will be made on this account. Allowable tolerance for glass thickness is + 0.3 mm. The glass shall be clear float glass and should be approved by the Engineer in Charge. It shall be clear, float transparent and free from cracks, flaws, Bubbles or Vision defects. The float glass shall conform to the IS 14900.</p>	Sqm	50		
5	<p><b>Low Height double skin glazed partition</b>  Supplying, fitting and fixing low height partly glazed double skin partition for specified enclosure, made out of 50.8 mm X 25.4 mm X 2 mm Aluminium Rectangular Tubes (Hindalco Extrusion Section TU512 or equivalent), in combination of 6mm BWP ply + 1mm matt/ mirror finish laminates on both sides and 8 mm glass with necessary beading as per the design and instruction of E-I-C, The bottom member shall be fixed to the R.C.C. floor with wedge bolt and rawl plugs at suitable intervals. All the wooden sections to be treated with anti fungal and anti termite chemical treatment before being used. The visible portion of the framework shall be French polish. The glass shall be fixed with required beading as per approved design and direction of Engineer-in-charge. All materials are to be of approved make, shade and quality. The rate shall include cost of all materials, labour, taxes, T&amp;P, transportation, royalties etc. for complete work.  The glass portion of the partition should be provided with deep etching as directed by the Engineer in charge.</p>	Sqm	75		
6	<p><b>Full height double skin partly glazed partition</b>  Supplying, fitting and fixing full height partly glazed double skin partition for specified enclosure, made out of 50.8 mm X 25.4 mm X 2 mm Aluminium Rectangular Tubes (Hindalco Extrusion Section TU512 or equivalent). The bottom portion i.e. upto 1200mm 6mm BWP ply + 1mm matt finish laminates on both sides, from 1200mm up to 2100mm height 5.5 mm glass with necessary beading, from 2100 upto ceiling level &amp; above same as per bottom portion. The vertical members shall go beyond the false ceiling level and fixed to the soffit of R.C.C. slab/beam along with one extra top member. The bottom member and top member shall be fixed to the R.C.C. floor/roof slab with wedge bolt and rawl plugs at suitable intervals. All the wooden sections to be treated with anti fungal and anti termite chemical treatment before being used. The visible portion of the framework shall be French polish. The glass shall be fixed with required beading as per approved design and direction of Engineer-in-charge. All materials are to be of approved make, shade and quality. The rate shall include cost of all materials, labour, taxes, T&amp;P, transportation, royalties etc. for complete work. The measurement shall be done upto false ceiling level and no extra payment shall be made for framework or for the ply or laminate above the ceiling level.  The glass portion of the partition should be provided with deep etching as directed by the Engineer in charge</p>	Sqm	160		
7	<p><b>Toughned Glass Partition</b>  P&amp;F 12mm thick TOUGHNED glass partition with patch fittings at floor, top and side walls for full height Cabins. The glass shall be saint Gobain/ TATA while patch fittings shall be Godrej/ equiv. A sealant of wacker/ DOW crunning shall be provided in between joint of glass panels.</p>	Sqm	20		
8	<p><b>Doors for full height partition/ SWO Back/Existing Rooms</b>  Providing and fixing partly glazed flush door matching with glazed wooden partition made out of 50mm x 150mm IInd class hard wood bottom &amp; top rail, 50mm x 100mm styles, 50mm x 200mm lock rail with 1mm laminate cladding, all hardware of SS finish, hydraulic door closure, door stopper, 5.5 mm etched glass along with concealed locking arrangements. All materials to be of approved make, shade and quality. All fixing, fitting works to be done to the satisfaction of Architect/ Bank's Engineer. The rate shall include cost of all materials, labour, taxes, T&amp;P, transportation, royalties etc.</p>	Sqm	20		

9	<b>Storage Cabinet</b> Providing and fixing 750mm high and depth of 450 storage cabinet having minimum 2 filing cabinets etc. made out of BWP block board of 19 mm thick with 1mm thk matt/mirror finished laminate wooden edge leaping and inside clad with 0.8 mm thk laminate of approved make and shade as per drawing and design including all hardware and locking arrangements. The rate shall include cost of all materials, labour, taxes, T&P, transportation, royalties etc.	Sqm	35		
10	<b>Vertical Blind</b> Providing & fixing vertical blinds of approve pattern and shade of Vista Leveller / Mac of 100 mm size including nylon twisted cords, ladder cords, powder coated aluminium top & bottom rail to windows/ partitions etc. cost includes all materials, labour, tax, lead, T&P etc. complete in all respects as per the direction of Bank's Engineer.	Sqm	30		
11	<b>False Ceiling</b>				
a	<b>Gypsum Board False Ceiling</b> Providing and fixing Gypsum board false ceiling made from 12.5 mm thick paper reinforced gypsum board sheets fixed with main frame channels 80mm X 26 mm X0.5 mm at every 450 mm centre to centre with perimeter channel 20mm X 26mmX 0.5 mm, fitting fixing, painting (two coats) all complete.	Sqm	220		
b	<b>Armstrong Ceiling</b> Providing and fixing in true horizontal level 600 mm. X 600 mm. false ceiling system manufactured by M/s. Armstrong World Industries using hot dipped galvanized steel section, exposed surface with pre-coated capping, main tee of size 24 x 32 mm., having 0.27 mm gauge at every 1200 mm. centre to centre maximum and rotary stitched cross tee of size 24 x 27 mm, having 0.27 mm gauge at every 600 mm. c/c. and sub cross tee of size 24 x 27 mm, having 0.25 mm gauge at 1200 mm c/c. and wall angle of size 19 x 19 mm., having 0.35 mm gauge fixed to the periphery of the wall. The above grid is suspended at every 1200mm c/c. in both directions using 2.0 mm. thick pre-straightened GI wire laying FINE FISSURED BUTT Edge ceiling tiles manufactured by M/s. Armstrong World Industries, of size 600mmx600mmx15mm having NRC 0.55, Light reflectance of >84% (WT), thermal conductivity k = 0.052-0.057 W/m0K, Humidity Resistance of 99% , having Fire Performance CLASS O / CLASS 1 (BS 476), surface having 3 coats of white paint with Fine Fissured, back of the tile duly sanded and finished with a coat of protective paint over the formed grid complete.	Sqm	350		
12	<b>Wall Column Panelling</b> Providing wall/ column panelling with AL Section frame work, 12 mm Block board & 1 mm th. Laminates, bending moulding etc. as per design	Sqm	80		
13	<b>Providing , fitting &amp; fixing flexible solid surface ( corian/ dupont) works as specified below:</b> Providing fitting and fixing 6mm thick flexible solid surfaces of approved shades to table top, low height storage unit tops, CNC cut corian jali in column panelling etc or any other places as directed with acrylic epoxy including edge finishing and moulds. Basic cost of solid surface including laying charges and taxed may be Rs 820/- per sqft. The job is to be executed through authorized applicator only as per the bank's specification and requirement. The work should include all necessary materials, accessories and labour. All materials should be approved by the bank. Actual executed plan &/ or elevation area of the surface work shall be measured for finished work.	Sqm	15		
14	P&F fixing 12mm thickness toughned glass door with handles, edge polish etc complete including making holes etc. Cost for handles shall be paid separately. Make: Saint gobain/ TATA/ Modi. Cost includes all accessories like patch fittings, pivots, and	Sqm	8		
15	Providing & fixing floor springs of Haffel/ Dorma/Ozone heavy duty to glass door including cutting the floors and embedding the floor springs and groutung the area by tile adhesive of latecrete matching with tile ccolour etc complete	Each	4		
16	P&F glass door lock at top edge of godrej make for toughened glass with all accessories	Each	4		
17	P&F good quality handles of approved shape and design pattern of make Godrej/ Dorma/ Haffle / equiv to the toughned glass doors	Each	4		
19	P&F frosted film of 3-M/ LG make of approved design pattern, shade and colour to glass panels	Sqm	10		

20	Providing 2.0 mm thick of Birla white wall care putty (Water resistant white cement based putty for concrete mortar walls and ceiling) after removing all loosely adhering material from the wall surface of 1 mm thickness.	Sqm	500		
21	Providing and applying two or more coats of Acrylic Emlusion paint to internal walls, columns, beams ceiling etc. Over a coat of primer as per manufacturer's specification including all labour and materials complete in all floors of approved make and shade.	Sqm	2200		
22	Supply and application of enamel paint of approved make and shade	Sqm	200		
	<b>Total Amount in Rs.</b>				

ies.....