



**SBI- RBO BARGARH (NEW PREMISES)**  
**INTERIOR FURNISHING WORKS**  
**PRICE BID**

SI No	Description of work	Unit	Qty	Rate in Rs.	Amount in Rs.
1	Providing and fixing work station for the Regional Manager as per design and instructions of Engineer-in-charge, without Side Credenza , the work station shall consist of: a) 19mm thick block board for Top (2100 x 900 mm), Front (2100x750 mm), Two sides and one middle member (each 900x750 mm) b) 400 mm wide Drawer unit having 3 drawers of equal sizes made of 12 mm thick BWP grade ply of approved make with locks and "C" type SS finish handles. c) Ebco/Godrej make telescopic sliding key board tray. d) All exposed surfaces shall be clad with 1 MM thick mirror finished laminates of approved make and shade except edges, which shall be covered with teakwood round and half-round polished beading as directed by the Engineer-in-charge. e) All un-exposed surfaces shall be clad with 0.8 mm thick s laminate of approved make and shade. f) Provisions to be made available for Corian solid surface work as per the design / direction of Engineer-in-Charge	Nos	1		
3	Officers table for CM, LBO, Doctor 6'x3' along with side unit of 20"x36": Made with 19mm block board BWP grade in table top, sides with one drawer unit of 450mm x 500deepx750mm with one drawer along with sliding channels and one cup board. Table unit shall have one PVC keyboard tray. The side units shall have one shutter with provision of storage units. All necessary Hardware, locks, handles of approved make shall be provided including foot rest. The table top along with side units shall be finished with 1mm thick laminate with edge teak wood PU polished. Front modesty panel and vertical sides of drawers, side units shall be finished with 1mm thick laminate. Inside surface of table unitS shall be finished with 1mm thick lamiante as approved. Ply: BWR grade Century /Green, and laminate: Marino/ Century/Green as approved. A 2" drop shall be provided on customer side with 8mm ply box and duly finished with same finished with laminate. Edges shall be finished with half round wood lipping on writing desk side and PU polished for smoothness. Drawers shall be finished with lipping polished.	Nos	5		
4	Officers table 5'x2-6" along with side unit of 20"x36": Made with 19mm block board BWP grade in table top, sides with one drawer unit of 450mm x 500deepx750mm with one drawer along with sliding channels and one cup board. Table unit shall have one PVC keyboard tray. The side units shall have one shutter with provision of storage units. All necessary Hardware, locks, handles of approved make shall be provided including foot rest. The table top along with side units shall be finished with 1mm thick laminate with edge teak wood PU polished. Front modesty panle and vertical sides of drawers, side units shall be finished with 1mm thick laminate. Inside surface of table unit shall be finished with 1mm thick laminate as approved . Ply: BWR grade Century / Green and laminate: Merino/ Century as approved. A 2" drop shall be provided on customer side with 8mm ply box and duly finished with same finished with laminate. Edges shall be finished with half round wood lipping on writing desk side and PU polished for smoothness. Drawers shall be finished with lipping polished.	Nos	21		

5	Staff table 4'6"x2'6": with side unit of 18"x36" Made with 19mm block board BWP grade in table top, sides with one drawer unit of 450mm x 500 mm x750mm with one drawer along with sliding channels and one cup board. All other specification shall be same as per Officers table specification.	Nos	8		
6	Server room table: Providing and fixing server room table made of 19mm BWR grade block board as table top with drawer units. The sides shall be 19mm block board. The drawer size shall be 450wide x500mm deep with two verticals of 19mm BB. The drawer shall have telescopic ebco make sliding channels, handles, locks etc. All exposed surface shall be finished with 1mm thick laminate. Table shall have one PVC key board tray of ebco make per 5' running length. All inside surface shall be polished. All edges shall be finished with teak lipping and specially table edge shall be finished with half round teak wood lipping PU Polish. All inside surface shall be finished with 1mm thick laminate of approved shade and colour.	RMT	5		
7	Conf table: 8840x2000x750mm including curved shape as per site condition. Made of 19mm block board BWP grade as a table top to be fixed in a aluminum frame work of 50x50x1mm duly finished with 6mm ply on each face. There shall be double frame Inner (7300x1000x750) and outer frame (7950x1350x750). The table width on each said will be 700 to 750mm. The middle strip shall be depressed by 150mm and all electrical/LAN etc shall be fixed to the running 150mm width strip. The top including depressed sides shall be finished with 4mm thick veneer duly melamine polished. The inspection door shall be provided for maintenance. The exposed vertical surface of frame shall be additionally finished with 4mm thick MDF board to which 1mm laminate shall be provided. The outer edges of the table shall be provided with a vertical drop of 100 mm with 8mm ply and it shall be finished with 4mm thickness veneer duly melamine polished. The edges shall be smoothened.	Nos	1		
8	Corner glass table: providing and fixing corner glass table made with 19mm Block board of box size of 500mmx500mmx500mm duly covered by 1mm thickness laminate on all exposed sides. A 12mm toughened glass top supported with ss stud of 75mm ht shall be provided.	Nos	1		
9	P&F Doctors bed 2'x6'6" with cushion at top made of sal wood / teak wood frame all complete	Nos	1		
10	Providing and fixing in position 12 mm thick clear float glass of Modi float / Indo asahi / Saint Gobain over table top with required etching of SBI emblem & border on the glass as directed and with machine polish finish edges to complete the work in all respect. All glasses should be clean, bevelled edges and machine cut and machine moulded. Allowable tolerance for glass thickness is + 0.3 mm. The glass shall be clear float glass and should be approved by the Engineer in Charge. It shall be clear, float transparent and free from cracks, flaws, Bubbles or Vision defects. The float glass shall conform to the IS 14900.	Sqm	50		
11	Providing and fixing low height partition glazed partition made with aluminum hollow box section of 50mmx25mmx 1.30mm wall thickness fixed with each sides of 6mm thick BWP grade ply and sandwiched with 3mm thickness exterior grade MDF board. The surface shall be finished with 1mm thickness laminate of approved shade (with colour and shade as approved by engineer in charge/ architect (solid/ teak wood / texture premium quality). The partition shall be fixed to floors and walls with screws rigidly. 8mm thick glass shall be provided if necessary and as directed at 3' level duly supported by teak wood lipping PU Polished and as directed at site by engineer in charge.	Sqm	110		

12	Supplying, fitting and fixing full height partly glazed double skin partition for specified enclosure, made out of 50.8 mm X 25.4 mm X 2 mm Aluminium Rectangular Tubes (Hindalco Extrusion Section TU512 or equivalent). The bottom portion i.e. upto 1200mm 6mm BWP ply + 1mm matt finish laminates on both sides, from 1200mm up to 2100mm height 5.5 mm glass with necessary beading, from 2100 upto ceiling level & above same as per bottom portion. The vertical members shall go beyond the false ceiling level and fixed to the soffit of R.C.C. slab/beam along with one extra top member. The bottom member and top member shall be fixed to the R.C.C. floor/roof slab with wedge bolt and rawl plugs at suitable intervals. All the wooden sections to be treated with anti fungal and anti termite chemical treatment before being used. The visible portion of the framework shall be French polish. The glass shall be fixed with required beading as per approved design and direction of Engineer-in-charge. All materials are to be of approved make, shade and quality. The rate shall include cost of all materials, labour, taxes, T&P, transportation, royalties etc. for complete work. The measurement shall be done up to false ceiling level and no extra payment shall be made for framework or for the ply or laminate above the ceiling level. The glass portion of the partition should be provided with frosting (garware/ or equiv) as directed by the Engineer in charge	Sqm	100		
13	P&F 4mm thick solid surface on top edge of low height partitions and its vertical exposed edges with flexible solid surface thickness with approved colour and shaded flexible type including buffing, finishing the smooth surface etc complete. (Preferably width will be 75 to 100mm with round smooth surface.	Sqm	20		
14	Providing and fixing 30mm thickness flush door of Sylvan/ Globe/ century finished with teak wood lipping on all edges , three hinges for each door, one door stopper, one door closer of godrej make, one mrotise lock of godrej make per door etc complete. The both surface shall be finished with 1mm thick laminate of approved shade.	Sqm	12		
15	P&F fixing 12mm thickness toughened glass door with handles, edge polish etc complete including making holes etc. Cost for handles shall be paid separately. Make: Saint gobain/ TATA/ Modi. Cost includes all accessories like patch fittings, pivots, and	Sqm	10		
16	Providing & fixing floor springs of Dorma/Ozone heavy duty to glass door including cutting the floors and embedding the floor springs and grouting the area by tile adhesive of latecrete matching with tile colour etc complete	Nos	2		
17	P&F glass door lock at top edge of godrej make for toughened glass with all accessories	Nos	2		
18	P&F good quality handles of approved shape and design pattern of make Godrej/ Dorma/ Haffle / equiv to the toughened glass doors	Pair	2		
19	P&F 12mm thick Toughened glass partition with patch fittings at floor, top and side walls for full height Cabins. The glass shall be saint Gobain/ TATA while patch fittings shall be Godrej/ equiv. A sealant of wacker/ DOW crunning shall be provided in between joint of glass panels.	Sqm	25		
20	P&F frosted film of 3-M/ LG make of approved design pattern, shade and colour to glass panels	Sqm	30		
21	Storage units 500mm size: Providing and fixing 450 mm deep (Inside clearance) made with 19mm block board on all five sides and 6mm backing ply. Vertical separators shall be provided at each 3' Centres with leaf of each shutter is 18" wide. Ebco/ Hettich make auto closing hinges shall be provided. All inside surface shall be finished with 1mm thick laminate as approved by engineer in charge while exposed surface shall be finished with 4mm thick veneer duly pu polished with basic price of 150 per sqft of veneer.	Sqm	50		

22	P&F vertical blinds of Vista make/ equiv as approved by engineer-in-charge with colour and shade as approved along with all accessories	Sqm	50		
23	Providing and fixing Gypsum false ceiling of India Gypsum / saint gobain make which includes G I perimeter channels of size 0.55mm thick having one flange of 20mm and another flange of 30mm thick and web of 27mm along with perimeter of ceiling etc complete. Putty and painting shall be paid separately	Sqm	120		
24	Modular false ceiling with Armstrong make Rh-95 and Tegular edge 600x600 x15mm as specified by manufacturer. Installation to comprise main runner at 1200 centres fixed to structural outfits. All works shall be executed as per manufacturers specification	Sqm	300		
25	Column panelling made with 12mm ply of BWR grade and sandwiched with 3 mm thick MDF board of exterior grade of Century/ marino/Green. The surface is then laminated with premium quality textured finish bi colour 1mm thick laminate of Marino / Century with shade and colour as approved by architect/ engineer in charge. Ply: BWp grade Century/ SylvaN / Green as approved.	Sqm	40		
26	Wall panelling with 25x25x1.00 mm hollow aluminum box section fixed to the wall and finished with 5.50mm exterior grade MDF boards. The board is finished with 1mm thick laminate of approved shade and colour with PU finish, purchase price of veneer : Rs 175 per sqft of Duro/ century. The aluminum section shall be provided in a grid of 600mmx600mm. The top edge shall be finished with teak wood beading duly PU polished with same veneer as directed.	Sqm	60		
27	Finishing the wall surface with putty of Birla/ Asian. Berger with thickness of 2mm to make the surface in line and level including gyp ceiling. For applying putty in gyp ceiling, uniform thickness of putty will be maintained which may be 2 to 4mm as	Sqm	600		
28	Roller Finishing the wall surface with two or more coat of wall primer followed by two or more coats of acrylic based tractor emulsion paints of Asian or equiv of berger/ ICI/ with approved shade and colour including gyp ceiling.	Sqm	1000		
29	Half Brick work using locally available good quality bricks for UPS room side wall, system room wall etc. with cement mortar of 1:3 (cement: Coarse sand). At every 1m, two nos 6mm bars shall be laid. Rate shall include lifting of materials to 2nd floor, curing etc complete	Sqm	50		
30	Finishing the wall surface with 12 to 15mm thickness plaster in proportion 1:4 (cement: coarse sand) to make the surface truly line and level including scaffolding, curing etc complete. At any level and height)	Sqm	50		
31	P&F 18mm thick granite slab with edge moulding	Sqm	2		
32	Providing and laying 600mm x 600mm nano polished double charged vitrified matt finished tiles of Jonson/ Nitco/ Kajaria/RAK or equivalent make with water absorption less than 0.08% and confirming to IS: 15622 of approved make, in all colours and shades, laid on 20 mm thk. cement mortar 1:4 (1 Cement : 4 Coarse Sand), including grouting the joints with white cement and matching pigment etc. all complete, including cost of all materials, labour, T&P etc. required for the work.	Sqm	100		
	Total amount in Rs.				
	Total amount in words( Rupees.....)				