INDICATIVE PRICE BID

	INTERIOR FURNISHING WORKS AT PALLOM			PREMISES	<u>S)</u>
S.No	Description	Qty	Unit	Rate	Amount
1	Providing and fixing double charged vitrified tiles	Qty	Oilit	Nate	Alliount
•	for the entire banking hall over the exising flooring	140	Sq.m		
	using tile to tile adhesive		- 4		
2	SINGLE WINDOW SYSTEM:				
	Providing and fixing of Single window system				
	without partitions as shown in drawings				
	comprising of each counter size 1500 to 1750 mm				
	& 2500 length or as per layout and 1200 mm				
	height or as per layout with below specifications				
	and provisions.				
	Counter and writing top at front, with counter 1500 to 1750 mm length and 1000 mm width at about				
	750 mm height. The Top shall be fixed with 19mm				
	Plywood (IS 303 marine grade) of approved make				
	with curved bend in front modesty as per drawing				
	and fixed with white corian top of 6mm thick				
	of approved brand. 18mm plywood of approved				
	make for sides and for front shaped support and				
	finished with 1mm laminate of approved color.				
	Front counter support for 750 mm height with 18				
	mm Plywood finished with 1 mm laminate of				
	approved color and shade . Below counter top.				
	Additional 18mm plywood finished with 1mm				
	laminate is fixed to pattern as shown.				
	12 mm thick clear float glass to shape with				
	etching is fixed with SS glazed clips fixed at front				
	(600mm) and sides (450mm) above the				
	counter as shown in the drawing. Modesty fixed with 8mm thick of Aqua Blue shade				
	of saint Gobain glass (or) equivalent fixed 3M				
	stickering suitably at 18mm thick Plywood vertical				
	finished with 1mm laminate				
	The side partitions of the counter , boxing on either side to shape as shown in the drawing with				
	18 mm Plywood of approved make and to be				
	finished with 1 mm thick laminate of approved				
	color from floor level to 1200 mm level at places				
	shown in the drg.				
	Necessary wicket door shutters are to be	8	Rm		
	provided using 18 mm Plywood and finished with				
	1mm laminate of approved color and shape as				
	shown in the drawing				
	One set of 3 drawers about 450 mm width, 712.5				
	mm height and 600mm deep supported with				
	18mm Plywood at bottom, sides and rear.				
	Drawers 3Nos. of equal height made out of				
	12mm thick Plywood for sides, rear, bottom and face of drawers with 18 mm Plywood and finished				
	with 1mm thick laminate of approved color, with				
	necessary lipping, telescopic drawer slides,				
	locking arrangements, 100mm long brush finish				
	S.S. handles, etc. complete. Top most cash				
	drawer should be arranged with provision for				
	denomination with 8mm thk plywood				
				ı	!

	Cash denomination separation to be provided for			
	1 draw unit of the SWO, preferable the top draw			
	with plywood. This draw unit has to be provided			
	with automatic lock.			
	MS Powder coated Telescopic keyboard tray and			
	MS wire manager of 50mm dia of approved			
	quality.			
	Foot rest cum CPU stand of required length			
	with18mm thickness Plywood to shape as shown			
	in the drawing.			
	All concealed faces of plywood finished with one			
	coat of wood preservative paint and exposed			
	faces of steam beach beading polished as per			
	direction of engineer. The inner side of the unit			
	finished with 1mm Laminate. The plywood and			
	corian materials are as approved by Bank.			
	The rate shall include locks, MS powder coated			
	keyboard trays, telescopic drawer slides, 100 mm			
	SS brush finish handle with necessary hardware			
	fittings, etc.			
3	SINGLE WINDOW SYSTEM (With Out Front			
	Glass)	•	D4	
	The same as above specification without front	2	Rmt	
	glass.			
4	LOW HEIGHT PARTITION FOR SINGLE			
-	WINDOW SYSTEM:			
	Providing and fixing of Low height partitions for			
	Single window system of 750 mm height from			
	finished floor level, as per the drawing.			
	Aluminium sections of size 63.5 X 38.1X1.2 mm			
	thk. of INDAL/JINDAL as internal frame structure			
	vertically at about 60 cm centers and 3 Nos			
	Horizontally of the same size of frame at floor			
	level, 750 mm and at 1200 mm level. same size			
	at 370 mm level, fixed in position. 8 mm Plywood			
	on both sides of framework finished with 1 mm			
	laminate of approved color and shade with			
	grooves on both sides. Top of the partition			
	finished with laminate of 1mm thick. The side	35	Sq M	
	portion glazing shall be done with "Blue			
	Laminated / Lacquered transperated glass of			
	12mm thick of approved brand and shall be fixed			
	with 'Doma' (or) equivalent brand 'SS ' 'D'			
	brackets. The curved 12mm thick lacquered			
	transperant toughened glass shall be fixed at			
	front size in between counters as per drawing and			
	shall be fixed suitably with 'SS' brackets.			
	·			
	Partition on rear similar to side partition, but solid			
	partition. One door shutter for each cabin for 675			
	mm width and 1200 mm height, similar to door			
	shutter item.			
5	Custom Made Low Height Partition: for CO			
ا	_			
	Cabin			
	Providing and fixing in position of custom made			
	low height partitions of the height 1500 mm as per			
	shape shown in the drawing.ie. (750mm solid			
	partition and 750mm glass above)			
				1

	Aluminium sections of size 63.5 X 38.1X1.2 mm thk. of INDAL/JINDAL as internal frame structure vertically and 3 nos. horizontally of the same section at floor level, 750mm level and at 1200mm level. Same size at 375 mm level all framed and fixed in position, 8 mm Plywood of approved quality finished with 1mm Laminate with grooves on both sides of approved color and shade. Top of the partition finished with laminate and 12mm thick glass with etching is fixed over the partition with Dorma make (or) Equivalent make 'D' bracket of SS finish of 12mm thick. Alround the partition 75mm thick Dark color laminate is provided as show in the drawing and pattern.	10	Sq M	
6	Custom Made Full Height Solid Partition: Supply and set in position of custom made double skin full height partitions as per shape and size shown in the drawing. Frame Work Detail: Aluminium sections of size 63.5 X 38.1X1.2 mm thk. of INDAL/JINDAL as internal frame structure, vertically at about 60cm centers varied along columns wall ends, junctions of walls, as necessary. Horizontally of the same size of frames at floor level,750 mm, 1500 mm,2100 mm, and roof level. Lining Work: 8 mm Plywood of approved make on both sides of framework from floor level to 6"above false ceiling level, and to be finished with	25	Sq M	
7	1mm laminate of approved colour and shaped on both sides including necessary grooves and steam beach beadings. Measurement for the partition area shall be considered from floor level to false ceiling level only. Full Height Partly Solid & Partly Glazed Partition: Providing and fixing in position of double skin			
	partition, partly paneled and partly glazed as per details shown in the drawing. Frame Work Detail: Aluminium sections of size 63.5 X 38.1X1.2 mm thk. of INDAL/JINDAL as internal frame structure ,vertically at about 60 cm centers varied along columns, wall ends , junctions of walls, as necessary. Horizontally of the same size of frame at floor level, 900 mm,2100 mm, and roof level.	20	Sa M	
	Lining Work: 8 mm plywood of approved make on both sides of framework from floor level to 900 mm level and 2100 mm level to 6" above false ceiling level finished with 1 mm laminate of approved color and shade. Between 900 mm and 2100 mm level, 12 mm thick glass with etching fixed with necessary Dorma (or) equivalent make 'D' bracket of SS finish of 12mm thick. The glass opening 'jamb' portion finished with laminate.	20	Sq M	
	Measurement for the partition area shall be considered from the floor level to false ceiling level only.			

	T=			I
8	Providing and fixing frameless fully glazed 12mm thk toughened float glass fixed with necessary patch fittings (Dorma make) including cutting, making holes, cutouts in the glass of required shape and size to accommodate fittings and fixing the fittings in floors, soffits, jams including necessary fixtures, screws, sealant wherever required and SS cover over patch fittings. Rate shall include necessary etching film / LOGO, approved patch fitting locking systems, 1 pair of 600mm long S. S. (H Shape) Handles of approved make, floor springs, and any necessary hardware items.(DORMA MAKE Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Euro Profile Cylinder - US 10, Handle - TG DIH600 - 32mm dia X 600mm length).	10	Sq M	
9a	Fully Glazed - Fixed Glass Partition - Patch Fitting Providing and fixing of fixed glass partitions with 12mm thick toughened glass using PT Standard fittings like PT 90/PT 92 of Dorma make at the top and bottom including cutting, making holes in glass and fixing the fittings in floors, ceilings etc and making the same good with necessary screws, 3M Vinyl sticker as per approved, colour, design and pattern, sealants etc.complete.	10	Sq M	
9b	Partly Glazed And Partly Paneled Doors. Il class T.W/hard wood. frame of size 75 X 50 mm as per the shape and size given in the drawing. 35 mm thick (finished) flush shutter finished with 1mm laminate on both sides with necessary grooves.8mm thick clear float glass of size 250 X 1400 mm fixed with necessary steam beach beading and etching. DORMA Make or equivalent make hardware fittings like locking arragements,20 mm dia and 300 mm high SS brush steel finish handles, door closer, hinges, tower bolts,etc,. Fixed to the shutters.	5	No	
10	Gypsum Board FALSE CEILING: NOTE:The false ceiling area will be measured in flat area only. Providing and fixing of M/F suspended false ceiling as the detail given in the drawings. With G.I frame work and 12.5 mm tapered gypsum board panels to form grids of 45.7 X 122 cm as per manufactures specification including provision for stepped shaped ceiling for lighting trough comprising			

Frame work of intermediate channels (M.F.T) at 122 cm centers along one direction M/F ceiling section MF5 at 45.7 cm center along other direction. Perimeter channels (MF 6A) along walls alround perimeter side of the ceiling. The intermediate channels suspened from ceiling, through starp hangers 25 X 0.5 mm (MF 8) at 122 cm centers connected to soffit cleats p534 (27 X 37 X 25 X 1.6mm) the cleats connected to ceiling through metal expansion rawl plugs 1/2" dia and 17/16" long with additional perimeter channels (MF 6A) for light fittings, Air conditioners Ducts, vertical drops, offset etc. 12.5mm thick gyp board with tapered edges fixed to underside of suspended grid with 25 mm screws to from grids with 2 coats of plastic emulsion paint of approved color and one coat of putty over a coat primer etc, complete.	140	Sq M		
Providing and fixing BM Table of size 1800 x 850 X 750 mm high to detail as shown in drg. Comprising table top out of 25mm thick Plywood post formed with 1 mm thickness flexy laminate of approved color and brand with both size half rounded edge and another two side edges with 3mm thick band strip. 12Mm thick glass with bevelled edges to be provided for the table top with necessary wire manager. On front and side of drawer finished with 1mm thk laminate and additional 18mm thick Plywood is fixed on front side to pattern with necessary grooves and finished with 1mm thick laminate. Foot rest cum CPU stand of required length with same 18 mm Plywood waxed and finished with varnish of app color and shade MS Powder coated Keyboard tray and 50mm Dia MS wire manager of approved quality. One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thick Plywood and finished with 1mm thick laminate at front side of approved color and shade with necessary lipping, telescopic drawer slides, locking arrangement, 100 mm long brush finish S.S. handles, etc. complete. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. The inside faces of drawer should be waxed and finished with varnish of app color and shade the table modesty shall be fixed with 8mm thick of Aqua blue shade of saint Gobain (or) equivalent toughened glass panel fixed on the 18mm thick to be fixed on front vertical laminated Plywood Board with SS studs.	1	Nos		

Providing table to 450mm, and One unit top 1mm thi brand w the three hung sh Plywood approved lipping, 100 mm ball cate rounded All conce coat of faces of to the sa of unit w color and 750 X 7 Compris Board per of approviding 750 X 7 Compris Board per of approvided 3mm this rounded blue she toughend be fixed with SS see Ton front sid finished MS Pow MS wire One set mm high with 18 II	ide Tables For BM			
Providing 750 X 7 Compris Board po of approrounded 3mm thi rounded blue sh toughene be fixed with SS: On front laminate front sid finished MS Pow MS wire One set mm high with 18 I	Providing and fixing side unit for Manager / BM able to detail as per drg. of size 1500mm x 50mm, 18 mm Plywood for bottom, rear, sides and One intermediate with necessary reeper. The init top shall be 25mm thick Plywood Board with mm thick flexy laminate of approved color and trand with front side half rounded edge and all the three sides with 3mm thick band strip. Side ung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade, including all necessary pping, Box Type hinges, Locking arrangement, 00 mm long S.S brush finish handles, tower bolt, all catch etc, complete. 12 mm glass with edges bunded to be provided for the table top All concealed faces of Plywood finished with one oat of wood preservative paint and exposed aces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved olor and shade.	1	Nos	
All conce coat of faces of satisfact drawer s	Providing and fixing Officer Table of size 1500 x 150 X 750 mm high to detail as shown in drg. Comprising table top out of 25mm thick Plywood Board post formed with 1mm thick flexy laminate of approved color and brand with both side half bounded edge and another two side edges with 1mm thick band strip.12 mm glass with edge ounded to be provided for the table top. Aqua office shade of saint Gobain (or) equivalent oughened glass panel fixed on the 18mm thick to be fixed on front vertical laminated Plywood Board with SS studs. On front and side of drawer finished with 1mm the 1minate and additional 18mm Plywood is fixed on 1minate and additional 18mm Plywood is fixed on 1minate and additional 18mm Plywood is fixed on 1minate with 1mm thick laminate. MS Powder coated Keyboard tray and 50mm Dia 1minate MS wire manager of approved quality. One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 os. of drawers out of which 3 nos. of equal 1minate in 12 mm thick MI concealed faces of Plywood finished with one 12 mm thick MI concealed faces of Plywood finished with one 13 of 14 mm thick of 15 mm beach beading polished to the 15 mm thick of 16 mm thick of 17 mm thick of 18 mm polished with one 18 mm polished to the 18 mm polished be waxed and finished with varnish of 18 mm polished with varnish of 1	2	Nos	

15 Low Level Storage: Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the edges with 3mm thick band strip. Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade. 16 Column Panelling Providing and fixing cladding around the columns to detail as per drwing ocmprising 18mm thick plywood with necessary stiffneron both ways of required nos and finished with 1mm thick laminate of approved colour and shade. The surface has also fixed with 8 mm thick Lacquared glass as per drawing. 8mm thick MDF broad jally work (CNC cutting) of approvd design/pattern finished with white colour high glossy duco paint fixed over laminate surface		Providing and fixing side unit for Cash Officer table to detail as per drg. of size 1200mm x 450mm, 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary reeper. The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip. Side hung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade, including all necessary TW lipping, Box Type hinges, Locking arrangement, 100 mm long S.S brush finish handles, tower bolt, ball catch etc,.complete.12 mm glass with edges rounded to be provided for the table top All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.	6	Nos	
faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade. 16 Column Panelling Providing and fixing cladding around the columns to detail as per drwing ocmprising 18mm thick plywood with necessary stiffneron both ways of required nos and finished with 1mm thick laminate of approved colour and shade. The surface has also fixed with 8 mm thick Lacquared glass as per drawing. 8mm thick MDF broad jally work (CNC cutting) of approvd design/pattern finished with white colour high glossy duco paint fixed over	15	Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip. Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade. All concealed faces of Plywood finished with one	20	Sq M	
Providing and fixing cladding around the columns to detail as per drwing ocmprising 18mm thick plywood with necessary stiffneron both ways of required nos and finished with 1mm thick laminate of approved colour and shade. The surface has also fixed with 8 mm thick Lacquared glass as per drawing. 8mm thick MDF broad jally work (CNC cutting) of approved design/pattern finished with white colour high glossy duco paint fixed over		faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.			
	16	Providing and fixing cladding around the columns to detail as per drwing ocmprising 18mm thick plywood with necessary stiffneron both ways of required nos and finished with 1mm thick laminate of approved colour and shade. The surface has also fixed with 8 mm thick Lacquared glass as per drawing. 8mm thick MDF broad jally work (CNC cutting) of approvd design/pattern finished wiht white colour high glossy duco paint fixed over	15	Sq M	
17 Providing and fixing wll panelling to detail as shown in the drawing with 18mm thick plywood 5 Sq.m finished with 1mm thick laminate 18 Writing Ledge		shown in the drawing with 18mm thick plywood finished with 1mm thick laminate	5	Sq.m	

	Providing and fixing of rectangular writing Desk of size 1200mm to a height of 120cm as per drawing, the vertical support shall be of 4nos finished with 25mm thick plywood finished with post forming with half rounded edge on outer side with 1mm flexy laminate. The top shall be of 18mm Plywood finished with 1mm laminate on both sides and edges finished with circular edge band. The glass top over the plywood circular top shall be of 12mm thick toughened glass to be velled edge/ edge polished and supported by intermediate vertical 12mm thick Plywood, finished with laminate on both side. The compartment shall be 4nos as per drawing. vertical support shall be 230mm height and all edge shall be with edge band of same color. The writing desk shall be fixed on a circular 18mm thick plywood platform and export surface shall be finished with 1mm thick laminate the interior space of platform with 1mm white laminate.	1	Nos	
19	Grahak Mithra Table Grahakmitra Table:Providing and fixing Officer Table of size 1200 x 750 X 750 mm high to detail as shown in drg. Comprising table top out of 25mm thick Plywood post formed with 1mm thick flexy laminate of approved color and brand with both side half rounded edge and another two side edges with 3mm thick band strip.On front and side of drawer finished with 1mm thk laminate and additional 18mm Plywood is fixed on front side to pattern with necessary grooves and finished with 1mm thick laminate.12 mm glass with edges rounded to be provided for the table top. The front fascia of the table to be provided with 12 mm thick glass properly fixed with SS studs.MS Powder coated Keyboard tray and 50mm Dia MS wire manager of approved quality .One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thick plywood.	1	No	
20	All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. The inside faces of drawer should be waxed and finished with varnish of app color and shade Painting banking hall using approved quality ' Asian			
	paint or equivalent two coats after applying putty finish	200	Sq,m	
21	Painting banking hall using approved quality 'Asian paint exterior paint two coats for the out side Providing and fixing back drop behind grahakmitra table	250	Sq.m	
22	and made of 8mm thick acrylic sheet, over Plywood wall panelling finished with approved laminate. The matter shall be clear vinyl printing reverse type and the digital printing shall be done on rear side	5	Sq.m	
23	Providing and fixing good quality Aluminium composite panelling for ATM room and front portion of Bank, at the exterior columns, with white coloured panels.	5	Sq.m	
24	Providing and fixing vertical blinds of approved quality for the windows	5	Sq.m	

25	Providing and fixing antiskid ceramic tiles for the toilets	10	Sq.m	
26	Providing and fixing wall cladding using ceramic tiles Khajaria /Somany or equivalent min price Rs.50/sq.ft	20	Sq.m	
27	Providing and fixing new sanitary fittings European water closet, flush tank cera make or equivalent 1 no. tap, one health faucet etc of approved quality) for each toilet	2	No	
	TOTAL			
	GST @18%			
	Grand Total			