

**STATE BANK OF INDIA
ODAKKALI BRANCH
(EXISTING PREMISES)**

| Name of Work | | INTERIOR RENOVATION WORK OF ODAKKALI BRANCH | | | |
|------------------------------------|--|---|------|------|--------|
| Name and Address of the Contractor | | | | | |
| | Description | Qty | Unit | Rate | Amount |
| 1 | <p>Providig and fixing single window system with below specifications and provisions . Counter and writing top at front, with counter 1500 to 1750mm length and 1000mm width at about 750mm height. The top shall be fixed with 19mm plywood (IS710 marine grade) of approved make with curved bend in front modesty as per drawing and fixed with white corian top of 6mm thick of approved brand. 19mm plywood of approved make for sides and for front shaped support and finished with 1mm laminate of approved colour. 12mm thick clear float galss to shape with etching is fixed with SS glazed clips fixed at front (600mm) and sides (450mm) above the counter as shown in the drawing.</p> <p>One set of 3 drawers of equal height made out of 12 mm thick plywood with 1 mm lamination of approved colour, with necessary lipping. Telescopic drawer slides, locking arrangements, 100mm long brush finish S.S handles etc complete. Top most cash drawer should be arranged with provision for cash denomination separation with 8mm thick plywood. This draw unit has to be provided wih automatic lock. M.S powder coated Telescopic keyboard tray and MS wire manager of 50mm dia of approved quality.Foot rest cum CPU stand of required length with 18mm thickness plywood to shape as shown in the drawing. All concealed faces of plywood finished with two coats of wood preservative paint and exposed faces of steam beach beading polished to the satisfaction of the Engineer. The inner side of the unit finished with 1 mm laminate. The plywood and corain materials are as approved by the Bank. The rate should include locks, MS powder coated keyboard trays, telescopic drawer slides, 100 mm ss brush finish handle with necessary hardware fittings etc. complete.</p> | 4 | RM | | |
| 2 | SINGLE WINDOW SYSTEM (With Out Front Glass). The same as above specification without front glass. | 5 | RM | | |

| | | | | | |
|---|--|----|------|--|--|
| 3 | Counter Partition - The partitions are made of 12mm thick glass for a height of 45cm above the solid partition as per the drawing. The edges of the glass to be polished. The bottom portion of the partition is of double skin type for a height of 75 cm. In the frame work verticals and horizontals are made of Aluminium square sections 5 cm x 5 cm to a max. distance of 60 cm c/c. Frame work is covered with 9 mm thick marine grade plywood on both sides and finished with 1 mm thick laminate of approved make. The partition is firmly fixed to the floor. Necessary wicket doors are to be provided as per drawing. Necessary handles, hinges, tower bolts hydraulic door closer auto closing lock (godrej/ equivalent) etc are to be provided for the wicket door. Teak/ Beech wood polished beadings/ grooves in laminate etc. to be provided. | 32 | Sq.m | | |
| 4 | Custom made low height partition for CO cabin - Providing and fixing in position custom made low height partition of height 1500 mm (750 mm solid partition and 750 mm glass above) The edges of the glass to be polished. The bottom portion of the partition is of double skin type for a height of 75 cm. In the frame work verticals and horizontals are made of Aluminium square sections 5 cm x 5 cm to a max. distance of 60 cm c/c. Frame work is covered with 9 mm thick marine grade plywood on both sides and finished with 1 mm thick laminate of approved make. The partition is firmly fixed to the floor. Necessary wicket doors are to be provided as per drawing. Necessary handles, hinges, tower bolts hydraulic door closer auto closing lock (godrej/ equivalent) etc are to be provided for the door. Teak/ Beech wood polished beadings/ grooves in laminate etc. to be provided. | 10 | Sq.m | | |

| | | | | | |
|---|--|----|------|--|--|
| 5 | <p>Full Height Solid Partition:Supply and fixing double skin full height partitions as per shape and size shown in the drawing.Frame Work Detail:Harwood sections of thickness 50 X 50mm,vertically at about 60cm centers varied along columns wall ends, junctions of walls, as necessary. Horizontally of the same size of frames at floor level,750 mm, 1500 mm,2100 mm, and roof level. 50 X 25 mm at 350 Lining Work:8 mm Plywood of approved make on both sides of framework from floor level to 6"above false ceiling level, and to be finished with 1mm laminate of approved color on both sides including necessary grooves and steam beach beadings, doors wherever required in matching pattern with 10 x 4 cm hard wood frames, all best quality hardware, godrej lock etc complete.</p> <p>NOTE:All concealed faces of plywood and frame work should be finished with coat of wood preservation paint and exposed faces of steam beach beading/ laminate finish to be polished with melamine to the satisfaction of the Bank and Architects. Measurement for the partition area shall be considered from floor level to false ceiling level only.</p> | 42 | Sq.m | | |
| 6 | <p>Providing and fixing in position of double skin partition, partly paneled and partly glazed as per details shown in the drawing.</p> <p>Frame Work Detail: Harwood section of thickness 50 X 50 mm ,vertically at about 60 cm centers varied along columns, wall ends , junctions of walls, as necessary. Horizontally of the same size of frame at floor level, 900 mm,2100 mm, and roof level. 50 X 25 mm at 450 mm Lining Work: 8 mm plywood of approved make on both sides of framework from floor level to 900 mm level and 2100 mm level to 6" above false ceiling level finished with 1 mm laminate of approved color and shade. Between 900 mm and 2100 mm level, 12 mm thick clear float glass with etching fixed with necessary Dorma (or) equivalent make 'D' bracket of SS finish of 12mm thick, access doors wherever required in matching pattern with 10x 4 cm hardwood frames, all best quality hard wares, Godrej lock etc. complete. The glass opening 'jamb' portion finished with laminate. Measurement for the partition are shall be considered from the floor level to false ceiling only.</p> | 25 | Sq.m | | |
| 7 | <p>Providing and fixing fully glazed door (1 shutters) of 12 mm thick toughened glass with pencil polish edges alround with etching patterns and bevelled at edges. The door shall be fixed with DORMA patch fitting assembly inclusive of top and bottom patches, floor springs, bottom locks, SS brushed handle of 60 cm long and 2.5 cm dia. Lock of approved make etc. to be fixed to the door, the edge of the glass to be polished.</p> | 3 | Sq.m | | |
| | | | | | |

| | | | | | |
|---|---|-----|------|--|--|
| 8 | <p>FALSE CEILING:NOTE:The false ceiling area will be measured in flat area only.</p> <p>Providing and fixing suspended false ceiling, which includes providing and fixing GI perimeter channels of size 27 mm, 0.5 mm thick having one flange of 20 mm and another flange of 30 mm along with perimeter of ceiling, screw fixed to brick wall/ partition with the help of nylon rawl plugs and screws. Then suspending GI intermediate channels of size 45 mm, 0.9mm thick with two flanges of 15 mm each from the soffit at 1200 mm centres in one direction and 60 mm in other with ceiling angle of width 25x25x0.5 mm thick fixed to soffit with GI cleat and steel expansion fastners.</p> <p>Ceiling section of 0.5 mm thickness having knurled wedge of 51.5 mm and flanges of 26 mm each with lips of 10.5 mm are then fixed to intermediate channel with the help of connecting clips and in direction perpendicular to the intermediate channel at 457 mm centres 12.5 mm tapered edge moisture resistant gipboard is then scre fixed to ceiling sections with 25 mm dry wall scre at 230 mm centres. Scre fixing is done mechanically either with screw driver or drilling machine with suitable attachment. Finally the tapered and square edges of the boards are jointed and finished to a flush with requisite jointing compound, tapes and finished with 2 coat putty and 2 coats of plastic emulsion Necessary steppings and cuttings for electrical fittings, security devices, fire fighting equipments etc. as per the directions at site and arrangements for fixing the electrical and other fittings are to be provided.</p> | 150 | Sq.m | | |
| 9 | <p>BM Table</p> <p>Providing and fixing BM Table of size 1800 x 800 X 750 mm with 25mm thick Plywood with 1 mm thick laminate for table top, front apron and vertical sides etc. One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thick Plywood and finished with 1mm thick laminate at front side of approved color and shade with necessary lipping, telescopic drawer slides, locking arrangement, 100 mm long brush finish S.S. handles, etc. complete. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. The inside faces of drawer should be waxed and finished with varnish of app color and shade. 12 mm glass with round edges to be provided for table top</p> | 1 | No | | |

| | | | | | |
|-----|---|---|-----|--|--|
| 10 | Side Tables For BMProviding and fixing side unit for Manager / BM table to detail as per drg. of size 1200mm x 800mm, 18 mm Plywood for bottom, rear, sides and One intermediate with necessary reeper. The unit top shall be 19 mm thick Plywood Board with 1mm thick laminate of approved color and brand with front side half rounded edge and all the three sides with 3mm thick band strip. Side hung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade with jally work, including all necessary lipping, Box Type hinges, Locking arrangement, 100 mm long S.S brush finish handles, tower bolt, ball catch etc.,complete. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade. | 1 | No | | |
| 11 | Officers TableProviding and fixing Officer Table of size 1500 x 750 X 750 mm high to detail as shown in drg. Comprising table top out of 19mm thick Plywood with 1mm thick laminate of approved color and brand with both side half rounded edge and another two side edges with 3mm thick band strip.12 mm glass with edge rounded to be provided for the table top. Aqua blue shade of saint Gobain (or) equivalent toughened glass panel fixed on the 18mm thick to be fixed on front vertical laminate Plywood Board with SS studs.MS Powder coated Keyboard tray and 50mm Dia MS wire manager of approved quality .One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thickAll concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. | 5 | No | | |
| 11a | Providing table of size 120 x 60 cms as detailed above | 1 | No. | | |

| | | | | | |
|----|--|---|------|--|--|
| 12 | Side Tables For OFFICER - Providing and fixing side unit for Officer table to detail as per drg. of size 1200mm x 450mm, 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary reeper. The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip. Side hung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade, including all necessary TW lipping, Box Type hinges, Locking arrangement, 100 mm long S.S brush finish handles, tower bolt, ball catch etc.,complete. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade. | 2 | No | | |
| 13 | Providing and fixing side table of size 1000 x 450 mm for tables as detailed above | 5 | No | | |
| 14 | Side table for counters - providing and fixing side unit of size 1500 x 450 mm for counters as detailed above | 2 | Nos. | | |
| 15 | Low Level Storage :Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickne laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip.Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade.All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade. | 8 | Sq.m | | |

| | | | | | |
|----|---|-----|------|--|--|
| 16 | Column Paneling Providing and fixing cladding around the columns to detail as per drawing comprising 18mm thick Plywood with necessary stiffner on both ways of required nos and finished with 1 mm thick laminate of approved colour and shade. The surface has also fixed with 8 mm thick Lacqured glass as per drawing. 8mm thick MDF board jally work (CNC cutting) of approved design / pattern finished with white colour high gloss duco paint fixed over the laminate finish surface. | 25 | Sq.m | | |
| 17 | Providing and fixing wall mounted writing desk of 1200 x 350 mm in 19 mm plywood with 1 mm laminate on all exposed surfaces. Top portion is to be provided with 12 mm clear glass with polished edges, with shelves to keep slip books including frosting of approved design and exposed edges to be fixed with TW beeding with melamine polish. A provision to be made for keeping Banks printed Broachers for public etc. complete | 1 | No | | |
| 18 | Painting banking hall using approved quality ' Asian paint or equivalent two coats after applying putty finish | 170 | Sq.m | | |
| 19 | Painting banking hall using approved quality ' Asian paint or equivalent two coats without putty finish | 250 | Sq.m | | |
| 20 | Provide and fix 'Everite' make door closers | 8 | No. | | |
| 21 | Providing and Fixing 100 mm wide Vertical Blinds of Fabric 100% Polyester as approved with regular imported mechanism and including all standard fittings, accessories. fixtures, fastenings, etc, as per manufactures specification for | 60 | Sq.m | | |
| 22 | Flooring:- Providing and fixing 60 x 60 cm vitrified ceramic tiles Johnson & Johnson 'Marbonite' or equivalen approved for flooring and skirting. Tiles to be fixed to existing flooring using approved quality tile on tile adhesive. Basic price of tile to be taken as Rs.65/- per square foot ex showroom. (Tiles will be selected by the Bank) | 170 | Sq.m | | |
| 23 | Providing and fixing AAC block partition wall with AAC blocks (auto clave aeorated concrete) of size 600 x 100 x 200 mm jointed with webar lock set etc. complete. Rate should be inclusive of mateials, labour, transportation etc. | 15 | Sq.m | | |
| 24 | Dismantling existing counters, cabins, partitions and false ceiling and and stacking as directed | | | | |
| | TOTAL | | | | |
| | GST | | | | |
| | TOTAL AMOUNT | | | | |