

**NIT NO: GUW201905011**

**RENOVATION & REPARING OF INTERIOR FURNITURE WORKS  
OF SBI SONESWAR BRANCH**

**PRICE BID**

**ANNEXURE-III**



**SBI INFRA MANAGEMENT SOLUTIONS PVT. LTD., (SBIIMS),  
(WHOLLY OWNED SUBSIDIARY OF SBI)  
GUWAHATI CIRCLE OFFICE  
3rd FLOOR, SBI, LHO, GUWAHATI BUILDING  
DISPUR, GUWAHATI-781006**

| BOQ FOR RENOVATION & REPAIRING OF INTERIOR & FURNITURE WORKS OF SBI SONESWAR BRANCH |  |      |      |      |        |
|---|--|------|------|------|--------|
| S.N.  | DESCRIPTION  | UNIT | QNTY | RATE | AMOUNT |
| 1   | <p><b>SWO COUNTER:</b> Supply and installing new <b>SWO Counters</b> of overall size 1680 mm X 1830 mm X 750 mm, including cost of side credenza (1200mm x 450 mm x 750 mm) made up of 19 mm thick Block board of approved brand all around and finished with laminate of 1.0 mm thick of approve colour, brand and shade. The cost to include three drawers of 375 mm wide made up of 6mm/12mm ply of approved brand on right hand side of the table on telescopic slider with partitions for keeping of notes of different denominations, a keyboard tray 250 mm wide, CPU stand, foot rest as designe and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to have teak wood bidding/lipping stained to match the desk and melamine finished. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved make. Locks to be of single control type. Design and detail of the counters shall be as per Bank's new uniform colour, layout &amp; elevation policy, <b>with curvature on front</b> with flexi ply. <b>Counter &amp; Credenza top to be provided with 8mm thick glass</b> duly finished on edges and necessary cut to accommodate wires, edges to be m/c polished, with ms powder coated wire manager, complete as directed by EIC and placement as per layout given.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p> | Each | 3    |      |        |
| 2   | <p>Providing &amp; fixing <b>counter Front 12 mm thick float glass</b> with polished edges, fixed with necessary S.S Brush finish brackets support on wooden partition as directed. Rate shall includes fixing of frost film as per design &amp; directed, cost of studs, making cut-outs for transaction and voice hole.</p>  | SQM  | 4    |      |        |
| 3   | <p>Providing &amp; Fixing <b>12 mm thick float glass</b> of size 320mm (width) x 1100mm (height) &amp; tapering towards bottom as per the design and shape as shown in Bank's new uniform colour, layout &amp; elevation policy, fixed with silicon and T.W beading support on wooden partition as directed, on either sides of SWO as per design. Rate shall includes etching of glass as directed by bank. All edges of glass shall be duly beveled &amp; polished as directed complete.<br/>Make: Saintgobin/ Modiguard or equivalent.</p>  | SQM  | 2    |      |        |
| 4   | <p>Supply and installing <b>Branch Head Table</b> of size- 2130 mm x 1830 mm x 750 mm <b>including cost of side credenza (1080mm x 600mm x 750 mm)</b> made up of 19mm thick Block board all around, finshed with 1 mm thick laminate of colour, shade &amp; brand as approved. The table cost to include (pedestal), three drawers of 450 mm wide made with 6mm/12mm ply on right hand side on telescopic slider and a keyboard tray 250mm wide, CPU stand, foot rest as per design and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to have teak wood lipping/ bidding of requierd size stained to match the desk and melamine finished. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved brand. Locks to be of single control type. Design and detail of the table shall be as per direction of EIC. All the surfaces to be in laminate finish &amp; <b>8mm thick glass duly finished to be placed on top of table &amp; credenza</b> and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout &amp; elevation policy.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>  | Each | 1    |      |        |

|   |   |      |   |  |  |
|---|---|------|---|--|--|
| 5 | <p>Supplying and installing <b>Tables</b> of Overall size - 1680 mm X 1830 mm x 750 mm including cost of side credenza (1230 mm x 450 mm x 750 mm) made up of 19mm thick block board of approved brand all around and finished with 1 mm thick laminate colour, brand and shade as approved by the Bank. The table cost to include (pedestal) three drawers of 375 mm wide made with 6mm/12mm ply on right hand side on telescopic slider, a keyboard tray 250mm wide with CPU stand and foot rest as per design and direction by Bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to have teak wood lipping/bidding of required size, stained to match the desk and melamine finished. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks , handles etc. of Godrej or approved make. Locks to be of single control type.Design and detail of the table shall be as per direction of EIC. All the surfaces to be in laminate finish &amp; 8mm thick glass duly finished to be placed on top of table &amp; credenza and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout &amp; elevation policy.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p> | Each | 2 |  |  |
| 6 | <p>Supplying and installing <b>Server room running Tables</b> 600 mm wide, made up of 19mm thick Block board of approved brand for top and vertical support, finished with 1 mm thick laminate of colour, brand and shade as approved by the Bank. The table cost to include to provide one drawers of &amp; one openable shutter made uo of 6mm/12 mm ply, a keyboard tray 250mm wide and CPU stand as per design &amp; direction of bank. All exposed edges to have teak wood lipping/bidding of requierd size stained to match the desk and melamine finished. The works to include all hardware like castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved make. All inner surface to be finished with mat finish enamel paint of approve brandcd. Design and detail of the table shall be as per direction of EIC. All the surfaces to be in laminate finish and necessary cut out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout &amp; elevation policy.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>  | RM   | 4 |  |  |
| 7 | <p>Providing and fixing floor mounted <b>writing desk</b> of size 1200mm x 300mm x 900mm(H) made of 19 mm/ 12 mm ply with 12 mm thick float glass on top and voucher pigeon holes as per design &amp; direction of bank, with laminated boards support.</p>   | Each | 2 |  |  |
| 8 | <p>Fabricating and installing <b>Grahak Mitra table</b> of overall size - 1520mm x 600mm x 750 mm in straight or curved profile made up of 19mm thick block board of approved brand all around and finished with 1 mm thick laminate of brand, colour and shade as approved by the Bank. The table cost to include three drawers of 375 mm wide made with 6mm/12mm ply on right hand side on telescopic slider, a keyboard tray 250mm wide, foot rest &amp; CPU stand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks , handles etc. of Godrej or approved make. Locks to be of single control type. All exposed edges to have wooden lipping/bidding of requierd size, stained to match the desk and melamine finished. All the surfaces to be in laminate finish &amp; <b>8mm thick glass duly finished to be placed on table</b> and necessary cut-out to accommodate wires, edges to be m/c polished, with m.s. powder coated wire manager complete as per Bank's new uniform colour, layout &amp; elevation policy.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>   | Each | 1 |  |  |

|    |   |      |    |  |  |
|----|---|------|----|--|--|
| 9  | <p><b>Low ht storage unit:</b> Providing and fixing <b>storage units</b> of size 450 mm x 750 mm, made up of 19 mm thick block board of approved brand on top &amp; vertical support and finished with 1 mm thick laminate of approved brand on side and top. The storage units shall have openable/sliding shutters made up of 19mm thick plywood and finished in 1 mm thick laminate of approved shade. The storage units shall have intermediate horizontal and vertical shelves made in 12 mm thick plywood. All exposed edges to have teak wood lipping/bidding of required size, stained to match the desk and melamine finished. All inner surface to be finished with mat finish enamel paint of approved brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, locks, handles etc. of Godrej or approved make.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p> | RM   | 5  |  |  |
| 10 | <p><b>Dining Table:</b> Supplying and Providing Dining Table of size 1830mm x 900mm x 750 mm height. Top shall be made of 18 mm thick plywood with additional 18mm thick Ply wood patta of required width on edges with 1.0 mm thick laminate on top of approved shade and brand. Exposed edge to be finished with teak wood beading of required size. Supports of the Table shall be made of wooden members of required size in a Design as directed. All surfaces not laminated shall be lacquer polished.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.<br/>Wooden support: 1st class Local wood.</p> <p>Exposed edges of Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.</p>   | Each | 1  |  |  |
| 11 | <p>Fabricating and fixing <b>wall/column paneling</b>, with 12 mm thick ply finished with 1 mm thick laminate of approved shade &amp; brand over 25 mm x 35 mm (thickness not less than 1.5 mm) aluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical.) Panelling framework to be secured to wall surface / column surface</p> <p>Design and detail shall be as per direction of EIC and Bank's new uniform colour, layout &amp; elevation policy.</p> <p>Rate shall include removing of existing panelling if any on column before fixing the new panelling.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>   | SQM  | 55 |  |  |
| 12 | <p>Fabricating and fixing <b>full height solid partition</b>, made of 6 mm ply approved brand both side and to be finished with 1 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm (thickness not less than 1.5 mm) aluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. All exposed edge shall be covered with teakwood bidding/lipping of required size with polishing complete in all respect. <b>Payment will be made for the area upto false ceiling only.</b></p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>   | SQM  | 2  |  |  |
| 13 | <p>Fabricating and fixing <b>full height semi glazed partition</b>, made of 6 mm ply of approved brand in both side and to be finished with 1 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm (thickness not less than 1.5 mm) aluminium section framework at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. Middle portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make: Saintgobin/Modigurd) fixed with 10 mm thick teak wood moulding duly polished. All exposed edge shall be covered with teakwood lipping/bidding with polishing complete in all respect. Payment will be made for the area upto false ceiling only.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>   | SQM  | 30 |  |  |

|    |   |     |    |  |  |
|----|---|-----|----|--|--|
| 14 | <p>Providing and fixing <b>low height semi glazed wooden partitions</b> made of 6 mm ply of approved brand in both side and to be finished with 1 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm ( thickness not less than 1.5 mm) alluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical). Portion from 900 mm to 1500 mm height shall have 6 mm thick plain float glass (Make: Saintgobin/Modigurd) fixed with 10 mm thick teak wood moulding duly polished as per designe and direction by bank. All exposed edge shall be covered with teakwood lipping with polishing complete in all respect. Rate shall includes making provision for fixing of counter top 12 mm glass on its edges with neccessary fixing arrangement as directed.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p> | SQM | 20 |  |  |
| 15 | <p>Providing and fixing <b>Semi glazed doors shutter</b> made up of 38 mm thick block board of approved brand and quality, finshed both side with 1 mm thick laminate of approved brand, colour and shade. Middile portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make Saintgobin/Modigurd) fixed with 10 mm thick teak wood bidding duly polished N C lacquer as per design and direction by bank. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make. All exposed edge shall be covered with teakwood lipping with polishing complete all respect.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>  | SQM | 6  |  |  |
| 16 | <p>Providing and fixing <b>Solid doors shutter</b>, made up of 38 mm thick block board of approved brand and quality, finshed with 1 mm thick laminate of approved brand, colour and shade. The door shall includes all hardware such as: lock, handle, tower bolt, door stoper, hinge, hydraulic door closer etc. of approve make. All exposed edge shall be covered with teakwood lipping with polishing complete all respect. (doors of other sizes will be paid on pro rata basis.)</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>  | SQM | 2  |  |  |
| 17 | <p><b>WICKET GATE:</b> Providing and fixing low height door shutter in back side of SWO counter made up of 38 mm thick block board of approved brand and finshed with 1 mm thick laminate of approved shade and brand as per design and direction of bank. The door shall includes all hardware such as: ss hinge with countersunk ss screw, handle, door coloser, door stoper etc. of approved make. All exposed edge shall be covered with teakwood lipping with polishing complete all respect<br/>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent.<br/>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>   | SQM | 5  |  |  |
| 18 | <p>Providing fittings and fixing of woodwork in door frame (chowkhat) 75 mm x 62.5 mm section to the column/stiffeners/walls with necessary holdfast/sleeves etc. as specified and directed by bank. Allow making rebate for fixing of door shutter. rate shall includes applying of two coat of enamel paint.<br/>1st class local wood.</p>  | RM  | 20 |  |  |
| 19 | <p><b>MAIN GATE:</b> Providing and <b>fixing glazed door</b> made of 12 mm thick float glass (Make: saintgobin, modigurd) with frosted film fixed in between top &amp; bottom rail and side stile teak wood framework of size 125 mm x 50 mm. The framework to be finished with 1.0 mm thick laminate on both side. Glass to have acid etched design pattern with logo as directed. Doors to be mounted on heavy duty floor spring. Rate shall includes all hardwears such as: Two nos S.S. finish handle, lock, door stoper, hinge, tower bolt etc. of approved make.</p>  | SQM | 3  |  |  |
| 20 | <p>Providing &amp; fixing in position <b>Aluminium Composite Panel (ACP)</b> Panelling with framing of min 20 gauge 35 mm x 25 mm Aluminium Tube section in 600 mm C/C both ways. Minimum 3 mm thick ACP to be fixed over the freamework with 3M or equivalent adhesive and mirror screw in 600 width panels or distributed equally. Joints to be finished with Silicon based sealant. Aluminium foil thickness to be min 0.20 mm on both sides.</p>  | SQM | 5  |  |  |

|       |  |      |     |  |  |
|-------|--|------|-----|--|--|
| 21    | <p><b>Shutter Boxing:</b> Providing &amp; fixing in position Aluminium Composite Panel (ACP) with with framing of min 20 gauge 35 mm x 25 mm Aluminium Tube section in 600 mm C/C both ways. Minimum 3 mm thick ACP to be fixed over the freamework with 3M or equivalent adhesive and mirror screw in 600 width panels or distributed equally. Joints to be finished with Silicon based sealant. Aluminium foil thickness to be min 0.20 mm on both sides. ACP Trap door will be 12 mm ply finished with 3 mm thick ACP.</p> <p>Make: Alubond, Eurobond, Fujibond, Alcobond or equivalent ISO certified or approved brands to be used. Shades to be as per Bank's approval.</p> | SQM  | 4   |  |  |
| 22    | <p><b>False ceiling :</b> Providing and fixing suspended <b>false ceiling</b> with <b>600x600 mm size &amp; 12mm thick</b> mineral fiber ceiling tiles of Armstrong dune or approved make. Suspende, frame work as per manufacturer's specifications. The item to include cost of making necessary cut-outs for lights/air-conditioning grills as per design direction by bank.</p>  | SQM  | 125 |  |  |
| 23    | <p><b>Gypsum board false ceiling :</b> Providing and fixing suspended 12mm thick <b>Gypsum board false ceiling</b> with GI framework of standard gauge and as per the specifications of India Gypsum Co. The rate to include painting with lustre paint and making necessary design,pattern &amp; cut outs for light fittings, cove light etc. complete as per design direction by bank.</p>   | SQM  | 50  |  |  |
| 24    | <p>Providing &amp; fixing in place 100 mm. <b>Vertical blinds with scotch guard</b> of approved make, quality and colour shade &amp; pattern. Rate shall include necessary fittings, scotch guard treatment on both sides etc. complete. The overlaps should be uniform &amp; adequate.</p>  | SQM  | 10  |  |  |
| 25    | <p>Supplying, providing and fixing Godrej Cylindrical night latch lock at cash enclosure doors</p>   | Each | 5   |  |  |
| 26    | <p>Wall Paper : Providing and fixing wall paper of approved, design, pattern colour/shade complete as per desired of bank.</p>   | SQM  | 5   |  |  |
| 27    | <p>Providing and applying Texture paint on internal walls. Rate includes surfaces preparation, applying necessary coats of paint to obtain Uniform and even finish. Rate also includes applying paint of approved shed etc. complete.</p>  | SQM  | 5   |  |  |
| Total |  |      |     |  |  |