

**STATE BANK OF INDIA
AMBALAMEDU BRANCH
(EXISTING PREMISES)**

NAME OF WORK		INTERIOR RENOVATION WORK OF SBI AMBALAMEDU BRANCH			
NAME AND ADDRESS OF THE CONTRACTOR					
SCHEDULE OF ITEMS FOR INTERIOR WORKS AT AMBALAMEDU BRANCH AS PER UNIFORM LAYOUT					
Sl.No	DESCRIPTION OF WORK	Qty	Unit	Rate	Amount
1	<p>Providig and fixing of single window system without partitions comprising of each counter size 1500 to 1750mm & 2500length or as per layout and1200 mm height with below specifications and provisions . The top shall be fixed with 19mm plywood (IS303marine grade) of approved make with curved bend in front modesty as per drawing and fixed with white corian top of 6mm thick of approved brand. 18mm plywood of approved make for sides and for front shaped support and finished with 1mm laminate of approved colour. Front counter support for 750mm height with 18mm plywood finished with 1mm laminate of approved colour and shade. 12mm thick clear float galss to shape with etching is fixed with SS glazed clips fixed at front (600mm) and sides (450mm) above the counter as shown in the drawing. Modesty fixed with 8 mm thick oa Aqua blue shade of Saint Gobain glass or equivalent fixed 3M stickering suitable at 18 mm thick plywood vertical finished with 1 mm laminate. The side partitions of the counter, boxing on either side to shape as shown in the drawing with 18 mm plywood of approved make and to be finished with 1 mm laminate of approved colour from floor level to 1200 mm level at places shown in the drawing. Necessary wicket shutters are to be provided using 18 mm plywood and finished with 1 mm laminate of approved colour and shape as shown in the drawing.</p> <p>One set of 3 drawers about 450mm width, 712.5mm height and 600mm deep supported with 18mm plywood at bottom sides and rear. Drawers 3 nos of equal height made out of 12 mm thick plywood and 1 mm lamination of approved colour, with necessary lipping. Telescopic drawer slides, locking arrangements, 100mm long brush finish S.S handles etc complete. Top most cash drawer should be arranged with provision for denomination with 8mm thick plywood. Cash denomination seperation to be provided for 1 draw unit of the SWO, preferable the top draw with plywood. This draw unit has to be provided wiht automatic lock. pvc Telescopic keyboard and MS wire manager of 50mm dia of approved quality.Foot rest cum CPU stand of required length with 18mm thickness plywood to shape as shown in the drawing. All concealed faces of plywood finished with one coat of wood preservative paint and exposed faces of steam beach beading polished to the satisfaction of the Engineer. The MDF boards/ plywood and corain materials are as approved by the Bank. The rate should include locks, pvc keyboard trays, telescopic drawer slides, 100 mm ss brush finish handle with necessary hardware fittings etc. complete.</p>	17	RM		

2	SINGLE WINDOW SYSTEM (With Out Front Glass). The same as above specification without front glass.	3.5	Rm		
3	LOW HEIGHT PARTITION FOR SINGLE WINDOW SYSTEM:Providing and fixing of Low height partitions for Single window system of 750 mm height from finished floor level, as per the drawing.Hardwood section of 50 X 50 mm ,vertically at about 60 cm centers and 3 Nos Horizontally of the same size of frame at floor level, 750 mm and at 1200 mm level. 50 X 25 mm at 370 mm level, fixed in position. 8 mm Plywood on both sides of framework finished with 1 mm laminate of approved color and shade with grooves on both sides. Top of the partition finished with laminate of 1mm thick. The side portion glazing shall be done with "Blue Laminated / Lacquered transperated glass of 12mm thick of approved brand and shall be fixed with 'Dorma' (or) equivalent brand 'SS ' 'D' brackets. The curved 12mm thick lacquered transperant toughened glass shall be fixed at front size in between counters as per drawing and shall be fixed suitably with 'SS' brackets. Partition on rear similar to side partition, but solid partition. One door shutter for each cabin for 675 mm width and 1200 mm height, similar to door shutter item.All concealed faces of plywood and frame work finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the client.In door area concealed 50 mmX50 mm Second class TW frame to be Provided.	100	Sq.m		
4	Custom Made Low Height Partition: for CO cabinProviding and fixing in position of custom made low height partitions of the height 1500 mm as per shape shown in the drawing.ie. (750mm solid partition and 750mm glass above) . Hardwood section of 50 x 50mm at about 600 mm centers vertically and 3 nos. horizontally of the same section at floor level, 750mm level and at 1200mm level. 50 x 25mm at 375 mm level all framed and fixed in position, 8 mm Plywood of approved quality finished with 1mm Laminate with grooves on both sides of approved color and shade. Top of the partition finished with laminate and 8mm thick clear float glass with etching is fixed over the partition with Dorma make (or) Equivalent make 'D' bracket of SS finish of 12mm thick. Around the partition 75mm thick Dark color laminate is provided as show in the drawing and pattern.Note: All concealed faces of the plywood and the frames should be finished with one coat of wood perservative paint and exposed faces of steam beach beading / laminate finish , molding to be polished to the satisfaction of the Bank and the Architect.	1	Sq.m		

5	<p>Custom Made Full Height Solid Partition:Supply and set in position of custom made double skin full height partitions as per shape and size shown in the drawing.Frame Work Detail:Harwood sections of thickness 50 X 50mm,vertically at about 60cm centers varied along columns wall ends, junctions of walls, as necessary. Horizontally of the same size of frames at floor level,750 mm, 1500 mm,2100 mm, and roof level. 50 X 25 mm at 350 Lining Work:8 mm Plywood of approved make on both sides of framework from floor level to 6"above false ceiling level, and to be finished with 1mm laminate of approved color on both sides including necessary grooves and steam beach beadings, doors wherever required in matching pattern with 10 x 4 cm hard wood frames, all best quality hardware, godrej lock etc complete.</p> <p>NOTE:All concealed faces of plywood and frame work should be finished with coat of wood preservation paint and exposed faces of steam beach beading/ laminate finish to be polished with melamine to the satisfaction of the Bank and Architects. Measurement for the partition area shall be considered from floor level to false ceiling level only.</p>	50	Sq.m		
6	<p>Providing and fixing in position of double skin partition, partly paneled and partly glazed as per details shown in the drawing.</p> <p>Frame Work Detail: Harwood section of thickness 50 X 50 mm ,vertically at about 60 cm centers varied along columns, wall ends , junctions of walls, as necessary. Horizontally of the same size of frame at floor level, 900 mm,2100 mm, and roof level. 50 X 25 mm at 450 mm level.</p> <p>Lining Work: 8 mm plywood of approved make on both sides of framework from floor level to 900 mm level and 2100 mm level to 6" above false ceiling level finished with 1 mm laminate of approved color and shade. Between 900 mm and 2100 mm level, 8 mm thick clear float glass with etching fixed with necessary Dorma (or) equivalent make 'D' bracket of SS finish of 12mm thick. The glass opening 'jamb' portion finished with laminate. Necessary etching sticker works as per direction to be provided.</p> <p>The rate includes providing and fixing door shutters with all necessary hardwares , locks, handles, door closers, door stoppers etc, complete. Measurement of the partition area shall be considered from floor level to false ceiling level only</p>	22	Sq.M		

7	Fully glazed Door- Providing and fixing frameless fully glazed 12mm thk toughened glass door (2 shutters) fixed with necessary patch fittings (Dorma make) including cutting, making holes, cutouts in the glass of required shape and size to accommodate fittings and fixing the fittings in floors, soffits, jams including necessary fixtures, screws, sealant wherever required and SS cover over patch fittings. Rate shall include necessary etching film / LOGO, approved patch fitting locking systems, 1 pair of 600mm long S. S. (H Shape) Handles of approved make, floor springs, and any necessary hardware items.(DORMA MAKE Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Euro Profile Cylinder - US 10, Handle - TG DIH600 - 32mm dia X 600mm length)	9	Sq.m		
8	<p>FALSE CEILING:NOTE:The false ceiling area will be measured in flat area only.</p> <p>Providing and fixing of M/F suspended false ceiling as the detail given in the drawings. With G.I frame work and 12.5 mm tapered gypsum board panels to form grids of 45.7 X 122 cm as per manufactures specification including provision for stepped shaped ceiling for lighting trough comprisingFrame work of intermediate channels (M.F.T) at 122 cm centers along one direction M/F ceiling section MF5 at 45.7 cm center along other direction. Perimeter channels (MF 6A) along walls alround perimeter side of the ceiling. The intermediate channels suspened from ceiling,through starp hangers 25 X 0.5 mm (MF 8)at 122 cm centers connected to soffit cleats p534 (27 X 37 X 25 X 1.6mm) the cleats connected to ceiling through metal expansion rawl plugs 1/2" dia and 17/16" long with additional perimeter channels (MF 6A)for light fittings, Air conditioners Ducts,vertical drops, offset etc. 12.5mm thick gyp board with tapered edges fixed to underside of suspended grid with 25 mm screws to from grids with 2 coats of plastic emulsion paint of approved color and one coat of putty over a coat primer etc, complete.</p>	250	Sq.m		
9	Partly Glazed And Partly Paneled Doors.				
	Il class T.W. frame of size 75 X 50 mm as per the shape and size given in the drawing. 35 mm thick (finished) flush shutter finished with 1mm laminate on both sides with necessary grooves.8mm thick clear float glass of size 250 X 1400 mm fixed with necessary steam beach beading and etching. DORMA Make or equivalent make hardware fittings like locking arrangements,20 mm dia and 300 mm high SS brush steel finish handles, door closer, hinges, tower bolts,handles etc,. Fixed to the shutters.	6	Sq.m		
10	Fully Glazed - Fixed Glass Partition - Patch Fitting				

	Providing and fixing of fixed glass partitions with 12mm thick toughened glass using PT Standard fittings like PT 90/PT 92 of Dorma make at the top and bottom including cutting, making holes in glass and fixing the fittings in floors, ceilings etc and making the same good with necessary screws, 3M Vinyl sticker as per approved, colour, design and pattern , sealants etc.complete.	20	Sq.m		
11	BM Table Providing and fixing BM Table of size 1800 x 800 X 750 mm with 25mm thick Plywood with 1 mm thick laminate for table top, front apron and vertical sides etc. Foot rest cum CPU ctand of required length with 18 mm plywood waxed and finished with varnish of app colour and shade. One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thick Plywood and finished with 1mm thick laminate at front side of approved color and shade with necessary lipping, telescopic drawer slides, locking arrangement, 100 mm long brush finish S.S. handles, etc. complete. Table modesty shall be fixed with 8 mm thick aqua blue shade of Saint gobin or equivalent toughened glass panel fixed on to the laminated vertical plywood with SS Studs. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. The inside faces of drawer should be waxed and finished with varnish of app color and shade. 12 mm glass with round edges to be provided for table top	1	No		
12	Providing and fixing side unit for BM table of size 1200mm x 450mm, 18 mm Plywood for bottom, rear, sides and One intermediate with necessary reeper. The unit top shall be 19 mm thick Plywood with 1mm thick laminate of approved color and brand with front side half rounded edge and all the three sides with 3mm thick band strip. Side hung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade with jally work, including all necessary lipping, Box Type hinges, Locking arrangement, 100 mm long S.S brush finish handles, tower bolt, ball catch etc.,.complete. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.	1	No		

13	Providing and fixing officer's Table of size 1500 x 800 X 750 mm with 25mm thick Plywood with 1 mm thick laminate for table top, front apron and vertical sides etc. Foot rest cum CPU stand of required length with 18 mm plywood waxed and finished with varnish of app colour and shade. One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thick Plywood and finished with 1mm thick laminate at front side of approved color and shade with necessary lipping, telescopic drawer slides, locking arrangement, 100 mm long brush finish S.S. handles, etc. complete. Table modesty shall be fixed with 8 mm thick aqua blue shade of Saint gobin or equivalent toughened glass panel fixed on to the laminated vertical plywood with SS Studs. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. The inside faces of drawer should be waxed and finished with varnish of app color and shade. 12 mm glass with round edges to be provided for table top	6	No		
14	Providing and fixing side unit for table of size 1200mm x 450mm, 18 mm Plywood for bottom, rear, sides and One intermediate with necessary reeper. The unit top shall be 19 mm thick Plywood with 1mm thick laminate of approved color and brand with front side half rounded edge and all the three sides with 3mm thick band strip. Side hung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade with jally work, including all necessary lipping, Box Type hinges, Locking arrangement, 100 mm long S.S brush finish handles, tower bolt, ball catch etc., complete. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.	6	No		
15	Side table for counters - providing and fixing side unit of size 1500 x 450 mm for counters as detailed above	11	Nos.		

16	Low Level Storage :Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickne laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip.Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade.All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.	56	Sq.m		
17	Providing and fixing system running table of width 70 cm and height 75 cm. The table will have 3 drawers and stand for cpu. Drawers provided with handles of appropriate size. The table will have MS wire manager of 50 mm dia of approved quality . The table will also be provided with footrest made of steem beach wood 75 x 32mm. The table top Plywood finished with 1mm thickness flexy laminate of approved color and brand with two sides shall be half rounded edge and another two sides with edge band strip of 3mm thickness. The table will be provided with a M.S powder coated keyboard tray. All the exposed plywood surfaces to be finished with 1 mm laminate and concealed faces to be painted with two coats of paint.	2	RM		
18	Column Paneling- Providing and fixing cladding around the columns to detail as per drawing comprising 18mm thick Plywood with necessary stiffner on both ways of required nos and finished with 1 mm thick laminate of approved colour and shade. The surface has also fixed with 8 mm thick Lacqured glass as per drawing. 8mm thick MDF board jally work (CNC cutting) of approved design / pattern finished with white colour high gloss duco paint fixed over the laminate finish surface.	20	Sq.m		
19	Providing and fixing wall mounted writing desk of 1200 x 350 mm in 19 mm plywood with 1 mm laminate on all exposed surfaces. Top portion is to be provided with 12 mm clear glass with polished edges, with shelves to keep slip books including frosting of approved design and exposed edges to be fixed with TW beeding with melamine polish. A provision to be made for keeping Banks printed Broachers for public etc. complete	3	No		
20	Painting banking hall using approved quality ' Asian paint or equivalent two coats after applying putty finish	450	Sq.m		
21	Painting banking hall using approved quality ' Asian paint or equivalent two coats without putty finish	300	Sq.m		

22	Post Construction Anti termite treatment : Anti termite treatment to be carried out using drill and injection of approved chemical along wall-floor junctions internally and in other critical areas. Termite tubes, wherever observed to be chemically treated. Wooden material such as cupborads, windows, doors etc to be drilled around borders and drilling drilling injection of chemical along with spray treatment using oil based spary to be carried out ensuring nil damage to wooden material. Chemical : Imidacloprid 30.5 SC .1 litre chemical / 499 litre of water (2 ml / litre)	300	Sq.m		
	TOTAL				
	GST				
	TOTAL AMOUNT				