

NIT NO: GUW201911074

**RENOVATION & REPAIRING OF INTERIOR FURNITURE WORKS
OF SBI AMOLAPATTY BRANCH**

PRICE BID

ANNEXURE-III



**SBI INFRA MANAGEMENT SOLUTIONS PVT. LTD., (SBIIMS),
(WHOLLY OWNED SUBSIDIARY OF SBI)
GUWAHATI CIRCLE OFFICE
3rd FLOOR, SBI, LHO, GUWAHATI BUILDING
DISPUR, GUWAHATI-781006**

BOQ FOR RENOVATION & REPAIRING OF INTERIOR & FURNITURE WORKS OF SBI AMOLAPATTY BRANCH

S.N.	DESCRIPTION	UNIT	QNTY	RATE	AMOUNT
1	<p>MODIFICATION OF EXISTING SWO COUNTER: Supplying and fixing of 6 mm thick ply of approved brand and finished with 1 mm thick laminates of approved colour, brand and shade on top of the existing SWO counters. The front of the counters have to be modified by fixing of flexi ply with curvature in front as per Bank's new uniform colour, layout & elevation policy and finished it with 1 mm thick laminates of approved colour and brand. Rate shall includes removing and refixing of the existing front glass as requierd at site with all nmeccceassry clamps etc. complete and covering the exposed edges with new teak wood beeding after removing of existing beeding. Rate shall included removing of front glass and refixing it.</p> <p>Overall size of counters 1680 mm X 1830 mm X 750 mm, including side credenza.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent. Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>	Each	3		
2	<p>MODIFICATION OF EXISTING BM TABLE: Supplying and fixing of 6 mm thick ply of approved brand and finished with 1 mm thick laminates of approved colour, brand and shade on top, front and side of the existing table, face of drawers and side cabinets as per Bank's new uniform colour, layout & elevation policy. Rate shall includes covering the exposed edges with new teak wood beeding after removing of existing beeding.</p> <p>Overall size of table 1680 mm X 1830 mm X 750 mm, including side credenza</p> <p>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>	Each	1		
3	<p>Providing & Fixing 12 mm thick float glass of size 320mm (width) x 1100mm (height) & tapering towards bottom as per the design and shape as shown in Bank's new uniform colour, layout & elevation policy, fixed with silicon and T.W beading support on wooden partition as directed, on either sides of SWO as per design. Rate shall includes etching of glass as directed by bank. All edges of glass shall be duly beveled & polished as directed complete.</p> <p>Make: Saintgobin/ Modiguard or equivalent.</p>	SQM	2		
4	<p>MODIFICATION OF EXISTING OFFICER TABLE: Supplying and fixing of 6 mm thick ply of approved brand and finished with 1 mm thick laminates of approved colour, brand and shade on top, front & side of the existing table, face of drawers and side cabinets as per Bank's new uniform colour, layout & elevation policy. Rate shall includes covering the exposed edges with new teak wood beeding after removing of existing beeding.</p> <p>Overall size of table 1680 mm X 1830 mm X 750 mm, including side credenza</p> <p>Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>	Each	2		
5	<p>MODIFICATION OF Low ht storage unit: Supplying and fixing of 6 mm thick ply of approved brand and finished with 1 mm thick laminates of approved colour, brand and shade on top, & side of the existing sotrage cabinets and fixing of new 1 mm thick leminets in front side cabinet shutter after removing of the existing leminets by heating method. Rate shall includes covering the exposed edges with new teak wood beeding after removing of existing beeding.</p> <p>Size of Cabinets: 450 MM X 750 MM</p> <p>Laminate Make: Greenlam/Centurylam/Archidlam or equivalen</p>	RM	20		

6	<p>MODIFICATION OF EXISTING SEMI GLAZED FULL HT PARTITION: Fabricating and fixing of 8 mm ply of approved make in both side of existing aluminium frames after removing of particle boards of the existing aluminium partition and necessary strengthening of the frames as requerd at site. Th ply on both side to be finished with 1 mm thick laminate of approved brand, colour and shade on both side. the exisiting glass of the partition will remain same in the middile portion at 900 mm to 2100 mm height. All exposed edge shall be covered with teakwood lipping/bidding with polishing complete in all respect.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent. Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>	SQM	50		
NEW WORKS:					
7	<p>Fabricating and fixing wall paneling, with 12 mm thick ply finshied with 1 mm thck laminate of approved shade & brand over 25 mm x 35 mm (thickness not less than 1.5 mm) alluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical.) Panelling framework to be secured to wall surface / column surface Design and detail shall be as per direction of EIC and Bank's new uniform colour, layout & elevation policy. Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent. Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>	SQM	25		
8	<p>Fabricating and fixing full height semi glazed partition, made of 6 mm ply of approved brand in both side and to be finished with 1 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm (thickness not less than 1.5 mm) alluminium section framework at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. Middle portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make: Saintgobin/Modigurd) fixed with 10 mm thick teak wood moulding duly polished. All exposed edge shall be covered with teakwood lipping/bidding with polishing complete in all respect. Payment will be made for the area upto false ceiling only.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent. Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>	SQM	5		
9	<p>Providing and fixing low height semi glazed wooden partitions made of 6 mm ply of approved brand in both side and to be finished with 1 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm (thickness not less than 1.5 mm) alluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical). Portion from 900 mm to 1500 mm height shall have 6 mm thick plain float glass (Make: Saintgobin/Modigurd) fixed with 10 mm thick teak wood moulding duly polished as per designe and direction by bank. All exposed edge shall be covered with teakwood lipping with polishing complete in all respect. Rate shall includes making provision for fixing of counter top 12 mm glass on its edges with neccessary fixing arrangment as directed.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent. Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>	SQM	10		

10	<p>Providing and fixing Semi glazed doors shutter made up of 38 mm thick block board of approved brand and quality, finished both side with 1 mm thick laminate of approved brand, colour and shade. Middle portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make Saintgobin/Modigurd) fixed with 10 mm thick teak wood bidding duly polished N C lacquer as per design and direction by bank. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make. All exposed edge shall be covered with teakwood lipping with polishing complete all respect.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply or equivalent. Laminate Make: Greenlam/Centurylam/Archidlam or equivalent.</p>	SQM	10		
11	<p>INTERIOR PAINTING: Applying & Finishing interior walls with 2 or more coats of plastic emulsion paint of approved colour/shade on surfaces after preparation of base with sand papering, POP/Putty wherever required over a coat of primer of approved brand. Make: Asian paint, Deulux or equivalent.</p>	SQM	150		
12	<p>Applying & Finishing walls with 2 or more coat of enamel paint of required shade on wooden and steel surface. Rate including cost of primer coat. Make: Asian paint, Deulux or equivalent.</p>	SQM	50		
13	<p>False ceiling : Providing and fixing suspended false ceiling with 600x600 mm size & 12mm thick mineral fiber ceiling tiles of Armstrong dune or approved make. Suspender, frame work as per manufacturer's specifications. The item to include cost of making necessary cut-outs for lights/air-conditioning grills as per design direction by bank.</p>	SQM	20		
14	<p>Gypsum board false ceiling : Providing and fixing suspended 12mm thick Gypsum board false ceiling with GI framework of standard gauge and as per the specifications of India Gypsum Co. The rate to include painting with lustre paint and making necessary design,pattern & cut outs for light fittings, cove light etc. complete as per design direction by bank.</p>	SQM	15		