

BOQ FOR CIVIL WORKS					
CHANDMARI BRANCH(RENOVATION)					
Sl.No	Description of items	Unit	Qty	Rate(Rs.)	Amount(Rs.)
1	Finishing old/ new wall with water proofing weather coat smooth anti-fungal exterior painting of Apex brand of Asian Paints and of required shade after cleaning and clearing the surface etc. including scaffolding complete as directed at all levels (two coats)	Sqm	100		
2	Removing white or colour wash by steel wire brushing and or scrapping,sand papering and preparing the wall surface smooth including necessary repairs to scratches complete.	sqm	100		
3	Applying of one coat of cement primer of approved brand and manufacture on wall surfaces free from foreign matter and including preparing the surface even and sand papered smooth	sqm	100		
4	Applying priming coat over old wood after removing old paint or polish from wood and wood base surfaces with paint remover of approved brand. With ready mix paint wood primer(white)	sqm	20		
5	Painting one coat (excluding priming coat)on old wood and wood based surfaces with enamel paint to give an even shade including cleaning the surface of all dirt,dust and other foreign matter sand papaering and stopping	sqm	20		
6	Applying primary coat over old surface after removing old pain from steel and other metal surface and making the surface even. With ready mixed"red-oxide" primer	sqm	20		
7	Painting two coats (excluding priming coat)on new steel and other metal surface with enamel paint of approved brand and manufacture(Asian paint/Berger paint/Nerolac) to give an even shade including cleaning the surface surface of all dirt,dust and other foreign matter.Surface over 100mm in width or girth	sqm	30		
8	WALL PUTTY :Providing two coats of Birla White Wall Care Putty (Water Resistant White Cement based putty for concrete/ mortar walls and ceiling both internal and external) after removing all loosely adhering material from the wall surface with the help of emery stone, putty blade or wire brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department. (Total thickness of two coats is maximum 1.5mm)	sqm	150		
9	Providing & applying 2coats of plastic emulsion paint after scrapping and preparing the old surface by way of POP punning 6 MM and filling up to even finish/as per approved make/shade including removing splashes & cleaning	sqm	150		
10	Cleaning of vitrified floor tiles/anti skid vitrified floor tiles/wall tiles/marble with chemical for getting clean surface complete in all respect	sqm	150		
Total Cost					

Rates are exclusive of GST