

BHU2020 06 006 PRICE BID
SOQ for furnishing works for proposed DSH at Bhawanipatna

No	Description of work	Unit	Quantity	Rate	Amount
1	P&F 12.5mm thick Gypsum false ceiling of India Gypsum / Saint gobain make which includes G I perimeter channels , GI runners with perimeter of ceiling, screw fixed to brick work/ partition with the help of Nylon sleeves and screws at specified enters. Then suspending GI intermediate channels from the soffit at specified centres with ceiling angle fixed to soffit with GI cleat and steel expansion fasteners, ceiling section having knurled web etc complete. GI chanel, runners etc shall be IS marked. Ceiling frame shall be rigidly fixed to the wall, RCC rigidly so that it will not fall down while fixing boards, providing lights, electrical cables, pipes etc. Provision shall be made for light fitting, fire equipment, CCTV equipment. Extra support shall be given if necessary as per site requirement. Ceiling type : Plain, stepped, cove type as directed by engineer.	<i>sqm</i>	46.50		
2	P&F modular grid ceiling with Armstrong make Rh-95 anf tegular edge 600x600 x15mm as specified by manufacturer. Installation to comprise main runner at 1200 centres fixed to structural outfits. First and last Armstrong suspension system should not be greater than 6000 from adjacent wall. 600x600 cross tees shall be provided between 1200 tees. M6 anchor fastener with vertical hangers made of galvanised steel 26x26x25x1.2mm , a pre straight hanger wire 2.68mm dia, adjustable hooks clips of 0.8mm thick spring steel of 2.68mm shall be used. Thre work shall be executed as per manufacturers specification. Ceiling frame shall be rigidly fixed to the wall, RCC rigidly so that it will not fall down while fixing boards, providing lights, electrical cables, pipes etc. Provision shall be made for light fitting, fire equipment, CCTV equipment. Extra support shall be given if necessary as per site requirement.	<i>sqm</i>	96.50		
3	P&F 35mm thickness MR grade flush door finished with 6mm thick teak wood lipping on all edges duly polished, three SS Hinges for each door, one door stopper, one mortise lock combo set per door finished with 1mm thickness laminates on both sides of approved shade and colour (solid and glazed with 5.5mm thickness float glass). Make: Kitply/ Mayor/Sylvam as approved, Hinge: Dorset/ equiv, Lock: Godrej/ Dorset (Inspire)	<i>sqm</i>	4.00		
4	P&F 12mm toughened glass in Main entrance door with patch fittings , SS handles of 200mm duly supported by pivot at top and bottom with floor springs and top chord aluminium powder coated section as directed by engineer with edge polish. Cost of floor spring and alu section shall be paid extra.	<i>sqm</i>	2.00		
5	P&F 38mm thickness Fire retardent door sutter made with 2x19mm Fire retardent ply and finished with 6mmx38mm duly polished teak wood lipping in all edges, three SS Hinges for each door, one door stopper, one cylindrical lock per door. Make: Kitply/ Mayor/Sylvam/Green Fire retardent ply as approved, The door shallbe finishd with 1mm thick laminates on both sides of fire retardent plywood pmier and two or more caots fire retadent paint . (cost of laminte or paint shall be paid extra) Hinge: Dorset/ equiv, Lock: Godrej/ Dorset (Inspire)	<i>Sqm</i>	0.00		
6	P&F floor springs of Hafele / Dorma/Ozone heavy duty to glass door including cutting the floors (granite/ tiles/ concrte floors) and embedding the floor springs and grouting the area by approved tile adhesive matching with existing floors complete.	<i>no</i>	1.00		
7	P& fixing Door Closure of Haffel/ Dorma/Ozone heavy duty to glass door including cutting the floors and embedding the floor springs and grouting the area by tile adhesive of latecrete matching with tile colour etc complete	<i>no</i>	2.00		
8	P&F vertical blinds of Vista/ Marble/ D Décor with colour and shade as approved along with all accessories.	<i>sqm</i>	4.50		
9	P&F frosted film of 3-M/ LG make of approved design pattern, shade and colour to glass panels including cleaning glass panels etc complete.	<i>sqm</i>	8.00		

10	Officers table 5'x2-6" x2'6"along with side unit of 18"x42"x2'6": Made with 19mm MR grade BB in table top, sides with one drawer unit of 450mm x 150mmx450mm with sliding channels and one cup board. The side units shall have one shutter with provision of storage units (450x450x750). All necessary hardware's, locks, handles, PVC KBT of approved make shall be provided including foot rest. Front modesty panel shall be 12mm MR grade ply. All exposed surfaces shall be finished with 1mm thick laminate. Inside surface of table units shall be polished. A 40mm drop shall be provided on customer side with 19mm BB and laminate. Edges shall be finished with half round wood lipping on writing desk side and PU polished for smoothness. Drawers shall be finished with lipping polished. Ply: MR KITPLY/Mayoor/Century/ Sylvam / Green, and laminate: Green/ Marino/ Century/Kit ply as approved.	no	5.00		
11	CM table 6'x3'x2'6"along with side unit of 20"x42": Made with 19mm MR grade BB in table top, sides with one drawer unit (400x450x150mm) and one cup board with shutter. The side unit shall have one shutter with provision of storage units (450x450x650). All necessary hardware's, locks, handles, hinges, PVC KBT of approved make shall be provided including foot rest. Front modesty panel shall be 12mm MR grade ply. All exposed surfaces shall be finished with 1mm thick laminate. Inside surface of table and side units shall be polished. A 40mm drop shall be provided on customer side with 19mm BB and laminated. Edges shall be finished with teak wood beading 6mm thick polished for smoothness. Drawers shall be finished with lipping polished. Ply: MR KITPLY/Mayoor/Century/ Sylvam / Green, and laminate: Green/ Marino/ Century/Kit ply as approved..	no	2.00		
12	4 SEATER WORK STATION : Providing & placing 4 seated Work station as per drawing & design made of 18 mm thick Ply Wood of MR Grade Confirming to IS 303 finished with laminate of approved make and shade. Table top to be of 18 mm thick Ply Wood of MR Grade Confirming to IS 303 finished with 6mm thick solid surface and mounded as per the design. Table to be provided with storage cabinet with drawers made of 18 mm Ply Wood of MR Grade Confirming to IS 303 front side and back faces & drawer bottom with 12mm Ply wood of MR Grade. The table to be provided with foot rest of size 60X40mm thk. including locks, handles, telescopic slides for drawers,computer key board tray with retractable mouse pad,(tray with 250mm extension), all complete. All exposed surface to be finished with laminate. Inside surface to be painted with enamel paint of approved make and shade. This item shall include:	Nos	3.00		
	4 Low Height partially glazed Partition 5'-0" high and 5'6" long as per drawing made from Frame work for partition should with 3" x 2" Aluminium Channel horizontally and vertically at 600 mm c/c. The partition to be fixed tightly on floor by means of rawl plugs / dash fastners. The frame shall be treated with two coats of fire retardant paint of approved quality and manufacturer with glazing with 8mm glass as per design 4'-0" X 2'-0" Facing the partition both sides with 8mm thick plywood of MR Grade Confirming to IS303 firmly fixed with screws including making of necessary cut outs in partition Lamination both sides over ply surface with 1 mm thick laminate of approved quality and shade fixed by means of applying glue and pressing complete with grooves as per design / instructions.				

13	Full height and Low height Partition: (70mm thick) Providing and fixing solid and glazed partition made with GI Channel section 50mmx25mmx0.55mm thick spaced at 600mmx600mm grid and duly finished with 9mm MR grade ply and 1mm thick laminate (colour & shade approved by engineer as solid/ teak wood / texture premium quality on each side. The frame shall be properly anchored at true ceiling, wall/ column sides and floor with long screws at 900mm centres. The glass panel shall be 5.5 to 6 mm thick duly supported by 9mm MR ply and finished with laminate. Make: GI section Jindal/ Saint Gobain/ India gypsum, MR ply: Century/ Green/ Kit ply/Mayoor, Laminate: Century/ Green/ Kit ply/ Marino as approved	<i>sqm</i>	32.80		
14	Wall panelling with MDF board: Providing and fixing aluminium frame 25mmx40mmx0.80mm with a grid of 600mmx600mm duly anchored with wall screws to the walls and finished with 9.75mm MDF board and 1mm thick laminate of approved colour and shade. Make: MR Ply: Kit ply/Century/Mayoor/Green and laminate: Kit ply/Century/Green/Marino.	<i>sqm</i>	7.50		
15	Storage units 450mm deep: Made with 19mm MR grade Block board on all five sides and 6mm backing ply. Vertical separators shall be provided at each 3' Centres with door leaf of each shutter of 18" wide supported by auto closing hinges. All inside surface shall be finished with 0.80mm thick laminate. Exposed surface including shutter edges shall be finished 1mm laminate of approved shade. Hardwraes like locks, handles shall be provided. Make: Mr Ply: Kit ply/Century/green/mayoor, Laminate: Kit ply/century/green/ Marino; Hardware Godrej/ebco/ Hettich as approved Make:	<i>sqm</i>	31.00		
16	Finishing the wall surface, gypsum ceiling and other locations with two or more coat of wall primer including scrapping the area as site conditions and applying 2mm thick putty to the finished surafce	<i>sqm</i>	157.60		
17	Finishing the wall and gypsum area with tractor emulsion pants of Asian or berzer as approved with colour and shade in two or more coats using roller application	<i>sqm</i>	157.60		
	Total cost excluding GST				