

INNER VALUE ARCHITECTS INDIA

info@ivarchitects.in +91 98143-33332,9814866664

LOCATION & SITE : STATE BANK OF INDIA, NORTH HALL AT LOCAL HEAD OFFICE BUILDING at CHANDIGARH.

Bried Schedule of Quantities for Interior Works of NORTH HALL ., at L.H.O. Building Sector-17, Chandigarh.

IT. NO	ITEM	DESCRIPTION OF ITEMS	UNIT	QTY.	Quoted Rates	AMOUNT
1.00 PARTITIONS / PANELLING						
1.10	Acosutic Fabric Panelling	Providing and fixing Acoustic wall panelling with square edges made of fiber glass substrate 25mm thick and wrapped on the front side with an acoustically transparent and classified for fire reaction, sample approved by Engineer in charge. Fabric with an option of variety of colors of size 600x600 mm and 600x1200mm providing a minimum sound absorption level of 0.85 NRC to be affixed to wall using Wall panel Impalers In order to fix the panels to the wall, the Impalers shall be fixed to the wall surface using self tapping screws 3nos in case of 660x600mm, 4 nos in case of 600mmx1200mm Impalers to be used for the installation purpose. Wall panels shall be pierced through the spikes of the impalers ensuring the line and level of the panels are maintained etc completed as per direction of Engineer in charge.	Sqm	67.00		
1.20	Acosutic Wood Perforated slats Panelling	Providing and fixing Embroshyal Wood Perforated Slats of width 192mm, thickness of 16mm and length of 2440mm or as required by the Architect / approving engineer, made of a medium density fiber board of Embroshyal to substrate with laminated facing as per the approved shade / species and finish and a melamine balancing layer over the reverse side and also having round perforations of 8mm. The board shall have a special perforated pattern where the visible surface has a ("Helmholtz" fluted perforation of 3mm width and 21mm visible panel) each. Tolerance(+/- 1mm). Install wooden battens/Gl Section of section 50X50mm if needed or as approved by the Architect on the solid wall horizontally using screws and plugs on spacing on 600mm centre-to-centre. Screw the provided aluminum extruded keel over the lowest second wooden batten at an on-centre distance of 600mm. Install the first set of wooden panels by inserting the clips for border and insert the groove of panel into projecting the flange of aluminum clip. Continue installing rows of panels by inserting the tongue into the groove of earlier inserted panel and progressively installing clips for inside into the next keel till the actual height is achieved. Use clips for the border to finish off the installation. Rockwool 50 mm of 48 Kg/m3 is	Sqm	78.00		
2.00 Carpet Flooring						
2.10	CARPET TILE FLOORING	Providing and fixing Carpet Tiles made of Nylon size 50 x 50 cm with pile Height of 3mm (+/- .5mm) Pile Weight 520 GSM, Stain resistant and Fire Retardant Make: Welspun	sqm	30.00		
3.00 LOOKING MIRROR						
3.10		Providing and Fixing 6mm thk. Looking Mirror in Green Room with 12mm thk. Ply base fixed on wall with 4-6 no's SS Studs. Looking Mirror to be Bevelled from all 4 sides., complete in all respects to the satisfaction of Engg. In Charge/ Architect.	sqm	3.35		
GRAND TOTAL						