



STATE BANK OF INDIA

LOCAL HEAD OFFICE, PREMISES & ESTATE DEPARTMENT 3rd FLOOR,
C-6, G- BLOCK, SYNERGY BUILDING, BANDRA-KURLA COMPLEX,
BANDRA (EAST), MUMBAI-400 051

TENDER ID: MUM20240126

CORRIGENDUM-01

**TENDER FOR: PROPOSED CIVIL CONSTRUCTION OF SPECIAL CURRENCY
ADMINISTRATION BRANCH AT BANK OWN PREMISES ON PLOT NO. 2,
MIDC, DOMBIVILI (E), DIST: THANE, FOR STATE BANK OF INDIA**

It has been decided by competent authority to update the parts of tender notice as under:

S. No.	Bidding Document		Description	Existing Schedule	Proposed Schedule
	Page No.	Clause No.			
1	6	4.0 of ITT	Earnest Money	The tenderers are requested to submit the Earnest Money of ₹2,79,000.00 (Rupees Two Lakh Seventy Nine Thousand Only) by means of Demand Draft / Pay Order (Valid for a period of 90 Days from the last date of submission of the tender) from any Scheduled Commercial Bank drawn in favour of SBI and payable at Mumbai.	The tenderers are requested to submit the Earnest Money of ₹2,79,000.00 (Rupees Two Lakh Seventy Nine Thousand Only) by means of Demand Draft / Pay Order (Valid for a period of 90 Days from the last date of submission of the tender) from any Scheduled Commercial Bank drawn in favour of SBI and payable at Mumbai. The MSMEs have been exempted from payment of EMD subject to submission of relevant valid certificate for claiming exemption.

2	166	Item 5.0 (b) of price bid	RCC WORK	<p>Providing and laying in position site batched design mix cement concrete for reinforced cement concrete work; using coarse aggregate and fine aggregate derived from natural sources, Portland Pozzolana / Ordinary Portland /Portland Slag cement, admixtures in recommended proportions as per IS: 9103 to accelerate / retard setting of concrete, to improve durability and workability without impairing strength; including pumping of concrete to site of laying, curing, carriage for all leads;</p>	<p>Providing and laying in position cast-in-situ reinforced cement concrete work, at all height and levels in Currency Chest floor, walls, roof slab in any shape and as per structural design and as directed using Ready Mix Cement Concrete (RMC) manufactured in fully automatic. RMC plant with OPC 53-grade cement of Ultratech / Lafarge / ACC or equivalent approved by the Engineer-in-charge with cement content as per approved design mix and transported to site of work in transit mixers having continuous agitation, for all leads and heights including placing / pumping of RMC from Transit mixers to site of laying of concrete, spreading, compacting and finishing the surface in line, level and plumb as per requirement and curing etc. including admixtures in recommended proportions as per IS : 9103 to accelerate / retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge.</p>
---	-----	---------------------------	----------	---	--

				<p>The Rate to include necessary formwork, centring, shuttering, including cost of admixtures in recommended proportions as per IS : 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability complete in all respects and execution of work at all heights and location with required leads and lifts etc. as directed by Engineer-in-charge as per direction of the engineer-in-charge; for the following grades of concrete:b) Concrete of M40 grade</p>	<p>The rate include cost of necessary centering, shuttering, strutting etc. using approved quality waterproof shuttering ply/steel plates, MS props, jacks etc. but excluding cost of MS reinforcement complete. Wherever necessary, the contractor shall arrange for ensuring proper designing of shuttering to withstand load of RCC walls and Roof / Floor slabs of the Strong Room / Locker Room up to any thickness varying from 300 to 600 mm at their own cost within the quoted rates and shall arrange shuttering material accordingly. The rate should include assisting the specialised agency in laying Tang bars.Note:-Contractors shall be responsible to arrange Designing of specified concrete Mix from authorised Govt. Engineering College/Institute/Specialised agency and shall arrange to submit the same to Structural Consultant and Bank and should seek prior approval for the same well before proceeding with concreting work.b) Providing M-40 grade concrete RMC. (Note : Cement content considered in M-40 is not less than @ 360kg/cum)(Make: Ultratech / Lafarge / ACC or equivalent approved by the Engineer-in-charge.</p>
--	--	--	--	--	--

3	169	Item 8 of price bid	EXTERNAL PLASTER	<p>Providing and laying in position external Sand Face Cement Plaster, average 20 mm thk, in two coats, at all heights with first coat of av. 12 mm thk in Cement Mortar 1:5 using natural silt free fine sand, and second coat of average 6 mm thickness in C.M. 1:4, including necessary staggering, scaffolding, curing, roughening the first coat to receive second coat of plaster etc, providing approved water proofing compound @1 kg per bag of cement or as specified by the manufacturer and adding polypropylene fibre of approved make as per manufacturers specifications to prevent shrinkage cracks, complete as directed by the Engineer or Architect in charge.</p>	<p>Providing and laying in position external Sand Face Cement Plaster, average 20 mm thk, in two or more coats including dash coat, bond coat & other coats etc as per the direction complete., at all heights with first coat of av. 12 mm thk in Cement Mortar 1:5 using natural silt free fine sand, and second coat of average 6 mm thickness in C.M. 1:4, including necessary staggering, scaffolding, curing, roughening the first coat to receive second coat of plaster etc, providing approved water proofing compound @1 kg per bag of cement or as specified by the manufacturer and adding polypropylene fibre of approved make as per manufacturers specifications to prevent shrinkage cracks, complete as directed by the Engineer or Architect in charge.</p>
---	-----	---------------------------	---------------------	---	---

4	169	Item 9 of price bid	INTERNAL CEMENT PLASTER	<p>Providing and applying in position average 12/15mm thick smooth finish cement Plaster in cement mortar 1:5 to all internal walls, using fine or Coarse sand and adding polypropylene fibre of approved quality in desired quantity per bag of cement as per manufacturers specifications complete. Rate includes providing chicken mesh to all joints of RCC members with Brick walls in all positions in proper line, level & plumb at all levels and heights with necessary scaffolding, cleaning of surfaces, raking out joints, roughening of surfaces, curing etc complete as directed at site. Rate includes making Flush/raised/sunk or moulded bands of any width, recesses, making grooves etc. complete as per Architectural drawings and no extra payment shall be considered for the same.</p>	<p>Providing and applying in position average 12/15mm thick smooth finish cement Plaster in cement mortar 1:5 including dash coat, bond coat & other coats etc. as per the direction complete to all internal walls, using fine or Coarse sand and adding polypropylene fibre of approved quality in desired quantity per bag of cement as per manufacturers specifications complete. Rate includes providing chicken mesh to all joints of RCC members with Brick walls in all positions in proper line, level & plumb at all levels and heights with necessary scaffolding, cleaning of surfaces, raking out joints, roughening of surfaces, curing etc complete as directed at site. Rate includes making Flush/raised/sunk or moulded bands of any width, recesses, making grooves etc. complete as per Architectural drawings and no extra payment shall be considered for the same.</p>
---	-----	---------------------------	-------------------------------	---	--

5	170	Item 10 of price bid	PLASTER ON CEILING	Providing applying in position 10/12mm (average) thick single coat cement plaster to Ceiling, Soffit of <i>Chhajja</i> , Cantilever Balconies or any other RCC projection/surface in approved pattern and design in cement mortar 1:4 in proper line and level using approved quality silt free natural sand (Fine or Coarse as directed) at all heights and locations including necessary scaffolding, curing etc. complete as directed by the Engineer-in-charge. Rate includes making Flush/raised/sunk or moulded bands of any width, recesses, making grooves etc. complete as per Architectural drawings and no extra payment shall be considered for the same.	Providing applying in position 10/12mm (average) thick single coat cement plaster to Ceiling, Soffit of <i>Chhajja</i> , Cantilever Balconies or any other RCC projection/surface in approved pattern and design in cement mortar 1:4 in proper line and level using approved quality silt free natural sand (Fine or Coarse as directed) at all heights and locations including necessary scaffolding, curing etc. complete as directed by the Engineer-in-charge. Rate includes making Flush/raised/sunk or moulded bands of any width, recesses, making grooves etc. complete as per Architectural drawings and no extra payment shall be considered for the same. Note: Dash coat, bond coat & other coats are also included as per the direction complete.
---	-----	----------------------	--------------------	---	---

All other terms & conditions of the tender document will remain same.

Assistant Manager (P&E)