

BOQ FOR INTERIOR WORKS AT SBI AO DEHRADUN

S.No	ITEM SPECIFICATION	UNIT	QTY	RATE	Amount
1	Dismantling of existing Brick/ Wooden Partitions/ False Ceiling etc. and disposing the material as directed	Sqm	100		
2	<u>Double Skin Solid Partition (Low Height 5 Feet height):</u> Supplying, fitting and fixing double skin solid partition for specified enclosure, made out of 50.80mm x 25.4mm X 2 mm size aluminium stud frame (Hindalco Section 9835 or equivalent) at 600 x 600mm c/c bothways and fixed with 8mm thk. MR ply, exposed surface clad with 1mm matt finish laminates on both sides of enclosure, including fixing 12 mm thick clear float glass as directed. The vertical members shall go beyond the false ceiling level and fixed to the soffit of R.C.C. slab/beam along with one extra top member. The bottom member shall be fixed to the R.C.C. floor/roof slab with wedge bolt and rawl plugs at suitable intervals. All materials are to be of approved make, shade and quality. The rate shall include cost of all materials, labour, taxes, T&P, transportation, royalties etc. for complete work. The measurement shall be done upto false ceiling level and no extra payment shall be made for framework or for the ply or laminate above the ceiling level. Rate to be quoted inclusive of placement of existing work stations as per layout (enclosed) in the tender document with partitions.	Sqm	100		
3	Laminate panelling works Providing & fixing Panelling consisting of: Frame work with 45 x 25 mm GI sections @ 600 mm c/c in both directions Facing with 8 mm thick MR ply board well secured to frame work by means of screws and nails. Finishing with 1.0 mm thick Laminate with grooves as per drawing and design. Fixing 100mm high skirting of 1mm thickness Mettallc Laminate as per approved sample on exposed partition surface as per architectural drawings	Sqm	100		

4	Providing & applying the walls, ceiling and elsewhere with Plastic Emulsion Paint (roller finish) after preparing the base, over a coat of primer as per manufacturer's specifications	Sqm	1600		
5	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	1000		
6	ENAMEL PAINT				
	P & L approved shade and colour of synthetic Enamel Paint of approved brand (Asian / Burger) on wooden / M.S. Doors/ Windows / Shutters with Red Oxide Base with scrubbing, preparation of base etc. complete. Note : All material will be deposited/kept in bank store room with all necessary bills satisfying the bank to assure the quality of material used on site.	Sqm	400		
7	Re furbishing existing table (size upto 7 Feet x 2.5 FeetX2.5 Feet) by cutting and placing table in desired size & location and cladding the exposed surface with 6/4 mm thick MR grade ply finished with 1 mm thick Matt finished laminate of approved make and shade, all unexposed surface painted with enamel paint two coats or more for desired finish, edges to be provided with flat lipping beat duly ploished. Rate inclusive of opening of existing locks/ handles etc and re-fixing the same over refurbished surface.	Nos	14		
8	Re furbishing existing table (size upto 6 Feet x 2.5 FeetX2.5 Feet) by cladding exposed surface with 6/4 mm thick MR grade ply finished with 1 mm thick Matt finished laminate of approved make and shade, all unexposed surface painted with enamel paint two coats or more for desired finish, edges to be provided with flat lipping beat duly ploished. Rate inclusive of opening of existing locks/ handles etc and re-fixing the same over refurbished surface.	Nos	40		

9	Re furbishing existing side table (size upto 3.5 feet x 2.5 Feetx2.5 Feet) by cladding exposed surface with 6/4 mm thick MR grade ply finished with 1 mm thick Matt finished laminate of approved make and shade, all unexposed surface painted with enamel paint two coats or more for desired finish, edges to be provided with flat lipping beat duly ploished. Rate inclusive of opening of existing locks/ handles etc and re-fixing the same over refurbished surface.	Nos	54		
---	--	-----	----	--	--

10	Refurbishig existing cup boards by cladding exposed surface with 6/4 mm thick MR grade ply finished with 1 mm thick Matt finished laminate, all unexposed surface painted with enamel paint two coats or more for desired finish. Rate inclusive of opening of existing locks/ handles etc and re-fixing the same over refurbished surface.	Sqm	150		
11	Refurbishig existing wall panelling by cladding exposed surface with 6/4 mm thick MR grade ply finished with 1 mm thick Matt finished laminate, wooden edges to be duly polished	Sqm	20		
12	Brick Work Providing & constructing first class burnt brick for load bearing wall of thickness 230 mm in cement-mortor mix ratio of 1:4, including providing & casting 100mm thick "patli beam" using 4 nos. 8mm dia. tor steel & 6mm dia. MS rings at 150mm c/c at every 1200 mm height, including racking of joints, curing and all necessary scaffolding , including all stone work like dasa , sill, coping, Lintels and chajja etc. at all heights as directed. DSR 2023 Item No 6.4.1	Cum	1		
13	CEMENT PLASTER :				
	Plastering of 15 mm thick cement mortar 1:4 (1 cement : 4 fine sand) on rough brick wall surface with required cement ghole sprinkling rates inclusive of required scaffolding and curing of plastered surface all included	Sqm	10		
14	Providing and fixing Roller Blinds (Vista Levelor/ MAC/ DACK) of approved shade, texture and fabric including all associated accesories etc. complete to the satisfaction of Bank.	Sqm	100.00		
15	Supply and Fixing of 20 Foot Long, 2.5 Foot High, and 2 Feet Deep Lunch Serving Counter made of MS Angle Structure with granite top (18-19 mm thick Z Black) and wooden front.Wooden front to be fixed with 19 mm thick BWP ply finished with 1mm thick matt finished laminate	Nos	1.00		
16	Fixing Wall Tiles in Lunch Room				

	Providing and fixing 1st quality standard white, grey, ivory, fume red brown, light green, light blue and other light shade glazed tiles confirming to IS 13753 & IS 15622 of size 12" x 24" in walls, pillars etc. laid on a bed of neat cement slurry finished with flush pointing in the white cement mixed with pigment to match the shade of the tile complete (including the cost of cement plaster). DSR Item 8.31	Sqm	10.00		
17	Enamel paint over existing wooden beat in wooden texture after cleaning the surface by sand papering with a undercoat of primer as per manufacturer's specifications	Sqm	100.00		
18	12 mm thick toughened glass partition Providing & fixing 12mm thick toughened Fixed Glass with S.S. clamps on sides and top & S.S. u-channel in floor as per detail drgs. and complete to the satisfaction of Bank	Sqm	10.00		
19	12 mm thick toughened glass door Providing & Fixing fully Glazed frame-less door made out of 12 mm thick toughened glass edge polished fixed with stainless steel patch fittings at top & bottom and floor springs and lock of ozone make . The door shall have the lock at bottom, and 600 mm length stainless steel brush finish handles of 25 mm dia complete.	Sqm	5.00		
Total					
GST Extra					