

BOQ FOR BOUNDARY WALL REPAIRS AND PAINTING
OF BANK'S RESIDENTIAL COMPLEX AT 14 KLIDAS MARG, DHRADUN

SI No	Item Description	Unit	Qty	Rate	Amount
1	Plastering of 15 mm thick cement mortar 1:4 (1 cement : 4 fine sand) on rough brick wall surface with required cement ghole sprinkling rates inclusive of required scaffolding and curing of plastered surface all included	SQM	1200		
2	Extra for providing waterproofing material in cement plaster in proportion as per manufacturer's specifications	Per 50 KG of Cement Bag	250		
3	Supplying and applying two coats of water proof cement paint (damp proof) of required shade @ 3.84 kg/ 10 Sqm including surface preparation by scrapping and sand papering.	SQM	1500		
5	Supplying and applying two coats or more @ 1.43 ltr/10 Sqm including priming coat of exterior primer of Premium Acrylic Smooth exterior paint with silicon additives of required shade	SQM	1500		
6	Painting of MS Gate, Grill, Electric Pole, Sitting Benches etc all complete with synthetic enamel paint of Asian Paints make as per manufacture's specification all complete.	SQM	700		
7	Dismantling of old plaster and disposal of malba to municipal grounds as per local by laws	SQM	1000		
8	Brick Work Providing & constructing first class burnt brick for load bearing wall of thickness 230 mm in cement-mortor mix ratio of 1:4, for repair of boundary wall	CUM	6		
Total					
GST extra as applicable					