

PRICE BID FOR INTERIOR FURNISHING WORK OF STATE BANK OF INDIA BRANCH AT MANALI (H.P)					
S.No.	Item	Quantity	Units	Rate	Amount
	<b>PANELING/PARTITON</b>				
	<b>Note: For the Paneling, Full height partitions and low height partitions the work measurement for costing shall be only of the plain visible surface, no extra cost for extrusions or extra frame work required as per drawing will be made. The work done above ceiling, below floor finish level or not directly visible shall not be measured.</b>				
<b>1</b>	<b>WALL PANELING</b>				
	Providing and fixing panelling on column/wall. Framing shall consist of Heavy duty Aluminium Box Sections 50mmx25 mm with maximum spacing of @ 600mm c/c Both ways horizontally and vertically on the column/wall. This framing would be covered by 9mm thk. Ply (Green ( Eco- Tech ) / Century / Archid) finished in approved 1.0mm Thk. Laminate (Merino / Formica / Archid ) of desired shade, design and gloss. Wooden molding, lipping etc. shall be provided wherever required as per drawing and deco painted in desired shade. The paneling shall have skirting and intermediate bands finished with metallic laminate of desired shade, design and gloss. The work shall also include the cost of making cut-outs for the electrical switches, lights, switch boxes etc. and provision for laying conduit for electrical/telephone/Data cabling etc.	<b>47.97</b>	<b>SQM</b>		
<b>2</b>	<b>FULL HEIGHT PARTITIONS:</b>				
	Providing and fixing wooden full height partition with following specifications:	<b>88.28</b>	<b>SQM</b>		
	(a) Supporting system comprising of Dry wall Frame Work Boral/Rondo/Gyp. of 50mm x 50mm (18 Gauge) square section@ max. 600mm c/c both horizontally and vertically. The frame shall be fixed rigidly at floor level and ceiling level wherever possible. The rate should also include necessary strengthening with additional members at doors and other openings.				
	(b) The partition shall have 9mm Plywood (Green ( Eco- Tech ) / Century / Archid) fixed on both sides with screws for the entire height of the partition and finished with approved 1.0mm Th. Laminate (Merino / Formica / Archid ) of desired shade, design and gloss on both sides. Wooden molding, lipping etc. as directed by Bank / architect shall be provided wherever required. The partition shall have skirting and intermediate bands finished with metallic laminate of desired shade, design and gloss.				
	(c) The full height partition shall be WITH OR WITHOUT 8mm clear float glass with etching fixed as per drawing with 75mm x 12mm Teak wood jamb/chaowkhat around glass opening and 12mm x 12mm teak wood beading for fixing of glass on both sides. As per the direction of Engineer-in-charge and design.				
	(d) The work to include providing and fixing of partly glazed wooden door shutters using 35mm readymade ISI flush door shutter with 1.0mm thick laminate (Merino / Formica / Archid ) of desired shade/textures and gloss as per drawing with teak wood frame of 75mm x 40mm. The door shall have 6mm thick teak wood lipping all around the edges. The door shall have vision panels with 8mm thick clear float glass with etching fixed with double 14mmx25mm thick teak wood moulding as per design. The exposed surface of wood shall be deco painted in desired shade. The door shall be complete in all respect with hardware handles, godrej 6-lever lock/night latch lock, door closer, door stoppers, 8" tower bolts, hinges etc all in brass.				
<b>3</b>	<b>Low height partition 4'-6" High</b>	<b>44.02</b>	<b>SQM</b>		
	Providing and fixing wooden low height partition with following specifications:				
	(a) Supporting system comprising of Dry wall Frame Work Boral/Rondo/Gyp. of 50mm x 50mm (18 Gauge) square section@ max. 600mm c/c both horizontally and vertically. The frame shall be fixed rigidly at floor level and ceiling level wherever possible. The rate should also include necessary strengthening with additional members at doors and other openings.				
	(b) The partition shall have 9mm Plywood (Green ( Eco- Tech ) / Century / Archid) fixed on both sides with screws for the entire height of the partition and finished with approved 1.0mm Th. Laminate (Merino / Formica / Archid ) of desired shade, design and gloss on both sides. Wooden molding, lipping etc. as directed by Bank / architect shall be provided wherever required. The partition shall have skirting and intermediate bands finished with metallic laminate of desired shade, design and gloss.				
	(c) The low height partition shall have 12 mm thick glass (Saint Gobain / TATA / Asahi) with etching as per design fixed with stainless steel wall cladding profile (WCP) of Hettich/Haffele/ Dorma make at bottom and sides with top surface and other side free. All the edges of the 12mm glass shall be duly grinded/bevelled and polished.				
<b>4</b>	<b>12mm thick Toughen glass for transaction partition &amp; ATM separation</b>	<b>10.46</b>	<b>SQM</b>		
	Providing and fixing 12 mm thick, clear plain toughened glass of approved pattern fixed in vertical position at counter front and as curved glass extension of low height partition as per drawing, fixed on wooden partitions with superior quality stainless steel patch fittings of ebco/godrej/ozone. An opening as per the drawing at the bottom for transaction shall be provided in case of glass in from of the transaction counter. All the edges of the glass shall be grinded/bevelled and polished. The glass shall also be etched as per the design. Glass area with maximum height shall be measured for the purpose of payment. The work shall be carried out as per drawings.				

5	<b>12MM THICK TOUGHENED GLASS PARTITIONS WITH FILM:</b>	17.26	SQM		
	Providing and fixing in position 12mm clear float toughened Glass(Saint Gobain / TATA / Asahi) partition with patch fittings for the full height glass partitions as per the direction of the engineer-in-charge. The work to include making necessary template for all the glasses and then cutting the clear float glass to correct size, making all the necessary holes, cuts etc., then toughen the same.				
	The cost to include all hardware (PATCH FITTINGS etc) required of Hettich/Haffe/ Dorma or approved equivalent make viz., single corner patch, top and bottom corner patch etc. or as per the direction of the engineer-in-charge, along with etching with sand blasting as per design and drawing. The maximum size of each glass shall be 1200mm to 2000mm x 2400mm to 2700mm as per the site requirement. The rate is for a finished item of work etc., complete as directed.				
	The cost to include the cost of bevelling and smoothing of the exposed edges of the glass.				
6	<b>12MM TOUGHENED GLASS FOR FRONT WITH FILM :</b>	6.51	SQM		
	Providing and fixing 12 mm thick, clear plain toughened glass (Saint Gobain / TATA / Asahi) of approved pattern fixed in vertical position at counter front and as curved glass extension of low height partition as per drawing, fixed on wooden partitions with superior quality stainless steel patch fittings of Hettich/Haffe/ Dorma. An opening as per the drawing at the bottom for transaction shall be provided in case of glass in front of the transaction counter. All the edges of the glass shall be grinded/bevelled and polished. The glass shall also be etched as per the design. Glass area with maximum height shall be measured for the purpose of payment. The work shall be carried out as per drawings.				
7	<b>SINGLE LEAF 12MM THICK TOUGHENED GLASS DOORS WITH ETCHING:</b>				
	Providing & fixing of fully glazed 12 mm thick toughened glass (Saint Gobain / TATA / Asahi) with top & bottom corner patch pivot, floor spring, glass locks & Handle with installation ( Dorma or equivalent make) of approve make as directed by Architect. All the edge of the glass shall be machine polished. 300mm "C" shaped s.s handle of approved make & design on both side. Including providing "PUSH" * "PULL" sticker labels of approved design & make. The rate to include all materials, labour, transport, taxes, delivered and placed in position at site of work.	7.00	SQM		
8	<b>GYPSON BOARD FALSE CEILING WITH STEPS:</b>	227.70	SQM		
	Providing and fixing suspended false ceiling including steps and provision of cope lighting as per design with 12.5mm tapered edge Gypboard / 12mm thick Elephant Gypsum Board (Gypsum India) to the grid comprising of cold rolled galvanized metal section to the required line and level. The grid consisting of a perimeter channel fixed round the perimeter. The intermediate channel at 1200mm c/c in the one direction and the ceiling section at 450mm c/c in the other direction to be connected by a connecting clip. The grid to be suspended with an adjustable strap hanger.				
	The grid to be suspended with an adjustable strap hanger at 1200mm c/c on both ways from the structural soffit using a soffit cleat and expandable bolts/fasteners Nut and bolts to be used to connect strap hangers to soffit cleats and for joining ends of channel sections together. The gypsum board layers to be screwed to the M/F ceiling sections with gypboard drywall screws. Jointing and screw spotting are then carried out as per manufacturer's standard recommendations. Perimeter Channels to be used around the cut outs for light fittings. A/C ducting etc. The work should be complete as per instructions of Architect or Engineer in charge including 2-3 coats of plastic emulsion , over a coat of primer.				
9	<b>GRID FALSE CEILING:</b>	159.50	SQM		
	Silhouette Grid False Ceiling:- Providing and fixing in true horizontal level false ceiling grid system of Armstrong World Industries. The suspension system shall be the Armstrong Trulok Silhouette revealed profile grid system with 15mm wide flanges incorporating a 3mm or 6mm central recess color, black or white revealed. Silhouette main runners and cross tees to have mitered ends with "birds mouth " notches to provide mitered cruciform junctions.				
	Main runners to be spaced at 120mm c/c fixed by using 2mm pre-straightened GI wire. Main tee, rotary stitched at every 1200mm c/c maximum and 1200mm cross tee at every 600mm c/c maximum and 600mm cross tee at every 1200mm c/c maximum and wall angle all-round the wall to form grid size of 600mm x 600mm and suspending the grid using 2mm pre-straightened GI wire and 6mm nylon rawl plug at every 1200mm intervals at the main tee and laying of premier mineral fiber tiles manufactured by Armstrong World Industries of size 600mm x 600mm x 15mm over the formed grid etc., complete as per manufacturer's specifications.				
10	<b>OFFICER'S TABLES WITHOUT SIDE CREDENZA</b>				

	(a) Providing and fixing at site Officer's table (10 mm thk glass on table top with foam ) made of 19mm th. commercial block ply (Green ( Eco- Tech ) / Century / Archid) with 1mm thick laminate (Merino / Formica / Archid ) of desired shade, design and gloss on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. . The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.				
	The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 19mm ply fixed with sliding telescopic channels of Haffele/Hettich make. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.				
	(b) There shall be provision of one storage cabinet 1'3" wide. The frame shall be made with 19mm thick commercial board. The cabinet shall have one lockable drawer running on side mounting drawer slides (channels) of EBCO make & one cupboard with shutter beneath the drawer, made of 19mm thick commercial block board with 1mm thick laminate (Merino / Formica / Archid ) of desired shade, design and gloss on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood (Green ( Eco- Tech ) / Century / Archid) , bottom of 6mm thick plywood & front of 19mm thick block board.				
	All other surfaces i.e. inside / legsapce of table, inside of drawer / cupboard shall be provided with 0.8mm thick laminate of desired shade/design and gloss, and wood lipping / beading shall be PU polished with matching pigment/deco painted in desired colour. The table shall have a CPU ledge made of 19mm thick block board on one side, complete as per drawing.				
a)	2.13 X 0.76 X 0.76	1.00	no.		
	<b>FOR THE CHIEF MANAGER</b>				
b)	1.37 TO 1.52 X 0.76 X 0.76	8.00	no.		
	<b>OFFICER'S TABLE</b>				
d)	1.20 X 0.76 X 0.76	1.00	no.		
	<b>Guard table</b>				
<b>11</b>	<b>SWO COUNTERS: (AS PER NEW DESIGN AND SPECIFICATIONS)</b>	<b>10.67</b>	<b>RMT</b>		
	(a) Providing and fixing at site SWO counters as per the new design and drawings. SWO counters to be made of 19mm thick commercial block board with 1mm thick laminate(Merino / Formica / Green New Mica ) of desired shade, design and gloss on outer visible surfaces; single color on horizontal surface & two colors on vertical surfaces. The counter shall have a curved front made with flexible 19mm ply (Green ( Eco- Tech ) / Century / Archid) and provision of kobe lighting as per the drawings. Top of the counter & curve part shall be finished with <b>12mm thick corian</b> . Provision for 3" dia. Round /3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the counter. Teak wood lipping will be provided on all the remaining edges of the counter, including bottom touching the floor and the drawers.The counter shall have wooden keyboard rest of size 600mmx 270mm fixed on sliding telescopic channels of ebco/hettich/godrej. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.				
	(b) The counters shall have three self lockable drawers running on side mounting drawer slides (channels) of Haffele/Hettich make, made of 19mm thick commercial ply (Green ( Eco- Tech ) / Century / Archid) with 1mm thick laminate (Merino / Formica / Archid )of desired shade, design and gloss on front face & 3 nos. self locking drawer locks be provided on one side of the counter as per layout. The sides of the drawers shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 19mm thick block ply (Green ( Eco- Tech ) / Century / Archid) . All other surfaces i.e. inside / legsapce of table, inside of drawer/Cupboard shall be provided with 0.8mm thick laminate of desired shade, design and gloss, and wood lipping / beading shall be PU polished with matching pigment/deco painted in desired colour. The drawers shall have partitions for keeping currency notes as per drawing, complete in all respects including the required stainless steel hardware like handles, hinges etc.The counter shall hal also include provision of foot rest made with wooden member of section 3" x 5" along the le				
	<b>Note: The contractor to get the sample of the counter approved from the Architect before covering it with laminate without any extra cost.</b>				
<b>12</b>	<b>Night latch</b>				
	Night latch in cash cabin door - Providing and fixing night latch lock Godrej make in aluminium / wooden doors, complete in all respects.	<b>1</b>	<b>NO.</b>		
<b>13</b>	<b>GRAHAK MITRA/CRO COUNTER:</b>	<b>1</b>	<b>NO.</b>		

	(a) Providing and fixing at site counters as per the design and drawings. Table to be made of 19mm thick commercial block board with 1mm thick laminate (Merino / Formica / Archid ) of desired shade, design and gloss on outer visible surfaces; single color on horizontal surface & two colors on vertical surfaces. Provision for 3" dia. Round /3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the counter. Teak wood lipping will be provided on all the remaining edges of the counter, including bottom touching the floor and the drawers.The counter shall have wooden keyboard rest of size 600mmx 270mm fixed on sliding telescopic channels of ebco/hettich/godrej. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space. The table to have writing top of toughened glass at 1200mm level as per drawing.				
	(b) The counters shall have three self lockable drawers running on side mounting drawer slides (channels) of Haffele/Hettich make, made of 19mm thick commercial ply (Green ( Eco- Tech ) / Century / Archid) with 1mm thick laminate (Merino / Formica / Archid ) of desired shade, design and gloss on front face & 3 nos. self locking drawer locks be provided on one side of the counter as per layout. The sides of the drawers shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 19mm thick block ply. All other surfaces i.e. inside / legsapce of table, inside of drawer/Cupboard shall be provided with 0.8mm thick laminate of desired shade, design and gloss, and wood lipping / beading shall be PU polished with matching pigment/deco painted in desired colour. The drawers shall have partitions for keeping currency notes as per drawing, complete in all respects including the required stainless steel hardware like handles, hinges etc.The counter shall have a CPU ledge made of 19mm thick commercial also include provision of foot rest made with wooden member of section 3" x 5" along				
<b>14</b>	<b>SIDE CREDENZA 0.91 TO 1.06 X 0.46 X 0.76</b>				
	Side credenza made of 19mm thick commercial ply frame and 6mm thick plywood (Green ( Eco- Tech ) / Century / Archid) on back side & 1mm thick laminate (Merino / Formica / Archid ) on top horizontal surface & one vertical visible side only, with teak wood lipping on all edges including bottom touching floor. The credenza will have drawer compartment 16" wide outer to outer, containing three drawers vertically running on side mounting drawer slides(channels) of Haffele/Hettich make. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 19mm thick block board. The remaining part of the credenza will have cupboard with over-lapped shutters and one shelf. All the internal surfaces shall be finished with 0.8mm thick mica of desired shade, design, gloss and the exposed wood shall be deco painted/malamine polished in desired shade.	<b>16.00</b>	<b>Nos.</b>		
<b>15</b>	<b>LOW HEIGHT STORAGE CABINETS/BACK STORAGE: (0.76 HIGH)</b>				
	(a) Providing and fixing storage cabinets of size 2'6" (High) x 16" (Deep) along the walls/partitions, as per interior drawings, using 19mm board for carcass, shutters, vertical and horizontal partitions, 6mm ply for the back and 1mm High Gloss laminate of approved shade on vertical and horizontal visible surfaces. The shutters shall be overlapped on the carcass and shall be provided with EBCO hinges. The width of the shutter shall be between 12" to 15" as per the site conditions. All the exposed edges of the board shall be provided with wooden lipping 19mm x 3mm, duly PU polished/deco painted in desired shade. The inner surface shall be provided with 0.8mm thick laminate of desired shade, design and gloss. The cabinet shall be complete with handles, knobs, locks and magnet catchers etc. to the satisfaction of the Architect/Engineer.	<b>17.76</b>	<b>RMT</b>		
<b>16</b>	<b>STORAGE CABINET FOR GENERAL STORAGE FOR PANTRY</b>				
	Out of 19mm Commercial Ply (Green ( Eco- Tech ) / Century / Archid) finished using 1mm thick laminate (Merino / Formica / Archid) . complete with all hinges, drawer glides and hardware from Hettich or equivalent. All internal surfaces to be completed using balancing white laminate. Including D-type handles for shutters and recessed type handles for drawers. Storage Cabinets to be used for Pantry. complete in all respect as per direction of Engineer-In-Charge.				
<b>a</b>	Pantry Under Counter 2'-9" high	3.00	RMT		
<b>b</b>	Overhead Storage 2'-6" high.	3.00	RMT		
<b>17</b>	<b>MDF cutwork paneling with Duco paint</b>	<b>3</b>	<b>SQM</b>		
	Providing & fixing of Paneling on columns, made of 12mm thick commercial ply (Green ( Eco- Tech ) / Century / Archid) with 1mm thick (Merino / Formica / Archid) glossy laminate. 8mm thick external MDF with CNC cutwork as per design finish with duco paint only on side finished at workshop and to be nailed and finish at the site. All other finishes shall be done as per detail drawings and as per instructions of architect / bank's engineer. The rate to include all materials, labour, transport, taxes, etc complete. As per approved hardware list.				
<b>18</b>	<b>WOODEN BOXING FOR ELECTRICAL PANEL (10'-0" X9'-0"X2'-0")</b>	<b>1.00</b>	<b>NO.</b>		

	Providing & fixing of Electrical panel cabinete, made of 8mm thick bison panel both side for shutter. External side shall be finished with 1mm thick laminate & internal side shall be finished with backlyte sheet . All accessories like ball catches, ss handle, Fixing MS powder cotted perforeted jali shall be provided in shutter top & bottom etc. All internal frames 50mm x 25mm x 1.6mm thick section at maximum 2'-0" c/c. Complete as directed depth of cup board 1'-6". Measurement shall be based on area of front elevation of cupboard. The rate to include all materials, labour, transport, taxes, etc complete as directed. As per approved hardware list.				
19	<b>ACP SHEETS WALL PANELING IN E- LOBBY &amp; FRONT SHUTTER BOXING</b>	48.44	SQM		
	Supplying & fixing 4mm thick Aluminum component sheet of approved make <b>(ALSTRONG /ALUCOBOND/ ALSTONE )</b> and shade including making of ground of (1"X2") aluminum hollow section as per design ,with 6mm-19mm wide vertical or horizontal groove finished with Dow Cowing sealant (789) as per Architect's drawings & instructions aluminum componenet sheet should be of virgin grade and having aluminum profile thickness of 0.5mm on both sides of core. The rate is inclusive of all fixtures and fittings (with sealant) for proper finish. The works includes front face shutter boxing complete. the rate includes all required shuttering, scaffolding, labour, material, complete.				
20	<b>Writing desk / Customer Voucher Stand / Forms Stand including Pass Book, Cheque Drop &amp; Suggestion Box</b>	1	No.		
	Providing and fixing forms stand of size 4'-0" X 1'-6" X 3'-9" with 3 nos. storage units of forms with 12 mm glass top fixed with 3" SS spacer. Space for housing vouchers of size 1'6"W, 1'-0" D & 9" H is also provided on the top and on side (L-shaped, wall hung) including provision of Pass Book, Cheque Drop & Suggestion Box as per drawings made of 19 mm thick commercial ply with 1.0 mm thick laminate to be fixed and 3/4" x 1/4" teak wood lipping on two visible sides on it All exposed Teak wood edges / teak wood lipping / beading shall be spirit polished with matching pigment. etc. & to be fixed on the wall.cost of spacers ect. all inclusive complete.				
21	<b>Semi glazed wooden doors with frame :-</b>	3	NO.		
	Providing & fixing of 35mm thick semi glazed flush type doors. Doors shall be finished with 1mm thick laminate of approved colour & make with 35 x 5mm steam beach wood beading on edges of door. The glass shall be 8mm thick clear float glass with edge polishing & round smoothenend exposed edges All accessories like the door Closer , door stopper, heavy duty brass hinges, latch, handle,mortice lock lock etc shall be part of the job. All teak wood members to have melamine spray polish finish. Rate to include cost of conveyance of all materials, labour charges etc. complete as directed. As per approved hardware list.				
22	<b>FIRE PROOF DOOR FRAME</b>				
	Providing and fixing fire resistant door frame of section 143 x 57 mm having built in rebate made out of 16 SWG G.I. Sheet (zinc coating not less than 120 gm/sqm) duly filled with vermiculite based concrete mix, suitable for mounting 60 minutes fire rated door shutters. The frame is fitted with intumuscent fire seal strip of size 10x4 mm (minimum) around the frame and fixing with dash fastener of approved size and make, including applying a coat of approved brand fire resistant primer etc. complete as per direction of Engineer-in-charge (including Dash fastener).	10.37	RM		
23	<b>FIRE PROOF SHUTTER</b>				
	Providing and fixing 50 mm thick glazed fire resistant door shutters conforming to IS:3614 (Part-II), tested and certified as per laboratory approved by Engineer-in-charge, with suitable mounting on door frame, consisting of vertical styles, lock rail, top rail 100 mm wide, bottom rail 200 mm wide, made out of 16 SWG G.I. sheet (zinc coating not less than 120 gm/ m2) duly filled FR insulation material and fixing with necessary stainless steel ball bearing hinges of approved make, including applying a coat of approved fire resistant primer etc. all complete as per direction of Engineer-in- charge (paneling to be paid for separately)	3.90	SQM		
24	<b>FIRE PROOF GLASS PANEL(10" X 8")</b>				
	Providing and fixing glazing in fire resistant door shutters, fixed panels, ventilators and partitions etc., with G.I. beading of appropriate size, made out of 20 SWG G.I. Sheet (zinc coating not less than 120 gm/ m2), fire resistant sealant, including applying a coat of approved fire resistant primer on G.I. beading etc., complete all as per direction of Engineer-in-charge.	0.19	SQM		
	With clear fire resistant glass panes 6 mm thick of approved brand, having minimum 60 minutes fire resistance.				
26	<b>TROPHY CASE FOR BRANCH MANAGER AS PER DRAWING.</b>				

	Providing and fixing trophy case (12'-0" X 9'-0") using 18mm commercial ply finished in 1.0 mm thick laminate of approved Shade, Max height of the case upto false ceiling bottom , Sides and top, behind and bottom out of commercial ply and laminate. Internal shelving (3 nos. internal shelves. of the case to be done using 10 mm thk. R polished glass in shelves (The Glass fixed with u brackets). Complete with closing of all joints and accessories complete in all respect as per direction of Engineer-In-Charge.	1.00	NO.		
<b>27</b>	<b>SBI LOGO ( SIZE 2'-0" DIA )</b>				
	Providing and making SBI logo using 19mm Commercial Ply Board finished using 1mm thick laminate (blue mica). Base cost of laminate to be taken as Rs. 325/ sq. mt. complete with all hinges and hardware from Hettich or equivalent. Complete in all respect as per direction of Engineer-In-Charge.	2.00	NO.		
<b>28</b>	<b>PAINT</b>				
	Providing and applying <b>TEXTURE PAINT</b> on internal walls surfaces including surface preparation, primer coats, levelling Patti and minimum 3 coats of brush and roller finish.As per approved selected design as per architect and engineer complete job . Sample, <b>Suggested Brand Nerolac / Berger / Asian Paints.</b>	47.97	SQM		
	<b>TOTAL INTERIOR FURNISHING</b>				
	<b>BUY BACK</b> ( Buy back of existing furniture , existing partition , existing counters and existing storages ( back and side ) etc.				
	<b>SUB TOTAL</b>				