	BOQ FOR FURNITURE WORKS OF SBI, PUNAGAM BRANCH, SURAT					
	ESTIMATED BILL OF QUANTITIES			ESTIMA	TED RATE	
Sr. No.	Description	Quantity	Unit	Rate	Amount	
Note	Rate should be inclusive of material,labour,tools, mach cleaning cutting wastage etc. All taxes, transportation e paid as Applicable at the time of payment of Bills					
[A]	FURNISHING WORK				 	
1	SINGLE WINDOW COUNTER / CASH COUNTER SIZE 5'-0" X 2'-9" with White corian & blue lacquered glass finishing	4.58	RMT			
	Supplying, fixing and keeping in position single window counter complete as per design and drawing made out of 18 mm thick commercial ply wood of approved make, complete with 19 mm. C.P. Teak wood lipping on all edges wherever required.					
	The cost shall be inclusive of S & F of a drawer unit or drawer & shelf unit with 18 mm thick commercial plywood and with approved make multipurpose Auto Lock in drawer and shelf unit. The cost shall also be inclusive of the following.					
[a]	size:					
	Description: L B Ht.					
	Writing Top 5'-0" 2'-9" 2'-6"					
	4 Drawers with					
<u> </u>	pigeon hole 2'-0" 1'-3" 2'-0"					
	Computer key Board with mouse Supplying and fixing metal key Board of approved make in	ļ			<u> </u>	
	counter as per design and instructions.				1	
[b]	Working table top and edges shall be finished with 6 mm thick white corian of DUPONT or equivalent approved make as per drawing and direction with all labour and material.					
	Front Appron: 2 nos 6 mm thick flexy ply wood in round shape with 6 mm thick white corian shall be provided at front as per design. All edges should be finished with corian of DUPONT make.					
	Front pannel shall be finished with 6 mm thick 18" high blue back painted glass of approved make and fixed on 18 mm thick commercial ply wood with Natural Silicon gum as per manufacturer's specification and to be completed as per drawing					
[e]	Foot rest of 3" x 1.5" in C.P. Teak wood and CPU stand of 18 mm ply finished with 1 mm thick laminate of size 16" x 24"					
[f]	All wood work shall be laquer polished to a smooth and uniform finish of choice colour and shade.					
[g]	All fittings like S.S. handle, Auto Lock to each drawer and cabinet doors, piano / auto hinges, ball catcher, stopper, metal cable manager etc. should be fixed of approved make.					

	ESTIMATED BILL OF QUANTITIES				TED RATE
Sr. No.	Description	Quantity	Unit	Rate	Amount
[h]	Heavy duty telescopic full extension sliding channel of approved make shall be used in all drawers.				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade etc. complete				
(i)	Counter shall be made independent in Length of 5'-0" and properly placed between two partitions. Counter will be measured in RMtr between two partition and paid (FOR DETAILS REFER DRG. NO- 1)				
	FINISHING DETAILS IN NUTSHELL:				
	Table Top: 6 mm thick white corian Front Appron: Round corian and 6 mm thick Table Top: 7 mm thick Table Top: 7 mm thick Table Top: 8 mm thick Table Top: 8 mm thick Table Top: 9 mm thick Table				
	backpainted blue glass fixed with Natural Silicon 3) Facing of Drawers: 1.00 mm thick laminate finish				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate				
451.7					
1[b]	Providing and fixing 12 mm thick Toughened Glass	3.83	SQMT		
	partition on counter top, front side as follows. Providing and fixing 12 mm thick Toughened float glass with polished edges to be fixed with necessary S.S Brush finish brackets & support on wooden partition as directed with necessary cut out in glass. All edges of glass shall have Diamond cut polished edges as directed. [REFER DRG NO-1]		SQIVII		
1[c]	Providing and fixing 12mm thick Toughened float Glass partition between Single Window counters as follows.		COMT		
	12 mm thick Toughened clear float glass with polished edges shall be fixed with silicon and T.W beading support on wooden partition as directed. All edges of glass shall be Diamond cut polished edges as directed complete. Wooden partition will be paid seperately. Maximum length and height will be measured for payment purpose, REFER DRG NO-1		SQMT		
2	TABLES MANAGER TABLE SIZE: 6'-0" X 2'-9" X2'-6" HT. with 3.5 mm thick Teak veneer with PU coating finish on Table Top, sides & Edges and all other visible surfaces etc complete as follows				

	ESTIMATED BILL OF QUANTITIES				18793 17886 TED RATE
Sr. No.	Description	Quantity	Unit	Rate	Amount
	Supplying and installation of Table as per the following				
	description: Size 6'-0" x 2'-9". Table top shall be made from				
	18 mm thick commercial ply wood with 3.50 mm thick Teak				
	veneer with PU Coating with necessary intermediate support.				
	Table top shall be supported by 18 mm thick commercial ply				
	wood with wooden framing. Storage cabinet of 1'-3" \times 2'-0" \times				
	2'-6" shall be provided using 18 mm thick commercial ply				
	wood having 4 Nos drawers as directed with heavy duty telescope sliding channel of approved make, grouplock, S.S.				
	Handle. Computer Key board of metal of approved make				
	shall be provided. Exposed surfaces of the CABINET shall				
	have Teak veneer with PU polish . Foot rest of 1 1/2" x 3"				
	T.W members shall be provided. All internal surface will				
	have 0.60 mm thick balacing laminate				
	Apron (Modesty Panel) made from 18 mm thick ply wood				
	finished with teak veneer PU Finish & groove pattern				
	as per drawing Table side made from 18 mm thick ply wood with 3.50				
	mm thick teak veneer with PU coating finish shall be				
	provided in a pattern as per drawing. Veneer to be				
	provided on all visible surfaces.				
	Drawer Fascia made out of 18 mm thick Plywood. The				
	sides/back/base of drawers be made of 12 mm thick Ply				
	wood & Bottom of drawers shall be of 6 mm thick ply wood.				
	fixing veneer on front side and all the internal surfaces shall				
	be 0.60 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks				
	of approved make and 100 mm long brush finish Stainless				
	Steel handles for each drawer. All the edges of Drawer Fascia				
	be provided with teak wood edge bending with laqueer				
	polished etc complete as directed.				
	Table shall have stand for keeping CPU and metalic cable				
	Manager shall be provided in table top. All exposed edges of				
	plywood shall have veneer with smooth edges & corners				
	Exposed edges of Table Top, Leg panel & Side Shelf shall				
	be made 36 mm thick by providing additional 18 mm thick ply				
	wood patta of required width. All the internal surface (non visible surface) shall be				
	provided with 0.60 mm thick balancing laminate of				
	approved shade. Etc. complete.				
	All the surface without teak veneer / laminate / balancing				
	laminate shall be lacquered polished of approved shade				
	As per drawing and instruction of Architect/Bank work to be Completed (FOR DETAILS REFER DRG. NO- 2)				
	FINISHING DETAILS IN NUTSHELL:				
	1) Table Top: 3.5 mm thick Teak Veneer with PU Coating				
	& Burma Teak beading on Edges with PU Coating				
	2) Front Appron & Sides: 3.5 mm thick Teak Veneer with				
	PU Coating				

	ESTIMATED BILL OF QUANTITIES				98793 17886 ATED RATE
Sr. No.	Description	Quantity	Unit	Rate	Amount
	 Facing of Drawers: 3.5 mm thick Teak Veneer with PU Coating 				
	4) All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate				
2[d]	Same as above Item no-2, but size 6'-0"x 2'-6" all external surfaces including top to be finished with 1 mm thick Laminate (approved shades) including 4 nos drawer unit with same finish		NO		
	same imism	Į į	NO		
2[e]	Same as above Item-no-2 but Size: 5'-0"x2'-6" with 4 Nos Drawer Unit with 1.0 mm thick Laminate finish on all exposed surfaces		NO		
4	GRAHAK MITRA TABLE OF 2'-3" WIDE with PU coating finish				
	Same as above item no 2 but Size 2'-3" wide with storage unit in Table with 4mm thick MDF board + Blue and white PU Coating finishing on all exposed visible surface as per drawing and instruction of Architect/Bank For Grahak				
	Mitra/Tech Mitra (Help Desk Table)				
	Table top made from 18 mm thick ply wood + 4mm thick MDF board with PU coating finish				
	Apron (Front side) made from 18 mm thick ply wood + 4mm MDF board with PU Coating finish				
	Both sides made from 18 mm thick ply wood + 4mm MDF board with PU Coating finish				
	3" thick Partition above working table top made from 18 mm thick+6 mm thick ply wood with necessary framing with 4mm thick MDF board + PU Coating finish as per drawing.				
	Exposed edges of Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	Drawer Storage Unit- 1'-4" W x 2'-0" D, 2 Nos Drawer on top and rest 1 No shutter				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate				
	(FOR DETAILS REFER DRG. NO-6)				
	FINISHING DETAILS IN NUTSHELL: 1) Table Top: 18 mm Thick Plywood with 4 mm thick MDF with High gloss white PU Coating				
	2) Front Appron & Sides: 4mm thick MDF with High gloss white/blue PU Coating				
	3) Facing of Drawers: 1.0 mm thick Laminate finish				
4[a]	GRAHAK MITRA TABLE OF 2'-3" WIDE: Same as above but with Laminate finish	1.52	RMT		
	FINISHING DETAILS IN NUTSHELL: 1) Table Top: 18 mm Thick Plywood with 1.0 mm thick matt finish super white laminate AICA Make-UGM- G 324/1324 & sapphire Bule laminate G 452/1452				

	ESTIMATED BILL OF QUANTITIES			+91 98793 17886 ESTIMATED RATE		
Sr. No.	Description	Quantity	Unit	Rate	Amount	
	2) Front Appron & Sides: 1.0 mm thick high gloss super white laminate AICA Make- UGM- G 324/1324 & sapphire Bule laminate G 452/1452					
	3) Facing of Drawers: 1.0 mm thick Laminate finish					
6	CUSTOMER WRITING DESK Writing Desk Size 3'-0" L x 1'-3" x (0'-6"+3'-0") ht.	1	NO			
	Verticle Sides and bottom shall be made out of 36 mm (2X18) thick Commercial plywood and back side 12 mm thick ply wood with Laminate on Top and Edges on all sides including inside divisions. Top shall be made from 12mm th Thoughend glass with polished edges making different divisions by 18 mm thick glass / plywwod with laminate on both side for slips or forms as per detail drawing and inststruction complete. (Drawing as enclosed herewith) Laminate to be provided on all visible surface [REFER DRG NO-07]					
	SIDE CREDENZA (SIDE TABLE)					
7	Side Credenza Size 3'-3"x1'-4" x 2'-6"/3'-0" ht. Openable shutter with 3.50 mm thick Teak veneer with PU Coating finish on Top , front, sides, shutter and 35 mmx6 mm thick Burma Teak beading on Top Edges with PU Coating. Veneer to be provided only on visible surface etc complete as follows. Only Front elevation will be measured for payment purpose. (For BM) Rate for length Less then 3'-3" length					
	Supplying and installation side cabinet for keeping computer and printer of size 1'-4" width 2'-6" height and 3'-6" length having openable shutters as directed. Cabinet shall be made from 18 mm thick commercial ply wood with 3.50 mm thick veneer with PU Finish. Back shall be made from 6 mm thick commercial plywood. Openable shutters shall be made from 18 mm thick commercial ply wood with veneer finished and approved make group lock, handle, hinges, magnet catch. , Rate includes all necessary provisions for installing computers. All the internal surface, back side shall have 0.60 mm thick balacing laminate					
	Exposed edges of Sides, Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.					
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate (FOR DETAILS REFER DRG. NO- 2)					
	SIDE CREDENZA (SIDE TABLE) Same as above Item No-7, but all external surfaces to be finished with 1.0 mm thick Laminate (approved shades). Size shall be 3'-0"/3'-3" x 1'-4" x 2'-6" ht. with openable shutters as directed.	3.2	SQ.MT			
	FINISHING DETAILS IN NUTSHELL:	J.∠	JQ.IVI I			

	ESTIMATED BILL OF QUANTITIES				TED RATE
Sr. No.	Description	Quantity	Unit	Rate	Amount
	Top : Dark Laminate & Burma Teak beading on Edges with pilishade				
	2) Front Appron & Sides: Frosty White Laminate				
7[e]	SIDE CREDENZA (SIDE TABLE) For S.W Countwer Same as above item No-7 but Side Table Top and edges shall be finished with 6 mmThick White Corian on Top and Edges. All other visible surface shall be finished with 1.00 mm th laminate. Size shall be 3'-0"x 1'-4"x2'-6" bt With openable shutter as directed	3.5	SQMT		
7[f]	STORAGE CABINET with Top & Front laminate finished.		2014		
	Storage of any height (BM Back Unit) Same as above Item No-7, but all external surfaces to be finished with Laminate (approved shades) FINISHING DETAILS IN NUTSHELL: 1) Top: Dark Laminate & Burma Teak beading on Edges with pilishade		SQMT		
	Front Appron & Sides: Dark Laminate/Frosty white Laminate as per design & instructions				
7[a]	P/F ELECTRIC CUB BOARD	3.5	SQMT		
	Providing and fixing Electric cup board using 18 mm thick Bison board for inside verticle division, shelves and shutter. Aluminium framing of 50x25x1.20mm thick with 6 mm thick Bison board on both side for outer partition with 1.0 mm thick laminate on all exposed surface and polishing/ synthetic enamal paint on all internal surface. Shutter will have approved make lock, handle, hinges, ball catches & S.S Perforated jali etc.complete as directed. Depth of cup board will be around 1'-3". Height of shutter will be maximum 7'-0". Only Front elevation shall be measured for payment purpose.				
7[h]	P/F PANTRY PLATFORM CUB BOARD SHUTTER	1.0	COME		
7 [1]	Providing and fixing cupboard shutters below pantry platform using 1 1/2" x 2 1/2" second grade T.W members for frame, 18 mm Tk plywood with 1.0 mm lamiante for shutters. Providing 1/2" th T.W beading all around shutter. Providing S.S hinges, Handles, stoppers and magnetic catch as directed. All the without lamiante surface shall be polished/synthetic enamal paint as directed complete. Providing and fixing 0.60 mm thick balancing laminate on internal shutter surface		SQMT		
	LOW HEIGHT PARTITION WORK				
8[a]	PROVIDING AND FIXING WICKET GATE WITH BOTH SIDE LAMINATE	6.60	SQMT		

	ESTIMATED BILL OF QUANTITIES				98793 17886 TED RATE
Sr. No.	Description	Quantity	Unit	Rate	Amount
	Same as item no 10 but P/F 30 / 32 mm thick flush shutter with both side laminate including SS hinges with countersunk SS screws, Aprroved make Night latch Lock, S.S Handles,Door stoppers, doorstop etc complete as directed.				
8[b]	P/F LOW HEIGHT BOTH SIDE LAMINATE PARTITION WITH CLEAR FLOAT GLASS	25.09	SQMT		
	Providing and fixing low height partition using 50mm x25mm x 1.50mm thick Aluminium members maximum in grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply of approved brand on both side of aluminium framing and fixing 1.0 mm thick laminate of approved shade on both sides. Fixing 12mm thick free clear float glass as directed. Applying lacquer polish on exposed steam beach members / edges as directed. Laminate to be provided only on visible surface Providing pinup board of soft board covered with fabric and fixed in partition as per design/instruction complete as directed.				
	FULL HEIGHT PARTITION WORK				
9	P/F BOTH SIDE LAMINATE SOLID/ PARTLY GLAZED FULL HEIGHT PARTITION WITH DOOR Providing and fixing both sides laminate full height partly glazed partition using 50mm x 25mm x 1.50mm thick	16.40	SQMT		
	Aluminium members in a maximum grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply on both sides,1.0 mm laminate of approved make shall be fixed on MDF / plywood. Providing and fixing 5.0/8.0 mm thick float glass as directed in the partition. Providing and fixing door shutter using 32 mm thick flush shutter both side laminated and fixing 6 mm thick glass with beading patti, 5" Long 3 Nos stainless steel hinges, doorstop shall be provided as directed. Godrej Mortice lock shall be provided in door shutter. All visible members if not laminated shall have lacquer polished as directed. [REFER DRG NO-5]				
10[a]	Providing and fixing UPS door shutter with Aluminium				
	Frame and both side Hilux sheet Providing and fixing door shutter made out of	1.8	SQMT		
	50x25x1.5mm thick aluminium framing at maximum 1'-6" C/C both way with 8 mm thick Hilux Board on both side with painting. Providing 6 mm thick clear float glass vision panel secured with 12 mm thick steam beach beading. Steam beach beading of size 31x 12 mm should be placed around shutter edges, aluminium stoper patti on frame including 3 Nos 5" long SS hinges with countersunk SS screws, Aprroved make Dead Lock, S.S Handles, Door stoppers, doorstopper to be fixed as per drawing & instructions. All beadings should be polished.				
	CLASS DOODS AND DARTITIONS				
	GLASS DOORS AND PARTITIONS				

ESTIMATED BILL OF QUANTITIES				98793 17886 ATED RATE
Description	Quantity	Unit	Rate	Amount
GLASS DIAPHARM FOR SEPARATING TWO M/C FOR E-LOOBY P /F 12mm th Toughened glass Diapharm between two	4	SQMT		
directed. Glass edges shall be round moulded and polished as per direction. Glass shall be fixed in wall and floor with				
DANIELLING WORK				
PANELLING WORK				
Pillar etc	31.30	SQMT		
mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium. framing of 25mmx25mmx1.20mm thick at maximum 2'-0"				
		RMT		
Panelling for Digital wall with Blue / white high gloss PU				
Coating finishing	16.4	SQMT		
Board exterior grade with PU coating fixed on wall with Aluminium framing of 25mm x 25mm x 1.20 mm thick at maximum 2'-0" c/c bothways etc. complete as directed. Only				
P/A WALL PAPERS on Digital wall	6.8	SOMT		
Providing and applying Wall paper approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft		J SQ IVI I		
ELEVATION for BRANCH AND ATM ROOM IN SIDE WALL		SQMT		
	PROVIDING AND FIXING 12 MM THICK TOUGHENED GLASS DIAPHARM FOR SEPARATING TWO M/C FOR ELOOBY P /F 12mm th Toughened glass Diapharm between two machines with etching and frosting Films complete as directed. Glass edges shall be round moulded and polished as per direction. Glass shall be fixed in wall and floor with necessary suitable patch fittings as directed. (Area based on outer diameters shall be measured and paid). PANELLING WORK P/F Wall panelling with laminate finishing for wall and Pillar etc Providing and laying panelling on walls & pillars having 12 mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium. framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways on wall and pillar etc complete as directed as per design and instruction of Architect Providing and fixing 18 mm thick plywood of 4" height with 1.0 mm thick laminate finish runner patta on Storage Top / Table Top if required.etc complete as directed. Panelling for Digital wall with Blue / white high gloss PU Coating finishing Providing and laying panelling on wall having 8mm th MDF Board exterior grade with PU coating fixed on wall with Aluminium framing of 25mm x 25mm x 1.20 mm thick at maximum 2'-0" c/c bothways etc. complete as directed. Only finished visible surface area shall be measured for payment. P/A WALL PAPERS on Digital wall Providing and applying Wall paper approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft	PROVIDING AND FIXING 12 MM THICK TOUGHENED GLASS DIAPHARM FOR SEPARATING TWO M/C FOR ELOOBY P /F 12mm th Toughened glass Diapharm between two machines with etching and frosting Films complete as directed. Glass edges shall be round moulded and polished as per direction. Glass shall be fixed in wall and floor with necessary suitable patch fittings as directed. (Area based on outer diameters shall be measured and paid). PANELLING WORK P/F Wall panelling with laminate finishing for wall and Pillar etc Providing and laying panelling on walls & pillars having 12 mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium. framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways on wall and pillar etc complete as directed as per design and instruction of Architect. Providing and fixing 18 mm thick plywood of 4" height with 1.0 mm thick laminate finish runner patta on Storage Top / Table Top if required etc complete as directed. Providing for Digital wall with Blue / white high gloss PU Coating finishing Providing and laying panelling on wall having 8mm th MDF Board exterior grade with PU coating fixed on wall with Aluminium framing of 25mm x 25mm x 1.20 mm thick at maximum 2'-0" c/c bothways etc. complete as directed. Only finished visible surface area shall be measured for payment. P/A WALL PAPERS on Digital wall Providing and applying Wall paper approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft ALUMINUM COMPOSITE PANEL FOR FRONT SIDE ELEVATION for BRANCH AND ATM ROOM IN SIDE WALL	PROVIDING AND FIXING 12 MM THICK TOUGHENED GLASS DIAPHARM FOR SEPARATING TWO M/C FOR ELOOBY P /F 12mm th Toughened glass Diapharm between two machines with etching and frosting Films complete as directed. Glass edges shall be round moulded and polished as per direction. Glass shall be fixed in wall and floor with necessary suitable patch fittings as directed. (Area based on outer diameters shall be measured and paid). PANELLING WORK P/F Wall panelling with laminate finishing for wall and Pillar etc Providing and laying panelling on walls & pillars having 12 mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium. framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways on wall and pillar etc complete as directed as per design and instruction of Architect. Providing and fixing 18 mm thick plywood of 4" height with 1.0 mm thick laminate finish runner patta on Storage Top / Table Top if required.etc complete as directed. Providing for Digital wall with Blue / white high gloss PU Coating finishing Providing and laying panelling on wall having 8mm th MDF Board exterior grade with PU coating fixed on wall with Aluminium framing of 25mm x 25mm x 1.20 mm thick at maximum 2'-0" c/c bothways etc. complete as directed. Only finished visible surface area shall be measured for payment. P/A WALL PAPERS on Digital wall Providing and applying Wall paper approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft ALUMINUM COMPOSITE PANEL FOR FRONT SIDE ELEVATION for BRANCH AND ATM ROOM IN SIDE WALL	PROVIDING AND FIXING 12 MM THICK TOUGHENED GLASS DIAPHARM FOR SEPARATING TWO M/C FOR ELOOBY P /F 12mm th Toughened glass Diapharm between two machines with etching and frosting Films complete as directed. Glass edges shall be round moulded and polished as per direction. Glass shall be fixed in wall and floor with necessary suitable patch fittings as directed. (Area based on outer diameters shall be measured and paid). PANELLING WORK P/F Wall panelling with laminate finishing for wall and Pillar etc Providing and laying panelling on walls & pillars having 12 mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium. framing of 25mmx25mmx1.20mm thick at maximum 2-0° c/c bothways on wall and pillar etc complete as directed as per design and instruction of Architect Providing and fixing 18 mm thick plywood of 4" height with 1.0 mm thick laminate finish runner patta on Storage Top / Table Top if required etc complete as directed. Providing and laying panelling on wall having 8mm th MDF Board exterior grade with PU coating fixed on wall with Aluminium framing of 25mm x 25mm x 1.20 mm thick at maximum 2-0° c/c bothways etc. complete as directed. Only finished visible surface area shall be measured for payment. P/A WALL PAPERS on Digital wall Providing and applying Wall paper approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft ALUMINUM COMPOSITE PANEL FOR FRONT SIDE ELEVATION for BRANCH AND ATM ROOM IN SIDE WALL

	ESTIMATED BILL OF QUANTITIES			+91 98793 17886 ESTIMATED RATE		
Sr. No.	Description	Quantity	Unit	Rate	Amount	
	Providing and fixing 3 mm thick aluminium composite panel of Flexi Bond / Euro Bond / Timex with 0.25 mm foil with 50 mm x 25 mm x 1.20 mm thick aluminium hollow section tray system with minimum 20 mm bending with silicon Dow Coming of GE seal proof - ACP of approved indian make complete as per selection and direction of Architect for front facade for the building. This item will be carried out as per manufacturer's specifications. Rate also includes providing trap door shutter with hinges, stoppers etc complete as directed. Design as per Bank standered Drawing and Architect's instructions etc complete. TIMEX - DIAMOND WHITE - 111, NAVY BLUE - 117 or equivalent					
	The second secon					
	FALSE CEILING WORK					
13	P/F GYPSUM BOARD FALSE CEILLING Providing and fixing Gypsum board 12.50 mm thick false ceiling in steps and design using Original Indian Gypsum board with original GI sheet section of Gypsteel ULTRA (Gypsteel Ultra shall be used) supporting system in line and level. Finishing the surface and applying 3 coats of Plastic emulsion paint as directed complete. Entire work to be done as per standard specifications of Saint Gobin Gyproc India. After completion of work, certificate from Saint Gobain Gyproc Company shall be submitted along with bill stating that work is satisfactorily completed as per their specification. Note: (1) Rate includes making necessary cut-outs for lighting fixtures (2) Pattas if any shall be measured in SqM and not in RMt and paid in SqM (3) Only finished visible surface area shall be measured for payment.		SMT			
13[d]	Providing and Fixing of Armstrong Mineral Fibre Accoustical Suspended ceilling system with FINE FISSURED (MICRO LOCK) EDGE TILES With Armstrong Silhouette Exposed Grid	94.46	SMT			
	Using Silhouette Grid with Fine Fissured microlook Edge Tiles. With necessary Angles at junctions as per company specifications as directed complete. Rate includes necessary cut outs for A/C Grills, diffusers light fixtures complete as directed. Cutout for light and Diffusers will be deducted from area. Only Tiles cost will be deducted for payment purpose					
	After completion of work, certificate from Company to be obtained and submitted with bill that work is carried out as per their specifications					
1/1	SOFT BOARD	3.5	SQMT			
_ 14	סטו ו שטאונט	٥.٥	OKIVII			

	ESTIMATED BILL OF QUANTITIES				98793 17886 ATED RATE
Sr. No.	Description	Quantity	Unit	Rate	Amount
	Providing & fixing soft board for pin up using moulded Steam beach frame of 1" x 1/2" with 6 mm thick commercial plywood on back side and 12mm th soft board on front covered with cloth of selected design of Basic rate of Rs. 150 per Rmt. Steam beach member shall have lacquer polish as directed.				
15	Supplying and fixing Roller Blind Blackout of approved make with selected fabric of approved design and shade. (Basic Price of Rs 135=00 Per Sq.Ft Including GST)		SQMT		
16	Providing and Fixing Frosted polyster film of 3M (Scotchcal 7725 - 324) or equivalent make over glass surface as per drawing & direction with all labour & materials to the satisfaction of the Architect/Bank as per manufacturer's specification. No deduction will be made for any cutting in the film.		SQMT		
18	Providing and fixing "Dorma/Ozone/Godrej " or equivalent make door closure.	3	NO		
19	Supplying and installation 3'-0" x 1'-9"x 1'-3" height Center Tepoy as follows. Providing and making open box structure type Tepoy made out of 36 mm (2X18) thick plywood with all over 1.0 mm thick	2	NO		
	laminate finish provided with bevelled & diamond polished edges 12mm thick glass top supported on 75 mm X 25 mm SS studs complete as directed.				
20	Sofa - (2 to 3)seater Making of 2 to 3 seater sofa with 18mm ply frame structure as per architect's design. Work includes all kind of lining work with 5" thk. Foam seat foam & 2" thk. Back foam of approved density (40 kg/m^3) to be covered with fabric (range-600rs./m) of approved colour & texture. 3" long SS legs to be provided and fixed to the sofa.		rmt		
21	TOTAL				- (+GST AS APPLICABLE