AT SBI PALSANA BRANCH. ARCHITECTS : SOPAN, 202,RIVER PALACE WING-B NANPURA SURAT-395001	
ARCHITECTS : SOPAN, 202, RIVER PALACE WING-B NANPURA SURAT-395001	
TELEPHONE NOS : 02612471302 (o) M: 09825117854	
E-MAIL : sopanrise@gmail.com, sopanssurat@gmail.com	

SITE ADDRESS : PALSANA, SURAT BOQ – FURNITURE AND FIXTUTRE WORK , SBI PALSANA BRANCH

NO.	ITEM	QTY	UNIT	RAT	E AMOUNT
Note :	Rate should be inclusive of material, labour, tools, machinery,	scaffoldi	ng, final	disposal of	debris, cleaning
	cutting wastage etc. All taxes, transportation etc. complete. (Ex the time of payment of Bills				
[A]	FURNISHING WORK				
1	SINGLE WINDOW COUNTER / CASH COUNTER SIZE 5'-0" X 2'- 9" with White corian & blue lacquered glass finishing	4.60	RMT		
	Supplying, fixing and keeping in position single window counter complete as per design and drawing made out of 18 mm thick commercial ply wood of approved make, complete with 19 mm. C.P.				
	Teak wood lipping on all edges wherever required. The cost shall be inclusive of S & F of a drawer unit or drawer & shelf unit with 18 mm thick commercial plywood and with approved make multipurpose Auto Lock in drawer and shelf unit. The cost shall also be inclusive of the following.				
[a]	size :				
	Description:         L         B         Ht.           Writing Top         5'-0"         2'-9"         2'-6"				
	4 Drawers with				
	pigeon hole 2'-0" 1'-3" 2'-0"				
	Computer key Board with mouse				
	Supplying and fixing metal key Board of approved make in counter as per design and instructions.				
[b]	Working table top and edges shall be finished with 6 mm thick white corian of DUPONT or equivalent approved make as per drawing and direction with all labour and material.				
[c]	Front Appron : 2 nos 6 mm thick flexy ply wood in round shape with 6 mm thick white corian shall be provided at front as per design. All edges should be finished with corian of DUPONT make.				
[d]	Front pannel shall be finished with 6 mm thick 18" high blue back painted glass of approved make and fixed on 18 mm thick commercial ply wood with Natural Silicon gum as per manufacturer's specification and to be completed as per drawing				
[e]	Foot rest of 3" x 1.5" in C.P. Teak wood and CPU stand of 18 mm ply finished with 1 mm thick laminate of size 16" x 24"				
[f]	All wood work shall be laquer polished to a smooth and uniform finish of choice colour and shade.				
[g]	All fittings like S.S. handle, Auto Lock to each drawer and cabinet doors, piano / auto hinges, ball catcher, stopper, metal cable manager etc. should be fixed of approved make.				
[h]	Heavy duty telescopic full extension sliding channel of approved make shall be used in all drawers.				
[i]	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade etc. complete				
[j]	Counter shall be made independent in Length of 5'-0" and properly placed between two partitions. Counter will be measured in RMtr between two partition and paid (FOR DETAILS REFER DRG. NO-1)				
	FINISHING DETAILS IN NUTSHELL:				
	1) Table Top: 6 mm thick white corian				

NO.	ITEM	QTY	UNIT	RATE	AMOUN
	2) Front Appron: Round corian and 6 mm thick backpainted blue				
	glass fixed with Natural Silicon				
	<ul><li>3) Facing of Drawers: 1.00 mm thick laminate finish</li><li>4) All the internal surface (non visible surface) shall be provided with</li></ul>				
	0.60 mm thick balancing laminate				
1[b]	Providing and fixing 12 mm thick Toughened Glass partition on				
	counter top, front side as follows.	3.50	SQMT		-
	Providing and fixing 12 mm thick Toughened float glass with polished				
	edges to be fixed with necessary S.S Brush finish brackets & support on wooden partition as directed with necessary cut out in glass. All				
	edges of glass shall have Diamond cut polished edges as directed.				
	[REFER DRG NO-1]				
	Providing and fixing 12mm thick Toughened float Glass partition between Single Window counters as follows.	1.40	SQMT		_
	12 mm thick Toughened clear float glass with polished edges shall	1.40	JOUNT		
	be fixed with silicon and T.W beading support on wooden partition				
	as directed. All edges of glass shall be Diamond cut polished edges				
	as directed complete. Wooden partition will be paid seperately.				
	Maximum length and height will be measured for payment purpose,				
	REFER DRG NO-1				
	TABLES				
2	MANAGER TABLE SIZE: 6'-0" X 3'-0" X2'-6" HT. with 3.5 mm				
	thick Teak veneer with PU coating finish on Table Top , sides &				
	Edges and all other visible surfaces and 12mm thick clear				
1	glass with bevelled edge polish on Top etc complete as follows	1.00	NO		_
	Supplying and installation of Table as per the following description :				
	Size 6'-0" x 2'-9". Table top shall be made from 18 mm thick				
	commercial ply wood with 3.50 mm thick Teak veneer with PU				
	Coating with necessary intermediate support. Table top shall be				
	supported by 18 mm thick commercial ply wood with wooden framing. Storage cabinet of 1'-3" x 2'-0" x 2'-6" shall be provided using 18 mm				
	thick commercial ply wood having 4 Nos drawers as directed with				
	heavy duty telescope sliding channel of approved make, grouplock,				
	S.S. Handle. Computer Key board of metal of approved make shall				
	be provided. Exposed surfaces of the CABINET shall have Teak				
	veneer with PU polish . Foot rest of 1 1/2" x 3" T.W members shall				
	be provided. All internal surface will have 0.60 mm thick balacing				
	laminate Apron (Modesty Panel) made from 18 mm thick ply wood				
	finished with teak veneer PU Finish & groove pattern as per				
	drawing				
	Table side made from 18 mm thick ply wood with 3.50 mm thick				
	teak veneer with PU coating finish shall be provided in a pattern				
	as per drawing. Veneer to be provided on all visible surfaces.				
	Drawer Fascia made out of 18 mm thick Plywood. The				
	sides/back/base of drawers be made of 12 mm thick Ply wood &				
	Bottom of drawers shall be of 6 mm thick ply wood. fixing veneer on				
	front side and all the internal surfaces shall be 0.60 mm thick				
	balancing laminate. The drawers to be fitted with Telescopic sliding				
	channel with SS Group locks of approved make and 100 mm long				
	brush finish Stainless Steel handles for each drawer. All the edges of				
	Drawer Fascia be provided with teak wood edge bending with laqucer				
ŀ	Table shall have stand for keeping CPU and metalic cable Manager				
	shall be provided in table top. All exposed edges of plywood shall				
	have veneer with smooth edges & corners				
	Exposed edges of Table Top, Leg panel & Side Shelf shall be made				
	36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	All the internal surface (non visible surface) shall be provided				
	with 0.60 mm thick balancing laminate of approved shade. Etc.				
	complete.				

NO.	ITEM	QTY	UNIT	RATE	AMOUN
	All the surface without teak veneer / laminate / balancing laminate				
	shall be lacquered polished of approved shade				
	As per drawing and instruction of Architect/Bank work to be Completed (FOR DETAILS REFER DRG. NO- 2)				
	FINISHING DETAILS IN NUTSHELL:				
	1) Table Top : 3.5 mm thick Teak Veneer with PU Coating &				
	Burma Teak beading on Edges with PU Coating				
	2) Front Appron & Sides: 3.5 mm thick Teak Veneer with PU				
	Coating				
	3) Facing of Drawers: 3.5 mm thick Teak Veneer with PU Coating				
	4) All the internal surface (non visible surface) shall be provided				
	with 0.60 mm thick balancing laminate				
2[d]	Same as above Item no-2, but size 6'-0"x 2'-9" all external				
	surfaces including top to be finished with 1 mm thick Laminate				
	(approved shades)		NO		-
2[e]	Same as above Item-no-2 but Size: 5'-0"x2'-6" with 4 Nos Drawer				
z[e]	Unit with 1.0 mm thick Laminate finish on all exposed surfaces				
		4.00	NO		-
4	GRAHAK MITRA TABLE OF 2'-3" WIDE with PU coating finish	1.50	RMT		-
	Same as above item no 2 but Size 2'-3" wide with storage unit in				
	Table with 4mm thick MDF board + Blue and white PU Coating				
	finishing on all exposed visible surface as per drawing and				
	instruction of Architect/Bank For Grahak Mitra/Tech Mitra (Help Desk				
	Table) Table top made from 18 mm thick ply wood + 4mm thick MDF board				
	with PU coating finish				
	Apron (Front side) made from 18 mm thick ply wood + 4mm MDF				
	board with PU Coating finish				
	Both sides made from 18 mm thick ply wood + 4mm MDF board with				
	PU Coating finish				
	3" thick Partition above working table top made from 18 mm thick+6				
	mm thick ply wood with necessary framing with 4mm thick MDF				
	board + PU Coating finish as per drawing.				
	Exposed edges of Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	Drawer Storage Unit- 1'-4" W x 2'-0" D, 2 Nos Drawer on top and				
	rest 1 No shutter				
<u> </u>	All the internal surface (non visible surface) shall be provided with				
	0.60 mm thick balancing laminate				
	(FOR DETAILS REFER DRG. NO-6)				
	FINISHING DETAILS IN NUTSHELL:				
	1) <b>Table Top</b> : 18 mm Thick Plywood with 4 mm thick MDF with				
	High gloss white PU Coating           2) Front Appron & Sides:         4mm thick MDF with High gloss				
	white/blue PU Coating				
	3) Facing of Drawers: 1.0 mm thick Laminate finish				
5	DINING TABLE Approx Size 5'-0"/ 6'-0"x 3'-0"	1.80	SQ MT		-
	Supplying and installation of Dining Table of 2'-6" height, 1" x 1.5" ht.				
	T.W beading shall be fixed on border. Top shall be made of 18 mm				
	thick commercial plywood with additional 18 mm thick Ply wood patta				
	of required width on edges with 1.0 mm thick laminate on top of				
	approved shade and supports of the Table shall be made of 2" x 2" T.W. members in a Design as directed. All surfaces not laminated				
	shall be lacquer polished.				
	Exposed edges of Table Top shall be made 36 mm thick by providing				
	additional 18 mm thick ply wood patta of required width.				
			NO		

NO.	ITEM	QTY	UNIT	RATE	AMOUN
	Verticle Sides and bottom shall be made out of 36 mm (2X18) thick Commercial plywood and back side 12 mm thick ply wood with Laminate on Top and Edges on all sides including inside divisions. Top shall be made from 12mm th Thoughend glass with polished edges making different divisions by 18 mm thick glass / plywwod with laminate on both side for slips or forms as per detail drawing and inststruction complete. (Drawing as enclosed herewith) Laminate to be provided on all visible surface [REFER DRG NO-07]				
	SIDE CREDENZA (SIDE TABLE)				
7	Side Credenza Size 3'-3"x1'-4" x 2'-6"/3'-0" ht. Openable shutter with 3.50 mm thick Teak veneer with PU Coating finish on Top, front, sides, shutter and 35mmx 6mm thick Burma Teak beading on Top Edges with PU Coating. Veneer to be provided only on visible surface etc complete as follows. Only Front elevation will be measured for payment purpose. (For BM) Rate				
	for length Less then 3'-3" length	1.00	SQ.MT		-
	Supplying and installation side cabinet for keeping computer and printer of size 1'-4" width 2'-6" height and 3'-6" length having openable shutters as directed. Cabinet shall be made from 18 mm thick commercial ply wood with 3.50 mm thick veneer with PU Finish. Back shall be made from 6 mm thick commercial plywood. Openable shutters shall be made from 18 mm thick commercial plywood with veneer finished and approved make group lock, handle, hinges, magnet catch. , Rate includes all necessary provisions for installing computers. All the internal surface, back side shall have 0.60 mm thick balacing laminate				
	Exposed edges of Sides, Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate (FOR DETAILS REFER DRG. NO- 2)				
7[i]	Same as above item but Storage Cabinate Length more then 3'- 3" length	3.10	SQ.MT		-
7[b]	SIDE CREDENZA (SIDE TABLE) Same as above Item No-7, but all external surfaces to be finished with 1.0 mm thick Laminate (approved shades). Size shall be 3'-0"/3'-3" x 1'-4" x 2'-6" ht. with openable shutters as directed.	7.20	SQ.MT		-
	FINISHING DETAILS IN NUTSHELL: 1) Top : Dark Laminate & Burma Teak beading on Edges with silichade				
	pilishade 2) Front Appron & Sides: Frosty White Laminate				
7[e]	SIDE CREDENZA (SIDE TABLE) For S.W Countwer Same as above item No-7 but Side Table Top and edges shall be finished with 6 mmThick White Corian on Top and Edges. All other visible surface shall be finished with 1.00 mm th laminate. Size shall be 3'-0"x 1'-4"x2'-6" ht. With openable shutter as directed	7.90	SQMT		
7[f]	STORAGE CABINET with Top & Front laminate finished. Storage of any height	4.65	SQMT		
	Same as above Item No-7, but all external surfaces to be finished with Laminate (approved shades)	1.00	CQIVIT		
	FINISHING DETAILS IN NUTSHELL: 1) Top : Dark Laminate & Burma Teak beading on Edges with pilishade				
	2) Front Appron & Sides: Dark Laminate/Frosty white Laminate as per design & instructions				
	P/F ELECTRIC CUB BOARD	4.70	SQMT		

NO.	ITEM	QTY	UNIT	RATE	AMOUN
	Providing and fixing Electric cup board using 18 mm thick Bison board				74110011
	for inside verticle division, shelves and shutter. Aluminium framing of				
	50x25x1.20mm thick with 6 mm thick Bison board on both side for				
	outer partition with 1.0 mm thick laminate on all exposed surface and				
	polishing/ synthetic enamal paint on all internal surface. Shutter will				
	have approved make lock, handle, hinges, ball catches & S.S.				
	Perforated jali etc.complete as directed. Depth of cup board will be				
	around 1'-3". Height of shutter will be maximum 7'-0". Only Front				
	<b>3</b>				
	elevation shall be measured for payment purpose.				
7[h]	P/F PANTRY PLATFORM CUB BOARD SHUTTER	1.52	SQMT		
	Providing and fixing cupboard shutters below pantry platform using 1	1.52	SQIVIT		-
	1/2" x 2 1/2" second grade T.W members for frame, 18 mm Tk				
	plywood with 1.0 mm lamiante for shutters. Providing 1/2" th T.W				
	beading all around shutter. Providing S.S hinges, Handles, stoppers				
	and magnetic catch as directed. All the without lamiante surface shall				
	be polished/ synthetic enamal paint as directed complete.Providing				
	and fixing 0.60 mm thick balancing laminate on internal shutter surface				
-	LOW HEIGHT PARTITION WORK				
8	P/F LOW HEIGHT BOTH SIDE LAMINATE PARTITION FOR				
	BACK SIDE AND IN BETWEEN S.W COUNTER AND CASH CABIN				
	WITH TOUGHENED GLASS	11.00	SQMT		-
	Providing and fixing low height partition using 50mm x 25mm x				
	1.50mm thick Aluminium members maximum in grid of 2'-0" x 2'-0"				
	fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply of				
	approved brand on both side of aluminium framing and fixing 1.0 mm				
	thick laminate of approved shade on both sides, fixing 12 mm thick				
	transparent thoughened glass as directed. Applying polish on				
	exposed steam beach members with lacquer polished edges as				
	directed. Laminate to be provided only on visible surface [FOR				
	DETAILS REFER DRG. NO- 1]				
	For Low height Single window and Cash cabin partition,				
	Average height of partition shall be measured and paid.				
8[a]	PROVIDING AND FIXING WICKET GATE WITH BOTH SIDE	1.70	SOMT		
	LAMINATE Same as item no 10 but P/F 30 / 32 mm thick flush shutter with	1.70	SQIVIT		-
	both side laminate including SS hinges with countersunk SS screws,				
	Aprroved make Night latch Lock, S.S Handles, Door stoppers, doorstop etc complete as directed.				
8[b]	P/F LOW HEIGHT BOTH SIDE LAMINATE PARTITION WITH	1 60	SUNAT		
	CLEAR FLOAT GLASS	4.60	SQMT		-
	Providing and fixing low height partition using 50mm x25mm x				
	1.50mm thick Aluminium members maximum in grid of 2'-0" x 2'-0"				
	fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply of				
	approved brand on both side of aluminium framing and fixing 1.0 mm				
	thick laminate of approved shade on both sides. Fixing 12mm thick				
	free clear float glass as directed. Applying lacquer polish on exposed				
	steam beach members / edges as directed. Laminate to be provided				
	only on visible surface Providing pinup board of soft board covered				
	with fabric and fixed in partition as per design/instruction complete as				
	directed.				
	FULL HEIGHT PARTITION WORK				
9	P/F BOTH SIDE LAMINATE SOLID/ PARTLY GLAZED FULL				
-	HEIGHT PARTITION WITH DOOR	5.00	SQMT		-
	· · · · · · · · · · · · · · · · · · ·				

NO.	ITEM	QTY	UNIT	RATE	AMOUN
	Providing and fixing both sides laminate full height partly glazed partition using 50mm x 25mm x 1.50mm thick Aluminium members in a maximum grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board				
	exterior grade / 6 mm thick ply on both sides,1.0 mm laminate of approved make shall be fixed on MDF / plywood. Providing and fixing 5.0/8.0 mm thick float glass as directed in the partition. Providing and				
	fixing door shutter using 32 mm thick flush shutter both side laminated and fixing 6 mm thick glass with beading patti, 5" Long 3				
	Nos stainless steel hinges, doorstop shall be provided as directed. Godrej Mortice lock shall be provided in door shutter. All visible members if not laminated shall have lacquer polished as directed.[REFER DRG NO-5]				
	For purpose of payment partition height up to bottom of false ceilling only shall be measured and paid . No extra payment shall be made for members going up to slab/beam bottom.				
9[a]	Same as above item no-9 specification but P/F ONE SIDE 3.5 mm THICK TEAK VENEER WITH PU COATING AND OTHER SIDE LAMINATE SOLID / PARTLY GLAZED FULL HEIGHT PARTITION FOR MANAGER CABIN	24.00	SQMT		
10	Providing and fixing Isolated flush door shutter (Partly Glazed	21.00			
	and Partly Laminate) with frame as follows. Providing and fixing 4"x2" steam beach member for frame and	12.20	SQMT		-
	Flush door shutter made out of 32 mm thick flush door with 6 mm thick clear float glass vision panel secured with 12 mm thick steam beach beading, 32 x 12 mm thick steam beach periphery patti around shutter edges, 1 mm thick laminate on both sides, 35x12mm thi				
	thick steam beach stopper patti on frame including 3 Nos 5" long SS hinges with countersunk S S screws, Aprroved make Dead Lock, S.S Handles,150 mm long Door stoppers, doorstop of approved make etc. All exposed surface /edges not laminated be provided with lacquer polish. Work to be completed as per drawing & instructions [REFER DRG NO-5]				
40[0]	Providing and fixing UPS / Recoed room door shutter with				
	Aluminium Frame and both side Hilux sheet Providing and fixing door shutter made out of 50x25x1.5mm thick aluminium framing at maximum 1'-6" C/C both way with 8 mm thick Hilux Board on both side with painting. Providing 6 mm thick clear float glass vision panel secured with 12 mm thick steam beach beading. Steam beach beading of size 31x 12 mm should be placed around shutter edges, aluminium stoper patti on frame including 3 Nos 5" long SS hinges with countersunk SS screws, Aprroved make Dead Lock, S.S Handles,Door stoppers, doorstopper to be fixed as per drawing & instructions. All beadings should be polished.	2.10	SQMT		
	GLASS DOORS AND PARTITIONS				
11	P & F FULLY GLAZED DOOR WITH PATCH FITTINGS for Entrance Door For Branch Head cabin, entry, audit room Providing & Fixing fully glazed main door at the main entrance and	12.70	SQMT		-
	ATM. The Item includes fixing of <b>12 mm th. Toughened glass</b> with the help of <b>top patch &amp; bottom patch fittings.</b> The door				
	will have patch lock, pti pivot, 100 Kg floor spring & 25mm dia D shape 400 mm long handles both sides, <b>(Ozone Make OGH-</b>				
	<b>55P11-25X400),</b> fixed with the glass by making necessary cutouts & holes. The glass edges shall be polished on all sides. The entire door shall be erected in complete line &				
	level. The door will have S.S brush finish Signage for pull & push.				
	The patch fittings (Ozone make) shall be of aluminium with s,s, matt finish coating & signage shall be of kich make. The entire door complete in all respect should be installed in positions as required.				

NO.	ITEM	QTY	UNIT	RATE	AMOUN
11[a]	Same as above item but P & F FULLY GLAZED PARTITION With Patch Fitting for front side of Main Entrance [FIXED PORTION] For				
	Branch and E-Lobby	18.00	SQMT		-
11[b]	PROVIDING AND FIXING 12 MM THICK TOUGHENED GLASS DIAPHARM FOR SEPARATING TWO M/C FOR E-LOOBY	5.90	SQMT		_
	P /F 12mm th Toughened glass Diapharm between two machines with etching and frosting Films complete as directed. Glass edges shall be round moulded and polished as per direction. Glass shall be fixed in wall and floor with necessary suitable patch fittings as directed. (Area based on outer diameters shall be measured and paid).				
	PANELLING WORK				
12	P/F Wall panelling with laminate finishing for wall and Pillar etc	9.30	SQMT		-
	Providing and laying panelling on walls & pillars having 12 mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium. framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways on wall and pillar etc complete as directed as per design and instruction of Architect.				
12[b]	Same as above item no 12 but Providing & Fixing 3.5 mm thick Veneer with PU coating finishing over aluminium framing panelling for wall panelling etc in Manager Cabin				
		6.20	SQMT		-
12[c]	Creating Box for fixing AC machine and concealing of copper and drain pipe and around front side main entrance door top, jambs using <b>18 mm thick MR Grade plywood</b> with 1.00 mm Thick Laminate to be fixed over alumininum framing of 25 X 25 X 1.2 mm as per requirement and drawing etc complete as directed.				
		1.50	SQMT		-
12[f]	Panelling for Display wall with 3M Vinyl glossy Film with printed design	2.28	SQMT		-
	Providing and laying panelling on wall having 8 mm th MDF Board exterior grade with 3M vinyl glossy films with printed design fixed on wall with Aluminium framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways etc. complete as directed. panelling as per design and instruction of Architect. MDF board to be finished with 0.60 mm thick laminate or paint before laying 3M film. Only Front elevation area shall be measured for payment purpose.				
	Exposed edges of Display wall four side shall be made 36 mm thick by providing additional required thickness MDF patta of required width.				
12[g]	Panelling for Digital wall with Blue / white high gloss PU Coating finishing Providing and laying panelling on wall having 8mm th MDF Board	3.50	SQMT		-
	exterior grade with PU coating fixed on wall with Aluminium framing of 25mm x 25mm x 1.20 mm thick at maximum 2'-0" c/c bothways etc. complete as directed. Only finished visible surface area shall be measured for payment.				
12[j]	P/A WALL PAPERS on Digital wall	9.00	SQMT		-
·	Providing and applying <b>Wall paper</b> approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft				
12[k]	ALUMINUM COMPOSITE PANEL FOR FRONT SIDE ELEVATION for BRANCH AND ATM ROOM IN SIDE WALL AND OUT SIDE	65.20	SQMT		

NO.	ITEM	QTY	UNIT	RATE	AMOUN
	Providing and fixing 3 mm thick aluminium composite panel of Flexi Bond / Euro Bond / Timex with 0.25 mm foil with 50 mm x 25 mm x 1.20 mm thick aluminium hollow section tray system with minimum 20 mm bending with silicon Dow Coming of GE seal proof - ACP of approved indian make complete as per selection and direction of Architect for front facade for the building. This item will be carried out as per manufacturer's specifications. Rate also includes providing trap door shutter with hinges, stoppers etc complete as directed. <b>Design as per Bank standered Drawing and Architect's instructions etc complete. TIMEX - DIAMOND WHITE - 111, NAVY BLUE - 117 or</b>				
	equivalent				
13	FALSE CEILING WORK P/F GYPSUM BOARD FALSE CEILLING	71.10	SMT		-
	Providing and fixing Gypsum board 12.50 mm thick false ceiling in steps and design using Original Indian Gypsum board with original GI sheet section of Gypsteel ULTRA (Gypsteel Ultra shall be used) supporting system in line and level. Finishing the surface and applying 3 coats of Plastic emulsion paint as directed complete. Entire work to be done as per standard specifications of Saint Gobin Gyproc India. After completion of work, certificate from Saint Gobain Gyproc Company shall be submitted along with bill stating that work is satisfactorily completed as per their specification.				
	Note : (1) Rate includes making necessary cut-outs for lighting				
	fixtures (2) Pattas if any shall be measured in SqM and not in RMt and paid in SqM (3) Only finished visible surface area shall be measured for payment.				
13[a]	Same as above item but providing and fixing of 8 mm thick Hilux board false ceiling instead of Gypsum Board for Item No-13 etc complete as per design and instruction. Only finished surface area shall be measured for payment.		SMT		-
13[b]	Same as above but providing and fixing of 8 mm thick MDF board strip with Blue shade high gloss PU Coating instead of Gypsum Board for Item No-1 over Transaction Area etc complete as per design and instruction. Only finished surface area shall be measured for payment.		SMT		<u>-</u>
13[c]	Same as above but providing and fixing 6 mm thick ply covered with 1 mm thick blue shade laminate		SMT		-
13[d]	Providing and Fixing of Armstrong Mineral Fibre Accoustical Suspended ceilling system with FINE FISSURED (MICRO LOCK) EDGE TILES With Armstrong Silhouette Exposed Grid Using Silhouette Grid with Fine Fissured microlook Edge Tiles. With necessary Angles at junctions as per company specifications as directed complete. Rate includes necessary cut outs for A/C Grills, diffusers light fixtures complete as directed. <b>Cutout for light and</b> <b>Diffusers will be deducted from area. Only Tiles cost will be deducted for payment purpose</b>	121.00	SMT		
	After completion of work, certificate from Company to be obtained and submitted with bill that work is carried out as per their specifications				
13[e]	Replacing of existing broken 600 mmx600 mm Armstrong Mineral Fibre Accoustical tiles matching with existing armstong tiles etc. complete as directed including alignment		NO		-
13[f]	Dismantling of existing gypsum/POP false ceiling including stacking				
10[1]	of serviceable materials and disposal of unserviceable materal.		SQMT		-

NO.	ITEM	QTY	UNIT	RATE	AMOUNT
	Providing & fixing soft board for pin up using moulded Steam beach frame of 1" x 1/2" with 6 mm thick commercial plywood on back side and 12mm th soft board on front covered with cloth of selected design of Basic rate of Rs. 150 per Rmt. Steam beach member shall have lacquer polish as directed.				
15	Supplying and fixing Roller Blind Blackout of approved make with selected fabric of approved design and shade. (Basic Price of Rs 135=00 Per Sq.Ft Including GST)	8.80	SQMT		-
16	Providing and Fixing Frosted polyster film of 3M (Scotchcal 7725 - 324) or equivalent make over glass surface as per drawing & direction with all labour & materials to the satisfaction of the Architect/Bank as per manufacturer's specification. No deduction will be made for any cutting in the film.	11.23	SQMT		-
16[a]	Extra Plotter Cutting charges for Frosted films as per drawing & direction with all labour & materials to the satisfaction of the Architect/Bank	11.23	SQMT		-
17	Supplying and installation Dressing Table with Puffy as follows.	1.00	NO		
	Dressing Table shall have 1'-6" x 4'-0" size 5mm thick mirror with 1 $1/2$ " x 3" T.W frame and 12 mm thick BWR plywood 2'-0" x 6" size with 1 mm thick laminate on top and having polished edges / bottom supported by brass bracket 2 Nos. as directed.				-
	Puffy shall be made of using TW member of size 2"x2" and 18 mm th.plywood for seat support. Seat shall be padded with 4" foam covered with hession cloth and upholstered with Approved shade and quality fabric. Basic price of fabric shall be Rs.400 per Rmt. Visible wooden support shall be polished. Size of Puffy shall be 1'6"x1'6".				
40	Description and fining "Description (October 10 adapting and the second second				
18	Providing and fixing "Dorma/Ozone/Godrej " or equivalent make door closure.	7.00	NO		-
18[a]	Providing and fixing "Dorma/Ozone/Godrej " or equivalent make 100 Kg Floor Spring.		NO		
19	Supplying and installation 3'-0" x 1'-9"x 1'-3" height Center Tepoy as follows.	1.00	NO		-
	Providing and making open box structure type Tepoy made out of 36 mm (2X18) thick plywood with all over 1.0 mm thick laminate finish provided with bevelled & diamond polished edges 12mm thick glass top supported on 75 mm X 25 mm SS studs complete as directed.				
19[a]	Same as above but size 1'-9" x 1'-9" x 1'-3" height for Corner				
	Тероу	1.00	NO		-
20	DR E SOEA SEATING 2/2 contor				
20	P& F SOFA SEATING 3/2 seater P & S of Visitors sofa. The seat shall be made out of 19 mm BB in a box form. The back shall be made out using internal wooden frame work of size 2"x1 ½" covered with 6 mm ply. It shall be covered with 100 mm & 50 mm th. 40 density u foam in seat & back respectively. This should be again covered with 14 mm th. 40 density u foam with madarpat cover on it & upholstered of suggested shade & finish in seat & back on all open visible sides with basic rate of Rs.1000/- per meter. It will have Metal PVD coating legs, / drawing. outer length with armrest will be considered for measurement purpose.	1.40	R.MT		-
	TOTAL COST "A"				
Note:					
[a]	In all furniture work, contractor shall make necessary cutout in panelling/partitions / wooden members to facilitate electrical/data cabelling and No extra amount shall be paid for this				
[b]	All internal surface (non visible surfaces) shall be provided with the 0.60 mm thick balacing laminate of aproved make & shade in the all S.W Counters/Tables/ Credenza,Storage Cup Board etc.				

NO.	ITEM	QTY	UNIT	RATE	AMOUNT
[B]	BUY BACK OF OLD FURNITURE				
	Dismantling of entire furniture and fixtures from existing	1.00	Lot		
	premises and buy back of furniture which is not required by				
	Bank, as follows				-
	TOTAL COST OF BUY BACK "B"				
	SUMMARY				
[A]	FURNISHING WORK				-
[B]	BUY BACK OF OLD FURNITURE		(-)		
	NET TOTAL COST [A-B]				
	GST as applicable extra				

NO.	ITEM
-----	------

NO.	ITEM
-----	------

NO.	ITEM

NO.	ITEM

NO.	ITEM
-----	------