

BOQ FOR INTERIOR FURNISHING WORK
SBI COLLECTORATE BRANCH, DEHRADUN

S.No	ITEM SPECIFICATION	UNIT	QTY	RATE	Amount
1	<p><u>Single Window Counter (1500x900x750 mm) without Side Credenza</u> Providing and fixing in position 750 mm high single window counter without side credenza. Side Credenza shall be paid in separate item where ever required. SWC shall consist of:</p> <p>a) 19mm thick BWP grade block board for Top (1500 x 900 mm), Front (1500x750 mm), Two sides and one middle member (each 900x750 mm).</p> <p>b) 400 mm wide Drawer unit having 3 drawers of equal sizes made of 12 mm thick BWP grade ply of approved make with Godrej auto locking push type locks and "C" type SS finish handles.</p> <p>c) Ebco/Godrej make telescopic sliding key board tray.</p> <p>d) All exposed surfaces shall be clad with 1 mm thick laminates of approved make and shade except edges, which shall be covered with teakwood round and half-round polished beading as directed by the Engineer-in-charge.</p> <p>e) All un-exposed surfaces shall be clad with 0.8 mm thick laminates of approved make and shade.</p>	Each	2.00		
2	<p><u>Providing , fitting & fixing flexible solid surface as specified below:</u> Providing fitting and fixing 6mm thick flexible solid surfaces of approved shades to table top, low height storage unit tops, CNC cut corian jali in column panelling etc or any other places as directed with acrylic epoxy including edge finishing and moulds. The job is to be executed through authorized applicator only as per the bank's specification and requirement. The work should include all necessary materials, accessories and labour. All materials should be approved by the bank. Actual executed plan &/ or elevation area of the surface work shall be measured for finished work.</p>	SQM	10.00		
3	<p><u>Work station for BM (1800 mmx900mmx750mm) without Side Credenza :</u> Supply & fixing in position branch head table (size 3' x 6' x 2--6") as per design made out of 19 mm thick BWP grade ply with 4mm th. /teak veneer with high glass PU FINISH on table top complete. Drawers shall have ball bearing slides & locks etc. complete internal surface shall be finished with 0.8 mm thick laminated with high glass white laminate. each table shall have the provision of key board with ball bearing slides Arrangement 12 mm in Toughened glass top & 12mm in Toughened glass modesy panel .The provision of side trac (upto 4' x 2.5" as per site) is included in the rate . The Design will be as per drawing approved</p>	Each	1.00		

4	<u>Work station for Officer without Side Credenza</u> : Providing and fixing work station for Feild Officer with same specification as item no. 1 above (Single Window Counter) but having only one drawer and one cupboard in place of three drawers as mentioned in item 1(b). The drawer should be provided with auto locking Godrej key system.	Each	1.00		
5	<u>Side Credenza (950X450X750) for SWC :</u> Providing and fixing in position Side Credenza made of 19mm thick BWP grade block board (Top: 1200 mm x 450 mm) having 1 drawer unit (450 W x 150 H mm) at the top made of 12 mm thick BWP grade ply of approved make complete with Godrej multipurpose drawer locks and "C" type SS finish handles and one cupboard (450 W x 500 H mm) at bottom with telescopic sliding drawers as above with auto closing hinges for the shutters of the cupboards. The unit shall be complete with SS finish "C" type handles with locking arrangement. All exposed surfaces shall be cladded with 1 mm thick laminates of approved make and shade except edges, which shall be covered with teakwood round and halfround polished beading as directed by the Engineer-in-charge. All un-exposed surfaces shall be cladded with 0.8 mm thick laminates of approved make and shade complete in all respect as per the drawing and direction of Engineer-in-charge.	Each	2.00		
6	<u>Side Credenza (950X450X750) for Branch Manager.FO and Service Manager:</u> Providing and fixing in position Side Credenza made of 19mm thick BWP grade block board (Top: 1200 mm x 450 mm) having 2 drawer unit (450 W x 150 H mm) at the top made of 12 mm thick BWP grade ply of approved make complete with Godrej multipurpose drawer locks and "C" type SS finish handles and one cupboard (900 W x 500 H mm) at bottom with telescopic sliding drawers as above with auto closing hinges for the shutters of the cupboards. The unit shall be complete with SS finish "C" type handles with locking arrangement. All exposed surfaces shall be cladded with 1 mm thick laminates of approved make and shade except edges, which shall be covered with teakwood round and half-round polished beading as directed by the Engineer-in-charge. All un-exposed surfaces shall be painted with 2 coates of synthetic enamel paint over a coat of wooden primer of approved make and shade complete in all respect as per the drawing and direction of Engineer-in-charge.	Each	2.00		
7	<u>12 mm thick Glass fixed in SWO Front/ Profile Glass in between Counters:</u> Providing and fixing 12mm toughened glass of approved make in SWO counters and other locations as directed by engineer with edge polish fixed using D bracket with cash transaction holes 6""to 7"x6""to 7"as directed and polished	Sqm	2.50		
8	<u>10 mm thick Glass fixed in Table Top:</u> Providing and fixing 12mm toughened glass of approved make in SWO counters and other locations as directed by engineer with edge polish fixed using D bracket with cash transaction holes 6""to 7"x6""to 7"as directed and polished	Sqm	8.00		
9	<u>Toughned Glass Door</u> Providing & erecting fully glazed frame less glass doors made out of 12 mm thk. Toughened glass work with pencil polish edges all around. Glass door shall be fixed with top edge fixed to MS support structure/ beams/ roof lintel/ wooden frame work with necessary patch fittings. Rate is to be inclusive of all required necessary hardware fittings i.e. door handles/ bottom locks etc. and etching as directed by Engineer-in-charge. However floor spring is to be paid separately.	Sqm	2.1		

10	<u>Toughned Glass Panel</u> Providing & erecting fully glazed toughned glass partitions made out of 12 mm thk. Toughened glass work with pencil polish edges all around. Glass panels shall be fixed with top edge fixed to MS support structure/ beams/ roof lintel/ wooden frame work with necessary patch fittings. Rate is to be inclusive of all required necessary hardware fittings and etching as directed by Engineer-in-charge. However floor spring (item no 16) is to be paid separately.	Sqm	10		
11	<u>Floor Spring</u> Providing and fixing floor spring of Godrej/ Dorma/ Haffle make in floors for fixing of Toughned Glass Doors capable of withstanding 100 kg weight with 0.3 million cycles rating along with pivot of same make on top.	Pair	1		
12	<u>Double Skin Solid Partition:</u> Supplying, fitting and fixing double skin solid partition for specified enclosure, made out of 25mm x 50mm X 2 mm size locally available aluminium stud frame at 600 x 600mm c/c bothways and fixed with 6mm thk. BWP ply, exposed surface clad with 1mm mirror/matt finish laminates on both sides of enclosure, glass portion of the partition will be paid separately. The vertical members shall go beyond the false ceiling level and fixed to the soffit of R.C.C. slab/beam along with one extra top member. The bottom member and top member shall be fixed to the R.C.C. floor/roof slab with wedge bolt and rawl plugs at suitable intervals. All materials are to be of approved make, shade and quality. The rate shall include cost of all materials, labour, taxes, T&P, transportation, royalties etc. for complete work. The measurement shall be done upto false ceiling level and no extra payment shall be made for framework or for the ply or laminate above the ceiling level. Necessary provisions to be made in the partition for fixing of 8 mm thk Glass	Sqm	20		
13	<u>Doors for partition</u> P&F 35mm thickness BWP grade flush door finished with 6mm thick teak wood lipping on all edges duly polished, three SS Hinges for each door, one door stopper, one mortise lock/ Night Latch combo set per door finished with 1mm thickness laminates on both sides of approved shade and colour (solid and glazed with 5.5mm thickness float glass). Make: Kitply/ Mayor/SylvaN as approved, Hinge: Dorset/ equiv, Lock: Godrej/ Dorset.	Sqm	8.40		
14	<u>Display Board / Notice board:</u> P&F pin up notice board made of 12mm backing ply duly laminated on one side and other side sandwiched with 12mm soft board. The soft board is covered by a light blue fabric and the stripped with teak wood lipping all around include edges with hooks for hanging.	Sqm	1.50		
15	<u>Voucher Stand / Writing Ledger :</u> P&F wall/ column mounted writing desk having size of 4'x1'6"x8"depth with slots spaced @8" centers made of BWP grade 19mm Block board on all sides and 6mm backing ply with slots of 8"x8"spaced @ 8"centers.All surfaces shall be laminated with 1mm thick laminates with edges teak wood lipping duly polished	Running Meter	1.50		

16	<p><u>Storage Cabinet:</u> Storage units 450mm deep: Made with 19mm BWP grade Block board on all five sides and 6mm backing ply. Vertical separators shall be provided at each 3' Centres with door leaf of each shutter of 18" wide supported by auto closing hinges. All inside surface shall be finished with 0.80mm thick laminate. Exposed surface including shutter edges shall be finished 1mm laminate of approved shade. Hardwraes like locks, handles shall be provided. Make: Mr Ply: Kit ply/Century/green/mayoor, Laminate: Kit ply/century/green/Marino; Hardware Godrej/ebco/ Hettich as approved Make:</p>	Sqm	8.00		
17	<p><u>CPU Trolley:</u> Providing and supplying mobile metal CPU trolley manufactured by M/s Godrej / EBCO attached with 4 wheels for holding CPU and for its smooth movement.</p>	Each	4.00		
18	<p><u>Armstrong Ceiling :</u> Modular false ceiling with armstrong make Rh-99 anf tegular edge 600x600 x15mm as specified by manufacturer. Installation to comprise main runner at 1200 centers fixed to structural outfits. First and last Armstrong suspension system should not be greater than 6000 from adjacent wall. 600x600 cross tees shall be provided between 1200 tees. M6 anchor fastner with verticle hangers made of galvanised steel 26x26x25x1.2mm , a pre straight hanger wire 2.68mm dia, adjustable hookss clipss of 0.8mm thick spring steel of 2.68mm shall be used.</p>	Sqm	60.00		
19	<p><u>Wall Panelling:</u> Providing wall/ column panelling with AL Section frame work spaced @ 600X 600, fixed with 8 mm thk. BWP ply having cladding of 1 mm thk Laminates, bending moulding etc. as per instructions of Engineer-in-charge</p>	Sqm	65.00		
20	<p>Providing and fixing Shutter Boxing for rolling shutter made up of Aluminium Composite Panel (ACP) sheets only on the outer visible side with framing of aluminium tube sections of min. 2" x 1" and 20 gauge at a spacing of 2' center to center both ways. ACP to be of bright silver shade in 2' width panels or distributed equally. ACP sheets to be fixed to the frame with 3M make adhesive along with mirror screws. Joints to be finished with silicon based sealant. ACP sheets to be min. 3mm thick with aluminum foil thickness to be min. 0.25mm on both sides. Item includes providing trap door of required size in the bottom of the shutter boxing made up of Aluminium Composite Panel (ACP) sheets only on the outer visible side with framing of aluminium tube sections as specified above along with Godrej make heavy duty tower bolts, required numbers of 3" SS hinges, handles etc. complete. Item includes providing additional sections to fix LED down-lighters which will be installed at the required position.</p> <p>Note: Only front of boxing including trap door shall be measured for payment purpose and sides of the boxing shall not be measured for payment.</p> <p>(Make: Alubond/ Eurobond/ Alcobond/ Aludecor).</p>	Sqm	1		

21	<p>Providing and fixing in position Aluminium Composite Paneling (ACP) with framing of aluminium tube sections of min. 2" x 1" and 20 gauge at a spacing of 2' center to center both ways. ACP to be of bright silver shade in 2' width panels or distributed equally. ACP sheets to be fixed to the frame with 3M make adhesive along with mirror screws. Joints to be finished with silicon based sealant. ACP sheets to be min. 3mm thick with aluminum foil thickness to be min. 0.25mm on both sides. Item includes providing additional sections to fix indoor AC units which will be installed at the highest position.</p> <p>(Make: Alubond/ Eurobond/ Alcobond/ Aludecor).</p>	Sqm	8		
					Total

GST Extra as applicable