SI.		5			
No.	Qty.	Description	Rate	Unit	Amount
1		Fully Glazed Partitions			
	80.00	Slim line partition of approved make :- Supply and installation of full height straight glass partition 10 mm thick toughened glass and proprietary electroplated as approved colour with aluminium sections of the SLIM LINE TWIN STYLE TWIN PRO SECTION NO. 6633 (35mm x 25mm) and 6634 (35mm x 20mm) male and female sections providing inside with rubber gaskets in top & bottom upto false ceiling level. The glass joints shall be filled with silicon sealant on both side . Rate shall include for providing transport charges, handling, loading and unloading, Installation, protecting the module and glass till handing over, testing, commissioning all necessary hardware's, scafolding, wastage, Structural supports if any, etc. complete and all as per manufacturers specifications as directed. Etching stickers are to be provided as per design. The partition is to be firmly fixed to the floor and ceiling. The partition up to false celing only be measured.			
2a		Fully Clared Deer (Single shutter)		M ²	0.00
za	15.00	Fully Glazed Door (Single shutter) Providing and fixing fully glazed door of 10 mm thick toughned glass			
	13.00	with pencil polish edges alround with etching patterns and bevelled at edges. The door shall be fixed with DORMA / Hafele/ Hettich/GEZE patch fitting assembily inclusive of top and bottom patches, floor springs, bottom locks,SS brushed handle of 60 cm long and 2.5 cm dia .Lock of approved make etc to be fixed to the door, the edge of the glass to be polished		2	
01				M ²	0.00
2b	5.00	Fully Glazed Door (Double shutter) Providing and fixing fully glazed door of 10 mm thick toughned glass with pencil polish edges alround with etching patterns and bevelled at edges. The door shall be fixed with DORMA / Hafele/ Hettich/GEZE patch fitting assembily inclusive of top and bottom patches, floor springs, bottom locks,SS brushed handle of 60 cm long and 2.5 cm dia .Lock of approved make etc to be fixed to the door, the edge of the glass to be polished		M^2	0.00
3		MODULAR PARTITION (120cm (H))			

SI. No.	Qty.	Description	Rate	Unit	Amount
		65 to 75mm thick powder coated 1.2mm thick CRCA partitions (Manufactured by Godrej/Metafab/Fether Lite/Methodox/ Victory any approved makes) with pre punched cutouts to run electric & networking cables. Dual Race ways with punch out to fix electrical & data modules for power & data at just below table and skirting level. Partitions are covered with 9 mm tiles both sides prelaminated particle board/Fabric Cladded Board/glass/soft board as required by using sliding panel method. Level adjusters and all the visible edges of partitions are covered with 2mm thick powder coated Aluminium trims & pvc joinery.			
				M^2	0.00

SI. No.	Qty.	Description	Rate	Unit	Amount
4		Double Skin Solid partition			
	60.00	The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of aluminium section of 50x50x1.2 mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 9 mm thick marine grade plywood (IS 303) on both sides and finished with 1 mm thick laminate on both sides. The partition is to be firmly fixed to the floor and ceiling. The partition up to false celing only be measured.		M^2	0.00
4a		Flush Door in Partitions (Both Side Laminated)		1 1	
	13.00	Providing and fixing 40mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwitched with 6 mm thick 303 Grade (BWR) Plywood and both sides finished with 1 mm thick Laminate of aproved colour and make. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no:s of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, door closer etc.			
				M ²	0.00
5	== 00	Wall / Column panelling			
	75.00	The frame work of panelling should be of aluminum rectangular section of size 50 mm x 25 mm x 1.5 mm both horizontaly and verticaly at 60 cm c/c. which is covered with 6 mm thick 303 grade marine plywood finished with 1 mm thick laminate as shown in the drawing.		M^2	0.00
6		Fire Rated Cement Partition		1	
	22.00	The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of aluminium rectangular section of 50x50x2 mm thick of internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 6 mm thick fire rated cement board on both sides finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer The partition is to be firmly fixed to the floor and ceiling.		M ²	0.00
6a		Partly Glazed Door			
	3.00	Door is to be provided with Aluminium frame of size 50x50x2 cm alround and intermediates at 60cmc/c and it is covered with 6 mm thick fire rated cement board on both sides and finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer .			

SI. No.	Qty.	Description	Rate	Unit	Amount
		A 8 mm thick glass is provided at a height of 75cm from bottom. Necessary Fittings such as 4Nos. 125 mm Anodised ball bearing hinges, 1No. godrej lock of approved make, 1 pair of stainless steel handle to each shutter, automatic hydraulic door closer etc. to be provided.			
				M^2	0.00

SI. No.	Qty.	Description	Rate	Unit	Amount
7		Cupboards			
		The width and height of the cupboard is shown in the drawing. All horizontal and vertical partitions, rear side and cupboard doors are made of 16 mm thick 303 grade marine plywood finished with 1 mm thick laminate of approved colour.			
		The front portion of the cupboard is to be provided with openable shutters using 16 mm thick marine plywood finished and all the exposed faces are finished with 1 mm laminate and the inner sides with 0.8 mm thick laminate			
		Necessary fittings such as cabinet hinges, Magnetic lock, ball catches, 200 mm long SS finish handles etc should be provided in each shutter. Necessary 2 mm thick PVC edgebanding shall be given in all visible/ exposed edges. Skirting for a height of 10cm should be provided as per the drawing.			
7a	10.00	Cupboard 45cm width and 75 cm height		M^2	0.00
7b	40.00	Cupboard 45cm width and 120 cm height		M ²	0.00
7c	9.00	Cupboard 45cm width and 230 cm height		M ²	0.00
8		False Ceiling (Plain Gypsum Board)			
	425.00	Providing and fixing suspended false ceiling, which includes providing and fixing G.I perimeter channels of size 27mm, 0.5mm thick having one flange of 20mm and another flange of 30mm along with perimeter of ceiling, screw fixed to brick wall / partition with the help of nylon rawl plugs and screws.			
		Then suspending G.I intermediate channels of size 45mm, 0.9mm thick with two flanges of 15mm each from the soffit at 1200mm centres in one direction and 600mm in other with ceiling angle of width 25x25x0.5mm thick fixed to soffit with G.I cleat & steel expansion fastners.			
		Ceiling section of 0.5mm thickness having knurled wedge of 51.5mm and flanges of 26mm each with lips of 10.5mm are then fixed to intermediate channel with the help of connecting clips and in direction perpendicular to the intermediate channel at 600mm centres.12.5mm tappered edge Moisture resistant gipboard is then screw fixed to ceiling sections with 25mm dry wall screw at 230mm centres.			
		Screw fixing is done mechanically either with screw driver or drilling machine with suitable attachment. Finally the tapered and square edges of the boards are jointed and finished to a flush with requisite jointing compound, tapes and finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer			
		Necessary steppings and cuttings for electrical fittings, security devices, fire fighting equipments etc. as per the directions at site and arrangements for fixing the electrical and other fittings are to be provided. (Refer ceiling plan).		M^2	0.00

SI. No.	Qty.	Description	Rate	Unit	Amount
9		Roller Blind			
	140.00	Supplying and providing zebra type roller blinds with smooth operations using manual and clutch roller controlled by a continuous cord loop. The blind is to be fixed within the window opening. The fabric shall be of sun screening quality and of approved shade. Top Roller and bottom roller to be provided with powder coated Aluminium.		M^2	0.00
10		Table for AGM 180X90x75 cm			
	3.00	Providing and fixing tables made out of 16mm thick 303 grade marine plywood of approved make finished with 1 mm thick laminate in all visible areas. The inner sides are with 0.8 mm thick laminate. Ready made keyboard tray made out of powder coated MS sheet mounted under the worktop with telescopic sliding channels. A country wood foot rest of size 7.5x2.5cm is also provided. 12mm thick glass is to be provided on table top and the edges of glass to be polished. Provision for cable manager is to be provided. Drawers are made of 16mm thick 303 grade marine plywood and exposed faces are finished with 1 mm thick laminate and inner sides with 0.8 mm thick laminate as shown in the drawing. Necessary fittings such as steel slides, godrej lock, handles etc. of approved make are to be provided. One Drawer set contains three numbers are to be provided. Necessary grooves in laminate are to be provided as shown in drawings. All the visible/exposed edges shall be provided with 2 mm thick PVC edgebanding.			
				No	0.00
11		Table for CM (HR)160x80x75 cm			
	1.00	Providing and fixing tables made out of 16mm thick 303 grade marine plywood of approved make finished with 1 mm thick laminate in all visible areas. The inner sides are with 0.8 mm thick laminate. Ready made keyboard tray made out of powder coated MS sheet mounted under the worktop with telescopic sliding channels. A country wood foot rest of size 7.5x2.5cm is also provided. 12mm thick glass is to be provided on table top and the edges of glass to be polished. Provision for cable manager is to be provided. Drawers are made of 16mm thick 303 grade marine plywood and exposed faces are finished with 1 mm thick laminate and inner sides with 0.8 mm thick laminate as shown in the drawing. Necessary fittings such as steel slides, godrej lock, handles etc. of approved make are to be provided. One Drawer set contains three numbers are to be provided. Necessary grooves in laminate are to be provided as shown in drawings. All the visible/exposed edges shall be provided with 2 mm thick PVC edgebanding.			
40		, , , , , , , , , , , , , , , , , , ,		No	0.00
12		Table for MGR, PA 150x75x75 cm			

SI. No.	Qty.	Description	Rate	Unit	Amount
	2.00	Providing and fixing tables made out of 16mm thick 303 grade marine plywood of approved make finished with 1 mm thick laminate in all visible areas. The inner sides are with 0.8 mm thick laminate. Ready made keyboard tray made out of powder coated MS sheet mounted under the worktop with telescopic sliding channels. A country wood foot rest of size 7.5x2.5cm is also provided. 12mm thick glass is to be provided on table top and the edges of glass to be polished. Provision for cable manager is to be provided.			
		Drawers are made of 16mm thick 303 grade marine plywood and exposed faces are finished with 1 mm thick laminate and inner sides with 0.8 mm thick laminate as shown in the drawing. Necessary fittings such as steel slides, godrej lock, handles etc. of approved make are to be provided. One Drawer set contains three numbers are to be provided. Necessary grooves in laminate are to be provided as shown in drawings. All the visible/exposed edges shall be provided with 2 mm thick PVC edgebanding.			
13		Work station 150x150		No	0.00
	30.00	Supplying and fixing table made out of 25mm thick interior grade both side prelaminated particle board with exposed top edges lipped with 2mm thick PVC edgeband applied with hot melt glue and other edges with 0.5mm thick PVC edge band all round panel and Gromet is proveded for wire management. Modesty Panel, hardwares like minifix powder coated clipboard screws, PVC right angle block, level adjustes etc. Foot rest are made of 18mm prelaminate particle board with 0.5mm thick PVC edge band knok down type bottom bush etc.30cm wide and 15cm height at one end and the other end is zero 50cm length fixed on the bottom side of the table etc. complete.			
10				No	0.00
13a	30.00	DRAWER UNIT Supplying and fixing Drawer unit made out of 18mm thick interior grade both side prelamiated particle board . 4 drawer pullouts mounted on sliders, with exposed edges lipped with PVC edge band 0.5mm thick central locking system for drawer pullouts (Ebco/Doorset/Hettich /Ozone), with bottom bush with necessary shutters to be provided.		No	0.00
13b		KEYBOARD TRAYS		1 1	
	30.00	Supplying and installing Keyboard tray made out of powder coated MS sheet exposed edges lipped with PVC edge band 0.5mm thick mounted under the worktop with telescopic sliding channelsEbco or other approved		No	0.00
13c		CPU TROLLEYS			

SI. No.	Qty.	Description	Rate	Unit	Amount
	30.00	Supplying and installing CPU Trolleys made out of powder coated 1.6 mm thick MS sheet with adjustable width, front & back open & provided with lockable castors .Ebco or other approved		No	0.00
14a		GM works station		1.10	0.00
	1.00	The size of the work station is 340x110x75 cm with side table 120x45cm and rear desk 340x45x75 cm. The table top is with 19 mm thick marine plywood with verticals as shown in the drawing. Drawers are made of 12mm thick marine plywood and exposed faces are finished with 1 mm laminate and inner sides with enamel paint finish as shown in the drawing. One drawer set consist of three drawers. Necessary fittings such as steel slides, godrej lock, handles etc. of approved make are to be provided. One cable manager is to be provided as shown in the drawing.			
		A keyboard tray is made of 12mm thick marine plywood finished with 1 mm laminate supported by steel slides. 12mm thick glass to be provided for table top and the edges of the glass to be polished. A foot rest with country wood of 7.5x2.5cm also to be provided.			
				No	0.00

SI. No.	Qty.	Description	Rate	Unit	Amount
14b	6.00	Providing and fixing coloured glass over the exposed faces of the GM work stations		M ²	0.00
14c		Table 90x90 cm			
	1.00	The table top and verticals are made up of 16 mm thick marine plywood of approved make finished with 1 mm laminate as shown in the drawing .The inner sides are with 0.8 mm thick laminate. All the visible/exposed edges shall be provided with 2 mm thick PVC edgebanding.		No	0.00
15		VC Room Table 483x110x75 cm			
	1.00	The width and height of the table is 110 cm and 75 cm respectively. The length of the table is 483cm as shown in the drawing. The table top is made of 25mm thick 303 grade marine plywood with 1mm thick laminate and 25mm thick 303 grade marine plywood as verticals at 90cm c/c. All the exposed faces are finished with 1mm thick laminate and inner sides with 0.8mm thick laminate.			
		12 mm thick glass with polished edges to be provided on the table top. All the visible/exposed edges shall be provided with 2 mm thick PVC edgebanding.		No	0.00
16		Dining table 110x90x75 cm			
	4.00	Supplying and fixing Stainless steel table 304 grade as per detailed drawing (enclosed). The table top are made of 19 mm granite slab (Basic price Rs.2200/Sqm) and the edges of the slabs are rounded and polished as per the direction of the authorites.		No	0.00
17		Side Tables AGM / CM (HR)120x45x75 cm			
	4.00	Providing and fixing side tables made out of 16 mm thick marine plywood of approved make finished with 1 mm thick laminate in all visible areas as shown in the drawing. Ready made keyboard tray made out of powder coated MS sheet mounted under the worktop with telescopic sliding channels. File rack with sliding shutters shall be made of 16 mm thick marine plywood finshed with 1 mm thick laminate by using Aluminium sliding channel, sliding cabnet shutter fittings (Ebco/Equivalent), lock and key, 5cm SS handle. CPU stand is provided in the side table. The inner sides are with 0.8 mm thick laminate. 12mm thick glass is to be provided on table top and the edges of glass to be polished. All the visible/exposed edges shall be provided with 2 mm thick PVC edgebanding.			
		promote man 2 min and 1 10 daysbanding.		No	0.00

SI. No.	Qty.	Description	Rate	Unit	Amount
18	٦٠,	Side Tables 100x45x72.5 cm	Nutc	1	Amount
	2.00	Providing and fixing side tables made out of 16 mm thick marine plywood of approved make finished with 1 mm thick laminate in all visible areas as shown in the drawing. Ready made keyboard tray made out of powder coated MS sheet mounted under the worktop with telescopic sliding channels. File rack with sliding shutters shall be made of 16 mm thick marine plywood finshed with 1 mm thick laminate by using Aluminium sliding channel, sliding cabnet shutter fittings (Ebco/Equivalent), lock and key, 5cm SS handle. CPU stand is provided in the side table. The inner sides are with 0.8 mm thick laminate. 12mm thick glass is to be provided on table top and the edges of glass to be polished. All the visible/exposed edges shall be provided with 2 mm thick PVC edgebanding.			
40		Aut D T. I.I. 400 45 75		No	0.00
19	1.00	Anti Room Table 123x45x75 cm The table top and verticals are made up of 16 mm thick marine plywood of approved make finished with 1 mm laminate as shown in the drawing .The inner sides are with 0.8 mm thick laminate. All the visible/exposed edges shall be provided with 2 mm thick PVC edgebanding. Provision for cable manager is to be provided.			
				No	0.00
_		TOTAL (A)			0.00
1 1	7.00	CIVIL WORK			
1	7.00	Demolishing brick work in cement mortar manually / by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in -Charge.		M ³	0.00
2	5.00	Dismantling doors, windows and celerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking 50 metres lead as per direction of Engineer - in -Charge.		No	0.00
3	4.00	Brick work with common burnt clay F.P.S.(non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in. Cement mortar 1:6 (I cement : 6 coarse sand) for closing the area of doors and windows etc complete as per the specifications		M ³	0.00
4	1.00	Providing and laying in position ready mix concrete of grade M 25 for reinforced cement concrete work including cost of all form work watering, curring etc complete but excluding cost of reinforcement for pantry slab		M ³	0.00

SI. No.	Qty.	Description	Rate	Unit	Amount
5	100.00		110.00		7 0 0
		Steel reinforcement for R.C.C. work including straightening, cutting,			
		bending,placing in position and binding all complete above plinth			
		level.Thermo-Mechanically Treated bars of grade Fe-500D or more.		Kg	0.00
6	3.00	Supplying & fixing powder coated aluminum openable windows and		T\9	0.00
		ventilators using aluminium 34 series z,j,gulliain glacing clips section			
		S,S friction hinges locking handles rubber beedings etc glazed with 4		M^2	0.00
7	50.00	mm clear glasses.		141	0.00
	00.00	Plastering with CM 1:4, 12mm thick (1 cement & 4 sand) 12mm thick			
		one coat floated hard and traveled smooth to walls including all staging work watering, curing etc complete.		2	
	475.00	3. 3. 1		M ²	0.00
8	1/5.00	Finishing plastered wall with one coat primer, 2 coat of putty and			
		painted with 2 coat of plastic emulsion paint after cleaning the surface. Approved make of paint: Asian, Berger, Nerolac		M^2	0.00
9	500.00			IVI	0.00
9	500.00	Painting the walls with two coat plastic emulsion paint after cleaning the surface etc complete. Approved make of paint: Asian, Berger,			
		Nerolac		M^2	0.00
10	175.00	Deinting with synthetic enemal point 2 cost over a priming cost to			0.00
		Painting with synthetic enamel paint 2 coat over a priming coat to new wood work and iron work after cleaning the surface.		M^2	0.00
		TOTAL (B)		IVI	0.00
		TOTAL (A)+(B)			0.00
		ADD GST @ 18%		 	0.00
		GRAND TOTAL			0.00