

**N.O.W. - FURNISHING OF STATE BANK OF INDIA****ADMINISTRATIVE OFFICE, LUDHIANA****ESTIMATE FOR THE CIVIL WORKS**

S.No.	DSR REF.	Item	Quantity	Units	Rate	Amount
<b>1</b>		<b><u>VITRIFIED TILE FLOORING 600MM X 600MM</u></b>				
	<b>11.41</b>	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete. (Digital Tiles from Johnson and Johnson, Kajaria, Somany etc)	<b>779.00</b>	<b>SQM</b>		
		The cost shall also include laying of tiles in groove and filling the same with epoxy of desired colour and shade.				
	<b>11.41.2</b>	Size 600mm x 1200mm <b>(MAKE: KAJARIA, JOHNSON AND JOHNSON, ORIENT, SOMANY)</b>				
<b>2</b>	13.41	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade :				
	13.41.2	Old surface (two or more coats) over and including water thinnable priming coat with cement primer	<b>200.00</b>	<b>SQ.M</b>		
		THE WORKS SHALL ALSO INCLUDE REPAIR OF THE BROKEN OR UNEVEN SURFACE TO MAKE THE WALLS SMOOTH FOR THE APPLICATION OF THE OBD COATS. <b>(MAKE: ASIAN, NEROLAC, BERGER)</b>				
<b>3</b>		<b><u>Granite Polishing of the Existing Stone</u></b>				
		Granite polishing of the Existing stone with 5- stone grinding/polishing with hand grinding and floor grinding machines as per the direction of the engineer-in-charge. The work shall include the required repairing of the existing stone with white/coloured cement. The work shall include the cost of stone grinding, machinery and all the material required for the granite polishing and repair. The work shall also include the cleaning of the polished surface and disposal of the sludge or malbe to a suitable location as per the direction of the engineer in-charge. The rate shall viable till the fifth floor.	<b>200.00</b>	<b>SQ.M</b>		
<b>4</b>	11.37	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), Jointing with grey cement slurry @ 3.3 kg/sqm including pointing the joints with white cement and matching pigment etc., complete.	<b>10.00</b>	<b>SQ.M</b>		
		<b>(MAKE: KAJARIA, JOHNSON AND JOHNSON, ORIENT, SOMANY)</b>				
<b>5</b>	NS	Dismantling the existing walls/rcc/floor/furniture/wiring etc. complete, providing the required supports in terms of steel girders/rcc beams and making good the surfaces damaged or as per the direction of the engineer-in-charge (As per the approved plan of the Branch). The work shall also include removal of the same to an appropriate location as permissible to the local authorities or as per the direction of the Engineer in charge. (Note: The amount is expected after deduction of amount to be deducted for the buyback of the existing furniture)	<b>1.00</b>	<b>LS</b>		
<b>6</b>		<b><u>12MM THICK TOUGHENED GLASS DOORS WITH ETCHING:</u></b>				

		Providing and fixing in position 12mm clear float toughened Glass for naked glass door. The work to include making necessary template for all the glasses and then cutting the clear float glass to correct size, making all the necessary holes, cuts etc., and then toughening the same. The cost to include all hardware required viz., Ozone/ebco/godrej or approved equivalent make floor spring with its accessories, top pivot, center lock, 450mm glass door handles etc., along with etching with sand blasting as per design and drawing. The maximum size of each glass shall be as per the drawing or the direction of the Engineer-in-charge. The rate is for a finished item of work etc., complete as directed.	32.20	SQ.M		
		<b>MAKES: (GLASS: SAINT GOBAIN/ TATA/ ASAHI) (HARDWARE: OZONE/ GODREJ/ DORMA)</b>				
7		<b>12MM THICK TOUGHENED GLASS PARTITIONS WITH ETCHING:</b>				
		Providing and fixing in position 12mm clear float toughened Glass partition with patch fittings for the full height glass partitions as per the direction of the engineer-in-charge. The work to include making necessary template for all the glasses and then cutting the clear float glass to correct size, making all the necessary holes, cuts etc., then toughen the same.	71.96	SQ.M		
		The cost to include all hardware (PATCH FITTINGS etc) required of Ozone/EBCO/GODREJ or approved equivalent make viz., single corner patch, top and bottom corner patch etc. or as per the direction of the engineer-in-charge, along with etching with sand blasting as per design and drawing. The maximum size of each glass shall be 1200mm to 2000mm x 2400mm to 2700mm as per the site requirement. The rate is for a finished item of work etc., complete as directed.				
		The cost to include the cost of bevelling and smoothening of the exposed edges of the glass.				
		<b>MAKES: (GLASS: SAINT GOBAIN/ TATA/ ASAHI) (HARDWARE: OZONE/ GODREJ/ DORMA)</b>				
		<b>TOTAL</b>				-
		<b>TOTAL</b>				
		<b>NOTE: GST SHALL BE EXTRA AS APPLICABLE</b>				