## STATE BANK OF INDIA LOCAL HEAD OFFICE, GUWAHATI PREMISES & ESTATE DEPARTMENT GUWAHATI, ASSAM.

## ELECTRICAL INSTALLATION WORK FOR RENOVATION OF KAMPUR BRANCH, ASSAM

PRICE BID

SI.No.	Description	UOM	Qty.	Rate ( <b>Rs</b> .) (Exclusive of GST)	Amount (Rs.) (Exclusive of GST)
1	Main Panel :- Supplying, Installing, testing and commissioning of fabricated floor mounted cubicle type districution Panel Board suitable for 415 V comprising of suitable copper bus bars, 125A 4P MCCB with overvoltage protection as incoming and 3 Nos. of 63A 4P MCCB at outgoing in compartmentalized chamber fully isolated with 2 mm thick steel sheet and 3 mm steel channel painted with 2 coats of red oxide primer paint followed by finishing paint with interconnection etc. as required.(MCCB Make - Legrands/ Havells/L&T/SIEMENS/schnieder)	Set	1		
2	Sub-main line:- Wiring in MS conduit of IS specification of Proper size with core PVC insulated stranded copper wire 11KV grade (Finolex/Havells/Polycab/ RR Kabel/KEI/gloster) and with supply ,installation, commissioning of all the materials required including proper termination, connection in complete as required from main DB to various DBs:-				
i)	with 3nos 4sq.mm (1ECC)	RM	140		
	with 3nos 6sg.mm (1ECC)	RM	140		
	Supply ,installation ,testing and commissioning of distribution board manufactures made sheet steel enclosure With the following MCBs		110		
i)	Computer/Raw power DB, 8way SPN double door with 40A (30mA)DP RCCB as incomer & 6nos 10A SP MCB as outgoing.	No.s	2		
ii)	DB with 40A DP MCB.	No.s	2		
iii)	DB with 63A DP MCB.	No.s	2		
<u> </u>	DB with 16A DP MCB.	No.s	2		
<u> </u>	DB with 32 A DP RCCB, 30mA for AC	No.s	5		
vi)	4 way VTPN Double Door Distribution Board with 63A 4 Pole MCCB ( 36kA) as incomer and 12Nos. 32A SP MCB's at outgoing	Set	1		
vii)	4 way VTPN Double Door Distribution Board with 63A 4 Pole MCCB ( 36kA) as incomer and 2 No. of 40A SP MCB , 6 nos. of 32 A SP MCB, 4 nos of 16A SP MCB at outgoing	Set	1		
viii)	Light DB 8way SPN double door with 32A (30mA)DP RCCB as incomer & 6nos 10A SP MCB as outgoing.	No.s	2		

	GUWAHATI, ASSAM			
4	Supplying, installing and commissioning of PVC Armored cable			
	complete with proper cable glands and two nos. of 8SWG GI wire			
	(Havell's/RR kebel/KEI/gloster) alongwith all the other materials			
	required including proper connection in complete as required from			
	main Panel, Power Distribution Board to various DBs .			
i)	With 3.5 core x 25 sq. mm cable	RM	80	
II)	With 3.5 core x 50 sq. mm cable	RM	40	
5	Supply, installing and commissioning of earth station including	Set	4	
	digging and refilling back the pit with black soil and with 3.15mm			
	x300mm size copper plate duly tinned through out the surface of the			
	plate, placed at least 3.0 Mtr,below the ground level with 2nos			
	10sq.mm PVC insulated stranded copper conductor in 20mm GI pipe,			
	fixed to the plate and providing 40mm,3.1 mtr,long GI pipe with			
	reducer and funnel at top for watering pipe with supplying and laying			
	earth continuity wire of 2x10sq.mm copper stranded PVC green color			
	in heavy duty MS conduit on the wall from earth plate to starting			
	point of the line earth connector.			
6	Computer/Raw Power point wiring in MS conduit of IS specification			
	of proper size with 3nos 2.5sq.mm single core PVC insulated stranded			
i)	With 3nos 6A socket with single 16A switch.	No.s	24	
ii)	With 2nos 16A socket with individual switch.	No.s	12	
,	With 1nos 16A socket with individual switch.	No.s	10	
7	Supply & Fixing of 15Watt commercial down lights of system efficacy	Nos	40	
	>100lm/W. The light should be recessed mounted slim circular type			
	LED panel with die-cast aluminium housing and smooth powder			
	coated finish with anti glare UV stabilized diffuser and separate			
	energy efficient electronic driver having inbuilt surge protection upto			
	2.5kV. Make :- Bajaj/Havels/Phillips/Wipro/Crompton			
8	Supply and fixing of 2'x2' LED commercial Luminaire of 36 Watt with	Nos	22	
	system efficacy of 110lm/W. The light should be recessed mounted			
	type and low depth with CRCA poweder coated housing, high			
	transmittance diffuser for sysmmetric light distribution with non-			
	integral enegy efficient isolated electronic driver and inbuilt surge			
	protection upto 3kV. Make :- Bajaj/Havels/Phillips/Wipro/Crompton			
٩	Supply installation testing and commissioning of LED batten Single	Nos	30	
9	Tube light fittings with 20W with glare free light distribution wall	1403	50	
	mounted at ceiling/false ceiling level/. Make :-			
10	Bajaj/Havels/Phillips/Wipro/Crompton Supply and installation of Wall Mounted fan 400 /450 mm Metallic	No.s	14	
10		140.5	14	
	body and metallic Blade ,1400 rpm Havels FHWV3TFSLB18 or			
	equivalent of crompton/bajaj/usha/orient make			
11	Supply and installation of 5 Star rated Ceiling fan 1200 mm	No.s	4	
	crompton/bajaj/usha/havell's make		i i	
12	Supply and installation of Heavy Duty metallic body & Blades Exhaust	No.s	4	
	Fan 225/300 mm crompton/bajaj/usha/havell's make		· · · · · · · · · · · · · · · · · · ·	

	GUWAHATI, ASSAM.				
13	Supplying, installation, testing & commissioning of Security ligh with 25W LED lamps with pressure die cast housing with epoxy coated dark graphite grey colour finish and prismatic polycarbonates cover with individual LED lenses, including necessary GI bracket with clamp. Make :- Bajaj/Havels/Phillips/Wipro/Crompton	Nos.	4		
14	Wiring for light/fan/exhaust fan points using 3 X 1.5 1.1 kV grade PVC insulated stranded copper conductor wire(Finolex/Havell's/Gloster/RR kebel/KEI) for phase, neutral and earth in 25 mm dia heavy duty MS conduit along with associated accessories like MS junction boxes, bends, saddles, screws et. concealed in wall, floor, under flooring, below false ceiling or on surface as well as suspended from ceiling with 25mm X 3 mm MS flat suspenders duly painted above false ceiling from individual light/Fan/Exhaust Fan point outlet. etc. to individual modular type switch boards, 10 Amp modular plate type switches etc.(MK/Legrands/Havel's /anchor/Crabtree/Northwest), as required complete including circuit wiring with 3 X 2.5 sqmm. 1.1 kV grade PVC insulated stranded copper conductor wire and as per site requirement and as instructed by Engineer.				
i)	one light/fan controlled by one switch	No.s	115		
ii)	6A socket & switch at same board	No.s	7		
iii)	Fan Point with electronic modular type regulator.	No.s	4		
	GST on work contract will be extra as applicable.	Total			