PRICE - BID

NAME OF THE WORK: ELECTRICAL WORKS AT STATE BANK OF INDIA, RACC, JASSUR, DISTT. KANGRA (HP)

| S.No. | Specifications | Onty. | Units | Rate | Amount |
|---------|---|-------|-------|------|--------|
| PART-I: | COMPUTER POINTS & DISTRIBUTION | | | | |
| 1 | Supply all material, storing, handling, fixing of computer | 28 | each | | |
| | points computer points in suitable size of GI/PVC box | | | | |
| | including providing 3 nos 5 amps 3 pin modular sockets to | | | | |
| | be provided under table top and controlled by 1 no 15 A | | | | |
| | moduler type switch and indicator (to be provided above the | | | | |
| | table top in partition) with moduler cover plate etc complete | | | | |
| | as required including 3X2.5 sq. mm copper armored cable, | | | | |
| | including connection between switch & socket. Note: | | | | |
| | Maximum two computer points are to be provided on one | | | | |
| | circuit. (Switches : Make: Anchor Roma/Crabtree/North- | | | | |
| | West/Legrand-ARTEOR) | | | | |
| 2 | As per item no. 1 above but with 2 no. 16amp 5pin modular | 3 | each | | |
| | sockets controlled by 1 no. 16 amp modular switch and 6 amp | | | | |
| | indicator Lamp including the cover plate (ATM-2, BM-1, Rack- | | | | |
| | 1) | | | | |
| 3 | Supply, installation, testing and commissioning of factory | | | | |
| | fabricated distribution board rust inhibited powder coated | | | | |
| | sheet fabricated comprising of incoming and outgoing | | | | |
| | isolator & MCBs neutral link or neutral bus, top and bottom | | | | |
| | detachable entry earthing bolts interconnection and grouting | | | | |
| | bolts etc complete as required as per details below. Make: | | | | |
| | Havells/HPL/Standard/ Legrand/L&T | | | | |
| a) | 8 way SPN MCBDB Double Door comprising of 1 No 63 Amp DP | 1 | no. | | |
| | Isolator and 6 No SPMCB 10/16 Amp. (UPS output) | | | | |
| b) | 12 way SPN MCBDB Double Door comprising of 1 No 63 Amp DP | 1 | No | | |
| - \ | Isolator and 10 No SPMCB 10/16 Amp. (UPS) | 0 | | | |
| c) | 4 Way TP MCBDB Double Door in recessed wall including cutting | 2 | no. | | |
| | of wall and making good the damages comprising 1 no 100 A | | | | |
| | FP TPN and 6 Nos.32 A DPMCBS etc complete as required. (for Air conditioning only). | | | | |
| d) | 4 WayTP MCBDB Double Door in recessed wall including cutting | 1 | no. | | |
| u, | of wall and making good the damages comprising 1 no 4P | _ | 110. | | |
| | 63AMP, 30mA ELCB and 12 Nos. 6/20/25 Amp SPMCBS etc | | | | |
| | complete as required. (for light points) | | | | |
| | complete as required. (for right points) | | | | |
| e) | 4 WayTP MCBDB Double Door in recessed wall including cutting | 1 | no. | | |
| | of wall and making good the damages comprising of 1no. | | | | |
| | 63Amp FP TPN & 12 Nos. 25 Amp SPMCBS etc complete as | | | | |
| | required. (for Raw Power) | | | | |
| 4 | RAW POWER: Supply all material, storing, handling, fixing of | 12 | each | | |
| | suitable size of GI/PVC box including providing 1 nos 15 | | | | |
| | amps 6 pin modular power sockets to be provided controlled | | | | |
| | by 1 no 15 A moduler type switch and indicator with moduler | | | | |
| | cover plate etc complete as required including 3X2.5 sq. mm | | | | |
| | copper armored cable. Note: One power points are to be | | | | |

| | | ı | 1 | T | |
|---------|---|-----|-----|---|--|
| | provided on one circuit and dirctly to be connected on Power | | | | |
| | DB. (Switches: Make: Anchor/Crabtree/North-West/MK | | | | |
| 5 | Supply, installation, testing and commissioning of following | | | | |
| | capacity 3 pin metal clad industrial type plug and socket | | | | |
| | arrangement with plug top, cap and chain controlled by under | | | | |
| | noted capacity: (Make: Havells/HPL/Standard/Legrand/L&T) | | | | |
| a) | 20 Amp with 25 Amp. C Curve SP MCB. (1.5 TR High wall split | 7 | no. | | |
| | AC's-2, UPS-4, Safe Room-1) | _ | | | |
| b) | 30 Amp with 63Amp SPMCB | 3 | no. | | |
| c) | 30Amp with 32Amp SPMCB (for 2.0TR AC) | 5 | no. | | |
| 6 | Providing and fixing of suitable size MS box fabricated with | 1 | job | | |
| | 16 G MS sheet either in recess wall or on surface to | | | | |
| | accommodate dedicated earth from earth electrode and | | | | |
| | further distribution of earth to computer points including | | | | |
| | providing of 5 mm bakelite on base connector strip and | | | | |
| _ | painting of box etc as required. | | | | |
| 7 | Basic electrical Wiring of light points, plug points & power | | | | |
| | points | | | | |
| | Wiring for light point/ ceiling fan point/ exhaust fan point | | | | |
| | with 1.5 sq.mm FRLS PVC insulated copper conductor single | | | | |
| | core cable in surface / recessed medium class PVC conduit | | | | |
| | ISI Mark, with 6Amp modular switch, modular plate, suitable | | | | |
| | GI junction & switch boxes & clip and earthing the point with | | | | |
| | 1.5 sq.mm FRLS PVC insulated copper conductor single core | | | | |
| | cable etc. as required.(Wires Make: Havells/ RR Kable / | | | | |
| | KEI/Finolex) (Switches : Make: Anchor/Crabtree/North- | | | | |
| | West/MK) | | | | |
| | (Rate includes 3 x 2.5 sq.mm FRLS copper conductor, single | | | | |
| | core cable in PVC conduit for circuit/sub main wiring along | | | | |
| - 1 | with earth wire) | 10 | | | |
| a) | single 6 Amp Switch controlling 1 light point for T-5, Wall Fans, | 10 | no. | | |
| | exhaust Fans , Ceiling fan and other seprate room supply only | 10 | | | |
| b) | single 6 Amp Switch controlling 4 no. downlights / 4 no. LED | 10 | no. | | |
| - \ | downlight / 2 no. 2'- 0"x 2'-0" 36 watt light fittings | - | | | |
| c) | single 6Amp socket controlling by 5Amp Modular switch in | 5 | no. | | |
| -17 | switch boards etc complete as required | 1.5 | | | |
| d) | Extension of points with 2x1.5 sq.m PVC insulated coppe | 15 | no. | | |
| | conductor cable in suitable MS conduit in recess couduit | | | | |
| | wiring system for wall fan points with modular switches of | | | | |
| | 6AMp(to be fixed at normal height) and 5Amp 5pin modular sockets (to be fixed 1'-6" below false ceiling) as per | | | | |
| | requirement & filling the chases etc, complete as required. | | | | |
| | | | | | |
| | Note: Lights/fans points to be calculated by numbers of lights and no extra cost shall be paid for dummy switch.) | | | | |
| PART_TT | : PANELS , KIT KATS & CABLES | | | | |
| 8 | Providing and fixing of 3 nos 100 Amps Kitkat with 1 no | 1 | job | | |
| U | neutral link on suitable size of Bakelite sheet of thickness | _ | Jon | | |
| | not less than 25 mm complete as required | | | | |
| 9 | MAIN PANEL: Supply at site installation testing and | | | | |
| | commissioning of panel fabricated with 16 G MS sheet. The | | | | |
| | commissioning of panel labilitated with 10 0 hs sheet. The | l | l | | |

| | panel shall be free standing type totally enclosed dust and | | | | |
|----|--|----|----------|---|---|
| | vermin proof construction with rubber gaskets. The floor | | | | |
| | mounting panel shall have ISMC mounting channels, GI earth | | | | |
| | busbar, busbar chamber ,cable alleys interconnection with | | | | |
| | solid bar/PVC insulated copper conductor as per | | | | |
| | requirement, and suitable supports of busbars. The panel | | | | |
| | shall be painted with two coats of enamel paint (Grey shade) | | | | |
| | over primer and shall also be provided with designation of | | | | |
| | Incoming and outgoing feeder as details below: | | | | |
| | INCOMING | | | | |
| | 1 no MCCB Breaking Capacity 25 KA 125 Amp 4P , DN Series, | | | | |
| | L&T make | | | | |
| | 1 no 0 -500V digital Voltmeter in separate compartment and | | | | |
| | digital Amp meter and one set of CTs (3 Nos) with CT Ratio | | | | |
| | 150/5 A with LED type phase Indication Lamps with | | | | |
| | protection fuses in a separate compartment | | | | |
| | 160 Amps capacity 4 strips Aluminium bus bars. | | | | |
| | OUTGOING | | | | |
| | 5No. MCCB Breaking Capacity 10 KA 63 Amp 3P, DN Series L&T | 1 | set | | |
| | Make | | | | |
| 10 | Supply, Installation, testing & commissioning of PVC | | | | |
| | insulated PVC sheathed armoured cable of 1100 V (IS ;1554 | | | | |
| | Part 1) and fixing of cable on wall with suitable size of | | | | |
| | clamps /saddles or laid in floor/recess wall including cutting | | | | |
| | of wall /floor and making good the damages etc complete as | | | | |
| | required of following sizes (ISI marked). (Make: Havells/ RR | | | | |
| | Kable / KEI/Finolex/Pymen) | | | | |
| a) | 3.5X25 sq. mm aluminum conductors armoured cable with two | 70 | mtr. | | |
| | Nos. 8 SWG GI wire | | | | |
| b) | 4X10 sq. mm aluminum conductors armoured cable with two | 70 | mtr. | | |
| | Nos. 8 SWG GI wire | | | | |
| c) | 3X6 sq. mm copper conductors armored cable with one Nos. | 50 | mtr. | | |
| | 8 SWG GI wire | | | | |
| d) | 3X2.5 sq. mm copper conductors armored cable | 20 | mtr. | | |
| 11 | Supplying and making end termination with brass | | | | |
| | compression gland and aluminium lugs for following size of | | | | |
| | PVC insulated and PVC sheathed / XLPE aluminium/Copper | | | | |
| | conductor cable of 1.1 kV grade as required. | | | | |
| a) | 3.5X 25 sq.mm aluminum conductor | 5 | no. | | |
| b) | 4x10 sq.mm aluminum conductor | 6 | no. | | |
| c) | 3X6 sq. mm Copper cable gland. | 4 | no. | | |
| d) | 3X 2.5 sq.mm aluminum conductor | 14 | no. | | |
| 12 | Supplying & fixing the 1 no.4 pole 100 Amps capacity change | 1 | no. | | |
| | over switch and complete connection with Electrical Panels | | | | |
| | as required .Make: Havells/HPL/Standard/ Legrand/L&T | | | | |
| 13 | UPS DISTRIBUTION BOARD | | | | |
| | supply, installation, testing and commissioning of factory | | | | |
| | fabricated distribution board rust inhibited, powder coated | | | | |
| | sheet fabricated comprising of incoming and outgoing | | | | |
| | isolator and MCB's neutral link or neutral bus, top and bottom | | <u> </u> | | |
| _ | | | | _ | _ |

| | | | ı | |
|---------|---|----|--------|---|
| | detachable entry earthing bolts interconnection and grouting | | | |
| | bolts etc complete as requd. Make: Havells/HPL/Standard/ | | | |
| | Legrand/L&T | | | |
| | as per details below :- | | | |
| а | 4 way DB comprising of 2 no. 63 amp DPMCB (UPS out put) | 2 | each | |
| b | 4 way DB comprising of 1no. 63 amp 4P TPN (UPS input) | 1 | each | |
| 14 | Providing and laying following sizes of PVC insulated copper | | | |
| | conductor cable of 1100 V in flexible/ PVC conduit pipe with | | | |
| | accessories such as glands bends etc (as per requirement) | | | |
| | including making necessary interconnection etc complete as | | | |
| | required. | | | |
| | 2 X 6 Sq mm with 1 no suitable insulated 2.5 sq mm multi | 20 | mtr. | |
| | stranded copper wire in PVC flexible pipe. (Make: Havells/ RR | | | |
| | Kable / KEI/Finolex) | | | |
| 15 | EARTHING | | | |
| a) | Supply and fix copper plate earth station with 600X600X3mm | 1 | Sets | |
| , | copper plate including all accessories such as watering pipe | | | |
| | and funnel and providing masonry enclosure at top with cover | | | |
| | plate i.e excavation of pit, supplying and filling of salt | | | |
| | charcoal, refilling of pit etc complete as required as per IS | | | |
| | 3043-1987. The voltage between neutral and earth must be | | | |
| | below 1 V. | | | |
| b) | Supply and fix GI plate earth station with 600X600X6mm GI | 2 | Sets | |
| 5, | plate including all accessories such as watering pipe and | _ | 0013 | |
| | funnel and providing masonry enclosure at top with cover | | | |
| | plate i.e excavation of pit, supplying and filling of salt | | | |
| | charcoal, refilling of pit etc complete as required as per IS | | | |
| | 3043-1987. | | | |
| 16 | a) Supply fixing and termination of 20X3 mm copper strip | 3 | Meter | |
| 10 | with earth station below ground level etc as required. | Ü | 110001 | |
| | b) Supply fixing and termination of 32x6 mm G.I. strip with | 6 | Meter | |
| | earth station below ground level etc as required. | Ü | 110001 | |
| | antin otation solon ground lovel ote de loquilou. | | | |
| 17 | a) Providing and fixing of 8 SWG copper earth wire in the | 50 | mtr. | |
| | recess for loop earthing etc. as required. | | | |
| | b) Providing and fixing of 8 SWG GI earth wire in the recess | 20 | mtr. | |
| | for loop earthing etc. as required. | | | |
| 18 | Supply and laying following dia 2 mm in thickness ISI Mark | | | |
| | PVC pipe under floor or in recessed walls from earth | | | |
| | electrode to UPS room for computer dedicated earthing | | | |
| | 25 mm diameter | 70 | Meter | |
| | | | | |
| PART II | I I - TELPHONE & DATA CABLE | | | |
| 19 | Wiring for telephone points with 0.6 mm dia 2 pair insulated | 12 | no. | |
| | annealed tinned electrolatic copper conductor in 2 mm thick | • | | |
| | 25 mm dia ISI marked PVC conduit complete with | | | |
| | accessories such as bends, junction boxes etc. with suitable | | | |
| | size of G.I./PVC box modular plate and cover in front on | | | |
| | surface or in recess including providing and fixing modular | | | |
| | type telephone socket outlet and making necessary | | | |
| l | 1 cips colophone cooker cariot and making necessary | | l | 1 |

| | | I | | |
|----|---|--------|-----------|--|
| | connections etc. complete as reqd.(Make: Dglink/KEI/Finolex) | | | |
| 20 | Supply, installation and testing & commissioning of Tag Block | 1 | 20 | |
| 20 | 20 pair for telephone connections Make: krone | 1 | no. | |
| 21 | Providing , Laying, testing & commissioning of 10 pair | 20 | mtr. | |
| 21 | telephone cable from outside govt. / bsnl DB to Rack for | 20 | mici. | |
| | lease line, ISDN of Make: Delton, finolex, polycab. | | | |
| 22 | Data cabling work for computer networking starting from | 23 | no. | |
| 22 | mounting rack at system room with UTP CAT-6e LAN Data | 25 | 110. | |
| | cable in 2mm thick 25 mm dia ISI mark PVC conduit with | | | |
| | accessories such as bends, Tees, junction boxes including | | | |
| | providing and fixing cat-6 I/O plates and SMB complete with | | | |
| | all networking accessories etc complete as reqd. (Make: D- | | | |
| | Link/MOLEX/AMP/COMMSCOPE). | | | |
| | Note: TWO Data Points to be provided in One Table/Counter. | | | |
| | Extra poits not to be paid if provided. Maximum 6 no. data | | | |
| | cable must be run in one pvc pipe. Tagging/marking at both | | | |
| | ends of data points (Seat & Switch) to be done. | | | |
| 23 | supply, installation, testing and commissioning of 24-port | 1 | no. | |
| | Patch Panel | | | |
| 24 | Supply and installation, testing and commissioning of | 1 | no. | |
| | mounted rack 15" hight made of powder coated MS sheet | | | |
| 25 | supply, installation, testing and commissioning of factory | | | |
| | manufactured CAT-6e patch chord complete with 2 no. | | | |
| | connectors etc. complete as reqd. | | | |
| a) | 1 mtr. long | 23 | no. | |
| b) | 2 mtr. long | 12 | no. | |
| | | | | |
| 26 | Supplying & laying recessed in wall Rigid ISI Mark PVC drain | 90 | mtr | |
| | pipe of size 25mm dia complete with fittings, U traps etc. $\&$ | | | |
| | as specified to the nearest toilet / drain point under floor | | | |
| | or in recessed walls for AC drains including cutting of walls, | | | |
| | bends & Tees. making good the damages etc. wherever | | | |
| | required. (Make: Diplast/Supreme) | | | |
| | | | | |
| | : SUPPLY, INSTALLATION TESTING & COMMISSIONING OF FANS & | FIXTUR | <u>ES</u> | |
| 27 | SITC of 2"x2" Celing grid 33-36 watt LED panel fixtures with | 25 | no. | |
| | essential driver in false ceiling including making necessary | | | |
| | arrangement for mounting the fixtures and connection with 2 | | | |
| | x 1.5 sq.mm insulated copper cable from adjacent point in | | | |
| | PVC flexible pipe etc Complete as reqd. Make : Cat No: | | | |
| | LDTLBK-36W-CDL of Crompton or equivalent of Wipro /Philips | | | |
| | 120 Lumens per Watt, Color temperature 6000K | _ | | |
| 28 | SITC of 15 watt LED fixtures /dowlighters with essential | 24 | no. | |
| | driver in false ceiling including making necessary | | | |
| | arrangement for mounting the fixtures and connection with 2 | | | |
| | x 1.5 sq.mm insulated copper cable from adjacent point in | | | |
| | PVC flexible pipe etc complete as reqd. Make Phillips cat no. | | | |
| | DN - 192 - 1000 or equivalent of Wipro/Crompton | | | |

| 29 | SITC of 5 watt recess mounted LED spotlight with assembly complete with including making necessary connections etc. Complete as reqd. (M/s Crompton Cat No. Or equivalent of Philips/Wipro/ Bajaj) | 4 | no. | |
|--------|--|----|------|----------|
| 30 | SITC of 18/20 watt of T5 LED fixtures directly on ceiling / wall including making necessary connections with 2x1.5 sq.mm insulated copper cable conductor wire etc. complete as reqd Make Phillips /Wipro / Crompton | 10 | no. | |
| 31 | SITC of 450 mm sweep wall fan with metal body & metal fins, complete as required. (Make: SStorm2 of Crompton or equivalent of Khaitan / Bajaj / Usha) | 12 | no. | |
| 32 | LED Strip light (4.5/5 watt)for cove (M/s Phillips /Wipro / Bajaj Complete in all respects with suitable drivers | 30 | MTR. | |
| 33 | SITC of 200 mm exhaust fans, metal body, complete with self opening louvers / shutters including necessary frame etc, complete as reqd. (M/s Crompton High Breeze or equivalent of USHA / Bajaj) | 4 | no. | |
| 34 | SITC of 1200 mm CEILING fans complete as required including modular type regulator. (M/s Crompton High Breeze of equivalent of USHA/BAJAJ) | 4 | no. | |
| 35 | SITC of 30Watt street light/flood light for lighting the front side of the Branch (M/s Crompton or equivalent of PHILIPS/WIPRO) | 2 | no. | |
| | TOTAL OF DADT T TT TTT (A) | | | |
| | TOTAL OF PART : I +II+III (A) TOTAL OF PART : IV (B) | | | |
| | TOTAL OF TAKE . IV (D) | | | |
| | TOTAL AMOUNT (A+B) | | | |
| Amount | In Words: | ı | 1 | - |