

Price-bid

CIVIL WORKS AT STATE BANK OF INDIA, SANGHOL BRANCH

<i>S.NO.</i>	<i>SPECIFICATIONS</i>	<i>QNTY.</i>	<i>UNITS</i>	<i>RATE</i>	<i>AMOUNT</i>
1	PAINT WORK:				
a)	Applying three or more coats of <u>ACRYLIC EMULSION</u> (ASIAN/ NEROLAC) of approved shade including making of ground, rubbing, filling of putty base preparation with BIRLA/ JK Putty, applying a coat of cement primer, complete. In case where the surface has been earlier white/colour washed, the old white/colour wash shall be entirely removed and surface broomed/scrapped down before preparing the surface for applying paint as described above. Rates include cleaning of splashes, stains on floor, window panes etc and scaffolding, if required and for all heights.	241.00	sq.m.		
2	DISMANTLING WORK:				
	Dismantling brick wall etc. & disposing the malba from site	1.00	job		
3	VITRIFIED TILE FLOORING:				
	Providing and laying 1st quality vitrified tiles (Marble series Double charged- JOHNSON/ KAJARIA/ RAK- as approved by Bank's Engineer/Architect) of following sizes, as per design pattern on floor & skirting with chemical or adhesive/ cement as directed and joints to be filled with grout of approved colour, including dismantling existing floor tiles and disposal of malba from site, cutting wooden/ aluminum doors to match new floor level, preparing of surface & disposal of malba from site.				
	32"X32" Vitrified tiles Double Charged- marble series.	164.00	sq.m.		
4	CERAMIC FLOOR TILES:				
NS	Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS : 15622, of approved make, in all colours, shades, except White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick Cement Mortar 1:4 (1 Cement : 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including pointing the joints with white cement and matching pigments etc., complete.	3.50	sq.m.		
5	WALL TILES:				
NS	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg	15.00	sq.m.		

SIGNATURES OF CONTRACTOR WITH SEAL

	per sqm,including pointing in white cement mixed with pigment of matching shade complete.				
6	BRICK WALL:				
	Providing & laying brick wall with brick class designated 75 in cement mortar 1:4 (1 cement: 4 coarse sand), including all types of leads/ lift, scaffolding, pads, racking joints, curing, cutting concrete floor before starting work, complete in all respect. In case of half brick wall, MS reinforcement as per CPWD specifications to be provided, i.e. 2 nos. 6mm dia TOR steel bars will be provided at every third course, for which no extra payment will be made.	31.00	sq.m.		
7	REPAIR WORK(12 to 15mm thick Cement plaster 1:4)				
	Providing & laying 12mm Cement plaster 1:4 (1 cement: 4 fine sand) on brick walls, shelves, ceiling etc, including all types of leads/ lift, scaffolding, pads, racking joints, curing, etc. complete	62.00	sq.m.		
8	REFIXING OF MS DOOR OF SAFE ROOM				
	Refixing MS gate & frame in strong room, fabricated out for frame, Square tubular section & square bars as per design for the shutter as per design, including providing adequate locking system / aldrop on both sides, fixing the frame/door in walls using suitable MS lugs/holdfasts (3-4 no. on each vertical side), chasing the walls & making good the surface after fixing. The work shall also include providing red oxide primer & 2-3 coats of enamel paint, complete in all respects. Size of the door is 4'-0"x7'-0" approximately, with space above door to be provided with fixed grill as per design.	1.00	nos.		
9	DOOR WITH CHOWKHAT				
	Providing & fixing 35mm thick solid core flush with 35 x 15mm beech wood beading around with 1 mm laminate on both sides including necessary hardware viz., door stopper, door lock, handles, brass hinges of approved make & equality melamine polish finish to all beech wood members etc., complete as directed.				
	Single Shutter 2'-6" x 7'-0" including chowkhat	3.00	nos.		
	Single Shutter 3'-0" x 7'-0" including chowkhat	1.00	nos.		
	Note: (i) All wood to be sprayed with anti termite and anti borer spray. 5 CONCRETE WORK (CAST IN SITU)				
10	WC				
	Providing & Fixing floor mounted one piece EWC including flushing cistern with dual flush (3/6ltrs) including all fittings & fixtures, water jet, seat cover complete in all respects. Model Aspiro S-100 of Hindware or equivalent of Cera/Somany/Parryware	1.00	no.		

11	SHIFTING & Refixing of WASHBASIN				
	Shifting & Refixing of Wash Basin including all fittings & fixtures complete in all respects. Model AMAZON of Hindware or equivalent of Cera/Somany/Parryware	1.00	no.		
12	WATER SUPPLY				
	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge.				
	15 mm dia nominal bore	10.00	mtr		
	20 mm dia nominal bore	10.00	mtr		
13	SOIL WASTE DRAINAGE PIPE WORK				
	Providing & fixing PVC(SWR) Pipes Type B, heavy class conforming to S13592-1992. (PRINCE / SUPREME / DIPLAST/ ASTRAL), including necessary fittings like bend, offset, collars etc., complete. Rates to include cutting/ chasing walls, floor, fixing pipe & making good the damages with cement mortar, complete in all respect.				
	75 mm dia	10.00	rft		
	100 mm dia	10.00	rft		
14	CP FITTINGS & ACCESSORIES				
	Providing & fixing 15mm dia CP Bibcock Bib Cock with CP wall flange, complete. (MODEL = Contessa Neo with wall flange, of Hindware) or equivalent of Cera/ESS ESS	1	nos.		
	Bibcock Long Body: same as above but long body (CAT no. F730011CP of Hindware) or equivalent of Cera/ESS ESS	1	nos.		
	Providing & fixing 15mm dia CP Pillar cock (JAQUAR PRS-CHR-031), auto closing type, complete.	1	nos.		
	Providing & fixing 15mm dia CP Angle valve Angle valve with CP wall flange, complete. (MODEL = Contessa Neo with wall flange, (CAT no. F730039CP of Hindware) or equivalent of Cera/Jaquar	3	nos.		
	Providing & fixing CP jali (heavy duty) with CP outer ring, complete.	3	nos.		
	Providing & fixing single bowl Kitchen Sink size 24"x18"x8" model Flamingo of HINDWARE or equivalent of JAINA/NEELKANTH	1	nos.		
	Providing & fixing 600x450 mm or as directed, beveled edge mirror 5.5 mm superior glass (ATUL/ SAINT GOBBIN) complete with 6 mm thick hard board ground fixed to wooden cleats & CP brass screws, washers & clips etc. complete.	1	No.		
15	GRANITE				

	Providing and laying Polished Granite stone flooring in required design and patterns, in linear as well as curvilinear portions of the building all complete as per the architectural drawings with 18 mm thick stone slab over 20 mm (average) thick base of cement mortar 1:4 (1 cement : 4 coarse sand) laid and jointed with cement slurry and pointing with white cement slurry admixed with pigment of matching shade including rubbing, curing and polishing etc. all complete as specified and as directed by the Engineer-in-Charge.				
	Polished Granite stone slab of all colour and texture except Black, Cherry/Ruby Red	1.50	sq.m.		
16	RCC SLAB				
	Providing and laying RCC slab 2.5" thk for kitchen in RCC 1:2:4 including shuttering steel reinforcement as req.all complete as per direction of Engineer-in-Charge.	1.50	sqm.		
	TOTAL (Item No. 1 to 16				
Amount in Words:					