

**SCHEDULE OF QUANTITIES – SBI Wealth KANNUR ROAD BRANCH**

Sr.No	Description	Qty	Unit	Rate	Amount
1	<b>Low Height Partitions</b>	7.50	Sq M		
	Providing and fixing in position of low height partitions of the height 1200 mm as per shape shown in the drawing.ie. (750mm solid partition and glass above)				
	Aluminium sections of size 63.5 X 38.1X1.2 mm thk. of INDAL/JINDAL as internal frame structure ,vertically at about 60 cm centers and 3 Nos Horizontally of the same size of frame at floor level, 750 mm and at 1200 mm level. same size at 370 mm level, fixed in position. 8 mm Plywood on both sides of framework finished with 1 mm laminate of approved color and shade with grooves on both sides., 8 mm <b>Plywood</b> of approved quality finished with 1mm Laminate with grooves on both sides of approved color and shade. Top of the partition finished with laminate and 12mm thick glass with etching is fixed over the partition with Dorma make (or) Equivalent make 'D' bracket of SS finish of 12mm thick. Around the partition 75mm thick Dark color laminate is provided as show in the drawing and pattern.				
2	<b>Fully glazed Door</b>	6.50	Sq M		

	Providing and fixing frameless fully glazed 12mm thk <b>toughened</b> float glass fixed with necessary patch fittings (Dorma make) including cutting, making holes, cutouts in the glass of required shape and size to accommodate fittings and fixing the fittings in floors, soffits, jams including necessary fixtures, screws, sealant wherever required and SS cover over patch fittings. Rate shall include necessary etching film / LOGO, <b>SBI Wealth branding stickers as per approved, colour, design and pattern</b> approved patch fitting locking systems, 1 pair of 600mm long S. S. (H Shape) Handles of approved make, floor springs, and any necessary hardware items. ( DORMA MAKE Top Pivot - <b>PT 24</b> , Top Patch Fittings - <b>PT 20</b> , Bottom Patch fittings - <b>PT 10</b> , Floor Spring - BTS 75 V, Corner lock with strike plate and Euro Profile Cylinder - US 10, Handle - TG DIH600 - 32mm dia X 600mm length)				
<b>3</b>	<b>Fully Glazed - Fixed Glass Partition - Patch Fitting</b>	29.00	Sq M		
	Providing and fixing of fixed glass partitions with 12mm thick toughened glass using <b>PT</b> Standard fittings like PT 90/PT 92 of <b>Dorma make</b> at the top and bottom including cutting, making holes in glass and fixing the fittings in floors, ceilings etc and making the same good with necessary screws, <b>3M vinyl SBI Wealth branding stickers as per approved, colour, design and pattern</b> , sealants etc.complete.				
<b>4</b>	<b>FALSE CEILING:</b>				
	NOTE:The false ceiling area will be measured in flat area only.				
<b>4(a)</b>	<b>Gypsum Board False Ceiling</b>	100.00	Sq M		
	Providing and fixing of M/F suspended false ceiling as the detail given in the drawings. With G.I frame work and 12.5 mm tapered gypsum board panels to form grids of 45.7 X 122 cm as per manufactures specification including provision for stepped shaped ceiling for lighting trough comprising				

	<p>Frame work of intermediate channels (M.F.T) at 122 cm centers along one direction M/F ceiling section MF5 at 45.7 cm center along other direction. Perimeter channels (MF 6A) along walls around perimeter side of the ceiling. The intermediate channels suspended from ceiling, through sharp hangers 25 X 0.5 mm (MF 8) at 122 cm centers connected to soffit cleats p534 (27 X 37 X 25 X 1.6mm) the cleats connected to ceiling through metal expansion rawl plugs 1/2" dia and 17/16" long with additional perimeter channels (MF 6A) for light fittings, Air conditioners Ducts, vertical drops, offset etc. 12.5mm thick gyp board with tapered edges fixed to underside of suspended grid with 25 mm screws to from grids with <b>2 coats of plastic emulsion paint of approved color and one coat of putty</b> over a coat primer etc, complete.</p>				
<b>5</b>	<b>Tables</b>				
	<p>The table top is 25mm thick post formed prelaminated particle board having underside covered with laminate, and other exposed faces are made of 19 mm thick marine plywood (IS 303 grade) finished with 1mm thick laminate. Ready made Keyboard tray made out of powder coated MS sheet exposed edges lipped with PVC edge band 0.5mm thick mounted under the worktop with telescopic sliding channels. Ebco or other approved is to be provided. A foot rest with country wood of 7.5x2.5cm also to be provided. 12mm thick glass to be provided for table top and the edges of the glass to be polished. The inner portion is finished with laminate finish. Drawers are made of 12mm thick marine plywood and exposed faces are finished with 1 mm laminate and inner sides with enamel paint finish as shown in the drawing. Necessary fittings such as telescopic steel slides, godrej lock, handles etc. of approved make are to be provided. One Drawer set contains three number of drawers (with 13-15cm inner depth) are to be provided. One cable manager is to be provided as shown in the drawing. Supplying and installing CPU Trolleys made out of powder coated 1.6 mm thick MS sheet with adjustable width, front &amp; back open &amp; provided with lockable castors. Ebco or other approved Necessary beddings and grooves in laminate to be provided. Edges of plywood finished with PVC edge banding /teakwood lipping.</p>				
<b>I</b>	Table of size 180x80x75cm	1.00	Nos		
<b>ii</b>	Table of size 150x75x75cm	6.00	Nos		

<b>6</b>	<b>Side Tables</b>				
	The side table top with 25mm thick postformed prelaminated particle board, and all other exposed faces are made of 19 mm marine plywood finished with 1mm thick laminate , and inside painted with 2 coats of enamel over a coat of putty and multiwood/teakwood beading on all exposed edges. Godrej metal body locks, all fixtures, nylon brushes etc complete,				
i	Side table of size 120x45x75cm	6.00	Nos		
<b>7</b>	<b>Low Level Storage :</b>	5.00	Sq M		
	Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip.				
	Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade.				
	All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.				
<b>8</b>	<b>High Level Storage</b>	25.00	Sq M		
	Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip.				
	Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade.				

	All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.				
<b>9</b>	<b>Column/Wall paneling</b>	10.00	Sq M		
	Providing and fixing wall paneling to detail as shown in the drawing with 18mm thick Plywood finished with 1mm thick laminate				
<b>10</b>	Providing and fixing 8mm thk. Toughened glass with 3 M vinyl stickering consisting of SBI Wealth Embelm consisting of cmyk 97 100 0 25 pantone 2745c as background and cmyk 20 30 70 15 pantone 872c for embelm as per approval from EIC.	0.90	Sq M		
<b>11</b>	<b>Custom Made Full Height Solid Partition :</b>	5	Sq M		
	Supply and set in position of custom made double skin full height partitions as per shape and size shown in the drawing.				
	<b>Frame Work Detail:</b> Aluminium sections of size 63.5 X 38.1X1.2 mm thk. of INDAL/JINDAL as internal frame structure,vertically at about 60cm centers varied along columns wall ends, junctions of walls, as necessary. Horizontally of the same size of frames at floor level,750 mm, 1500 mm,2100 mm, and roof level. same size at 350				
	<b>Lining Work:</b> 8 mm <b>Plywood</b> of approved make on both sides of framework from floor level to 6"above false ceiling level, and to be finished with 1mm laminate of approved color and shaped on both sides including necessary grooves and steam beach beadings.				
	Measurement for the partition area shall be considered from floor level to false ceiling level only.				
<b>12</b>	<b>Painting</b> - Painting the internal walls with 2 coats of plastic emulsion paint over putty finish and a coat of primer in the banking hall	50.00	Sq M		
<b>TOTAL</b>					

\_\_\_\_\_