

PRICE BID - Interior Decoration & Furnishing : LOOSE & FIXED FURNITURE WORK for State Bank Of India RACC BRANCH at NADIAD

Sr.No.	Description	QTY	Unit	Rate in Figure	Rate in Words	Amount
Note :	Rate should be inclusive of material,labour,tools, machinery, scaffolding, final disposal of debris, cleaning cutting wastage etc. All taxes, transportation etc. complete. (Excluding GST) GST will be paid as Applicable at the time of payment of Bills					
[A]	FURNISHING WORK					
1	WORK TABLES					
	Supplying and installation of Table as per the following description : Table top shall be made from 18 mm thick commercial ply wood with 1 mm thick Laminate (approved shades) with necessary intermediate support. Table top shall be supported by 18 mm thick commercial ply wood with wooden framing. Storage cabinet of 1'-3" x 2'-0" x 2'-6" shall be provided using 18 mm thick commercial ply wood having 4 Nos drawers as directed with heavy duty telescope sliding channel of approved make , grouplock, S.S. Handle, CPU Trolley (Steel with lockable roller supports/ Nylon castors), Key board tray(made from CRCA steel duly powder coated. It must have built-in slides which, must have a soft palm rest and a stow-away design of mousepad					
	Apron (Modesty Panel) made from 18 mm thick ply wood finished with 1 mm thick Laminate (approved shades) & groove pattern as per drawing					
	Table side made from 18 mm thick ply wood with 1 mm thick Laminate (approved shades) finish shall be provided in a pattern as per drawing. Laminate to be provided on all visible surfaces.					
	Drawer Fascia made out of 18 mm thick Plywood. The sides/back/base of drawers be made of 12 mm thick Ply wood & Bottom of drawers shall be of 6 mm thick ply wood. fixing Laminate on front side and all the internal surfaces shall be 0.60 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles for each drawer. All the edges of Drawer Fascia be provided with teak wood edge bending with laquer					
	Table shall CPU Trolley and metallic cable Manager shall be provided in table top. All exposed edges of plywood shall have Laminate with smooth edges & corners					
	Exposed edges of Table Top, Leg panel & Side Shelf shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.					
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade. Etc. complete.					

Sr.No.	Description	QTY	Unit	Rate in Figure	Rate in Words	Amount
	All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade					
	As per drawing and instruction of Architect/Bank work to be Completed					
	FINISHING DETAILS IN NUTSHELL:					
	1) All the Visible surface shall be provided with 1.00 mm thick Laminate (approved shades)					
	2) Table Top : 1 mm thick 1.0 mm thick laminat with melamine polish on Burma Teak beading .					
	3) All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate					
1[a]	TABLE Size: 7'-0"x2'-6" with Drawer Unit BM Cabin	1.00	NO			
1[b]	TABLE Size: 5'-0"x2'-6" with Drawer Unit Auditor, Mgr, Asst.	12.00	NO			
1[c]	TABLE Size: 5'-4"x2'-0" with Drawer Unit Grahak Mitra	1.00	NO			
2	TABLES					
	Supplying and installation of Meeting Table/ Dining Table of 2'-6" height, 1/2" x 1.5" ht. T.W beading shall be fixed on border. Top shall be made of 18 mm thick commercial plywood with additional 18 mm thick Ply wood patta of required width on edges with 1.0 mm thick laminate on top of approved shade and supports of the Table shall be made of 2" x 2" T.W. members in a Design as directed. All surfaces not laminated shall be lacquer polished.					
	Exposed edges of Table Top & Horizontal cross patta below top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.					
2[a]	MEETING RM TABLE Size: 7'-0"x3'-6" - 1 no Same as Sr. No. 02 with Provision of POP-UP box & 2 nos Cable Manager on either side of POP-UP box in center of Table top with necessary cutouts in top	1.00	NO			
2[b]	TABLE Size: 6'-0"x2'-6" - 1 no Dining Table	1.00	NO			
3[a]	SIDE CREDENZA & BACK RUNNER Openable shutter with 1.00 mm thick Laminate (approved shades) on Top , front, sides, shutter and 35 mmx6 mm thick Burma Teak beading on Top Edges Polish Finish. Laminate to be provided only on visible surface etc complete as follows. Only Front elevation will be measured for payment	40.00	SQ.MT			

Sr.No.	Description	QTY	Unit	Rate in Figure	Rate in Words	Amount
	Supplying and installation side cabinet for keeping computer and printer of size 1'-4" W, 2'-6"/3'-0"/4'-0"H having openable shutters as directed. Cabinet shall be made from 18 mm thick commercial ply wood with 1.00 mm thick Laminate (approved shades). Back shall be made from 6 mm thick commercial plywood. Openable shutters shall be made from 18 mm thick commercial ply wood with Laminate finished and approved make group lock, handle, hinges, magnet catch. , Rate includes all necessary provisions for installing computers. All the internal surface, back side shall have 0.60 mm thick balacing laminate					
	Exposed edges of Sides, Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.					
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate					
	FINISHING DETAILS IN NUTSHELL:					
	1) Top : Dark Laminate & Burma Teak beading on Edges with polished edge.					
	2) Front Apron & Sides: Frosty White Laminate					
3[b]	P/F ELECTRIC CUB BOARD	6.00	SQMT			
	Providing and fixing Electric cup board using 18 mm thick Bison/Hilux board for inside verticle division, shelves and shutter. Aluminium framing of 50x25x1.20mm thick with 6 mm thick Bison/Hilux board on both side for outer partition with 1.0 mm thick laminate on all exposed surface and polishing/ synthetic enamel paint on all internal surface. Shutter will have approved make lock, handle, hinges, ball catches & S.S Perforated jali etc.complete as directed. Depth of cup board will be around 1'-3". Height of shutter will be maximum 7'-0". Only Front elevation					
3[c]	P/F PANTRY PLATFORM CUB BOARD SHUTTER	2.00	SQMT			
	Providing and fixing cupboard shutters below pantry platform using 1 1/2" x 2 1/2" second grade T.W members for frame, 18 mm Tk plywood with 1.0 mm lamiante for shutters. Providing 1/2" th T.W beading all around shutter. Providing S.S hinges, Handles, stoppers and magnetic catch as directed. All the without lamiante surface shall be polished/ synthetic enamel paint as directed complete.Providing and fixing 0.60 mm thick balancing laminate on internal shutter surface					
3[d]	Overhead storage above pantry Platform	2.00	SQMT			

Sr.No.	Description	QTY	Unit	Rate in Figure	Rate in Words	Amount
	P/F PANTRY PLATFORM- Overhead Storage with Top/Bottom & Front laminate finished, which consist of 18 mm th. Comm. ply shutter with self closing hinges (full oval open) & wood lipping matching with approved laminate on all the edges.. They shall consist of 18 mm th. Comm. Ply top, sides and bottom and 6 mm th. Comm. ply back. 18 mm th. Ply pelmet if specified shall be provided below the storage to house the tube light. All the external surfaces shall be finished with 1.0mm thk. Laminate (suede finish) of approved make.					
	Division of the shutters shall be made equally according to the length of the storage. All internal surfaces shall be painted / French polished including the shutters. Rate shall be inclusive of all necessary approved fittings like hinges(Hafele make), locks(Godrej make/Vijayan), tower bolts and any					
	Note : The pelmet for tube lights (if made) will not be considered as separate item or in the measurements.					
4	P/F LOW HEIGHT BOTH SIDE LAMINATE PARTITION WITH CLEAR FLOAT GLASS / SOLID WITH FLAP DOOR	23.00	SQMT			
	Providing and fixing low height partition using 50mm x25mm x 1.50mm thick Aluminium members maximum in grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply of approved brand on both side of aluminium framing and fixing 1.0 mm thick laminate of approved shade on both sides. Fixing 12mm thick free clear float glass as directed. Applying lacquer polish on exposed steam beach members / edges as directed. Laminate to be provided only on visible surface Providing pinup board of soft board covered with fabric and fixed in partition as per design/instruction complete as directed.					
5	P/F FULL HEIGHT PARTITION BOTH SIDE LAMINATE SOLID/ PARTLY GLAZED WITH DOOR	43.00	SQMT			
	Providing and fixing both sides laminate full height partly glazed partition using 50mm x 25mm x 1.50mm thick Aluminium members in a maximum grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply on both sides,1.0 mm laminate of approved make shall be fixed on MDF / plywood. Providing and fixing 5.0/8.0 mm thick float glass as directed in the partition. Providing and fixing door shutter using 32 mm thick flush shutter both side laminated and fixing 6 mm thick glass with beading patti, 5" Long 3 Nos stainless steel hinges, doorstop shall be provided as directed. Godrej Mortice lock shall be provided in door shutter. All visible members if not laminated shall have lacquer polished as directed.					

Sr.No.	Description	QTY	Unit	Rate in Figure	Rate in Words	Amount
	For purpose of payment partition height up to bottom of false ceiling only shall be measured and paid . No extra payment shall be made for members going up to slab/beam bottom.					
6	Providing and fixing Isolated flush door shutter (Partly Glazed and Partly Laminate) with frame as follows.	3.00	SQMT			
	Providing and fixing 4"x2" steam beach member for frame and Flush door shutter made out of 32 mm thick flush door with 6 mm thick clear float glass vision panel secured with 12 mm thick steam beach beading, 32 x 12 mm thick steam beach periphery patti around shutter edges, 1 mm thick laminate on both sides, 35x12mm thick steam beach stopper patti on frame including 3 Nos 5" long SS hinges with countersunk S S screws, Approved make Dead Lock, S.S Handles,150 mm long Door stoppers, doorstop of approved make etc. All exposed surface /edges not laminated be provided with lacquer polish. Work to be completed as per drawing & instructions					
6[a]	Providing and fixing UPS door shutter with Aluminium Frame and both side Hilux sheet	2.00	SQMT			
	Providing and fixing door shutter made out of 50x25x1.5mm thick aluminium framing at maximum 1'-6" C/C both way with 8 mm thick Hilux Board on both side with painting. Providing 6 mm thick clear float glass vision panel secured with 12 mm thick steam beach beading. Steam beach beading of size 31x 12 mm should be placed around shutter edges, aluminium stoper patti on frame including 3 Nos 5" long SS hinges with countersunk SS screws, Approved make Dead Lock, S.S Handles,Door stoppers, doorstopper to be fixed as per drawing & instructions. All beadings should be polished.					
7	PANELLING WORK					
7[a]	P/F Wall panelling with laminate finishing for wall and Pillar etc	24.00	SQMT			
	Providing and laying panelling on walls & pillars having 12 mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways on wall and pillar etc complete as directed as per design and instruction of Architect.					

Sr.No.	Description	QTY	Unit	Rate in Figure	Rate in Words	Amount
7[b]	Providing and fixing 8mm thick MDF Board exterior grade with jali work with high gloss PU coating over central column having 8mm thick MDF Board Exterior grade covered with 1 mm thick blue glossy laminate fixed on pillar with aluminium framing of 25mm x25mm x1.20 mm thick at maximum 2'-0" c/c bothway as per drawing and direction with all labour and material etc complete (Rate shall be including CNC cutting jali work and 1 mm thick blue glossy laminate behind design jali work as directed)	18.00	SQMT			
7[c]	Providing and fixing Runner Patta 18 mm thick plywood of 6" height with 1.0 mm thick laminate finish above Storage Top / Table Top if required.etc complete as	5.00	SQMT			
7[d]	Creating Box for fixing AC machine and concealing of copper and drain pipe and around front side main entrance door top, jambs using 18 mm thick MR Grade plywood with 1.00 mm Thick Laminate to be fixed over aluminium framing of 25 X 25 X 1.2 mm as per requirement and drawing etc complete as directed.	5.00	SQMT			
8	P/A WALL PAPERS	10.00	SQMT			
	Providing and applying Wall paper approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft					
9	FALSE CEILING WORK					
9[a]	P/F GYPSUM BOARD FALSE CEILING	50.00	SMT			
	Providing and fixing Gypsum board 12.50 mm thick false ceiling in steps and design using Original Indian Gypsum board with original GI sheet section of Gypsteel ULTRA (Gypsteel Ultra shall be used) supporting system in line and level. Finishing the surface and applying 3 coats of Plastic emulsion paint as directed complete. Entire work to be done as per standard specifications of Saint Gobin Gyproc India.					
	After completion of work, certificate from Saint Gobain Gyproc Company shall be submitted along with bill stating that work is satisfactorily completed as per their specification.					
	Note : (1) Rate includes making necessary cut-outs for lighting fixtures (2) Pattas if any shall be measured in SqM and not in Rmt and paid in SqM (3) Only finished visible surface area shall be measured for payment.					
9[b]	Providing and Fixing of Armstrong Mineral Fibre Accoustical Suspended ceiling system with FINE FISSURED (MICRO LOCK) EDGE TILES With Armstrong Silhouette Exposed Grid	150.00	SMT			

Sr.No.	Description	QTY	Unit	Rate in Figure	Rate in Words	Amount
	Using Silhouette Grid with Fine Fissured microlook Edge Tiles. With necessary Angles at junctions as per company specifications as directed complete. Rate includes necessary cut outs for A/C Grills, diffusers light fixtures complete as directed. Cutout for light and Diffusers will be deducted from area. Only Tiles cost will be deducted for payment purpose					
	After completion of work, certificate from Company to be obtained and submitted with bill that work is carried out as per their specifications					
10	SOFT BOARD	1.00	SQMT			
	Providing & fixing soft board for pin up using moulded Steam beach frame of 1" x 1/2" with 6 mm thick commercial plywood on back side and 12mm th soft board on front covered with cloth of selected design of Basic rate of Rs. 150 per Rmt. Steam beach member shall have lacquer polish as directed.					
11	Supplying and fixing Roller Blind Blackout of approved make with selected fabric of approved design and shade. (Basic Price of Rs 135=00 Per Sq.Ft Including GST)	20.00	SQMT			
12	Providing and Fixing Frosted polyster film of 3M (Scotchcal 7725 - 324) or equivalent make over glass surface as per drawing & direction with all labour & materials to the satisfaction of the Architect/Bank as per manufacturer's specification. No deduction will be made for any cutting in the film.	12.00	SQMT			
13	Providing and fixing "Dorma/Ozone/Godrej " or equivalent make door closure.	3.00	NO			
14	P&M Waiting sofa with 19mm m.r. grade block board with T.W. Frameing inside, imported elastic, 40 density foam sheet for Seat & 32 density foam sheet for back, with full covering colth /art. lather(basic rate 600 rs./mt.) with 3" SS legs ,exposed wood shell be painted / polished com.	1.80	RMT			
	FURNISHING WORK - TOTAL AMOUNT					
	<u>+ GST AS APPLICABLE</u>					
Note:						
[a]	In all furniture work, contractor shall make necessary cutout in panelling/partitions / wooden members to facilitate electrical/data cabelling and No extra amount shall be paid for this					
[b]	All internal surface (non visible surfaces) shall be provided with the 0.60 mm thick balacing laminate of aproved make & shade in the all Counters/Tables/ Credenza,Storage Cup Board etc.					